
Metashape Python Reference

Release 1.6.4

Agisoft LLC

Aug 08, 2020

CONTENTS

1 Overview	3
2 Application Modules	5
3 Python API Change Log	181
Python Module Index	207

Copyright (c) 2020 Agisoft LLC.

OVERVIEW

1.1 Introduction to Python scripting in Metashape Professional

This API is in development and will be extended in the future Metashape releases.

Note: Python scripting is supported only in Metashape Professional edition.

Metashape Professional uses Python 3.5 as a scripting engine.

Python commands and scripts can be executed in Metashape in one of the following ways:

- From Metashape “Console” pane using it as standard Python console.
- From the “Tools” menu using “Run script...” command.
- From command line using “-r” argument and passing the path to the script as an argument.

The following Metashape functionality can be accessed from Python scripts:

- Open/save/create Metashape projects.
- Add/remove chunks, cameras, markers.
- Add/modify camera calibrations, ground control data, assign geographic projections and coordinates.
- Perform processing steps (align photos, build dense cloud, build mesh, texture, decimate model, etc...).
- Export processing results (models, textures, orthophotos, DEMs).
- Access data of generated models, point clouds, images.
- Start and control network processing tasks.

APPLICATION MODULES

Metashape module provides access to the core processing functionality, including support for inspection and manipulation with project data.

The main component of the module is a Document class, which represents a Metashape project. Multiple Document instances can be created simultaneously if needed. Besides that a currently opened project in the application can be accessed using `Metashape.app.document` property.

The following example performs main processing steps on existing project and saves back the results:

```
>>> import Metashape
>>> doc = Metashape.app.document
>>> doc.open("project.psz")
>>> chunk = doc.chunk
>>> chunk.matchPhotos(downscale=1, generic_preselection=True, reference_
↳preselection=False)
>>> chunk.alignCameras()
>>> chunk.buildDepthMaps(downscale=4, filter_mode=Metashape.AggressiveFiltering)
>>> chunk.buildDenseCloud()
>>> chunk.buildModel(surface_type=Metashape.Arbitrary, interpolation=Metashape.
↳EnabledInterpolation)
>>> chunk.buildUV(mapping_mode=Metashape.GenericMapping)
>>> chunk.buildTexture(blending_mode=Metashape.MosaicBlending, texture_size=4096)
>>> doc.save()
```

class `Metashape.Antenna`
GPS antenna position relative to camera.

copy()
Return a copy of the object.
Returns A copy of the object.

Return type *Antenna*

fixed
Fix antenna flag.

Type `bool`

location
Antenna coordinates.

Type *Vector*

location_acc
Antenna location accuracy.

Type *Vector*

location_covariance
Antenna location covariance.

Type *Matrix*

location_ref
Antenna location reference.

Type *Vector*

rotation
Antenna rotation angles.

Type *Vector*

rotation_acc
Antenna rotation accuracy.

Type *Vector*

rotation_covariance
Antenna rotation covariance.

Type *Matrix*

rotation_ref
Antenna rotation reference.

Type *Vector*

class `Metashape.Application`

Application class provides access to several global application attributes, such as document currently loaded in the user interface, software version and GPU device configuration. It also contains helper routines to prompt the user to input various types of parameters, like displaying a file selection dialog or coordinate system selection dialog among others.

An instance of Application object can be accessed using `Metashape.app` attribute, so there is usually no need to create additional instances in the user code.

The following example prompts the user to select a new coordinate system, applies it to the active chunk and saves the project under the user selected file name:

```
>>> import Metashape
>>> doc = Metashape.app.document
>>> crs = Metashape.app.getCoordinateSystem("Select Coordinate System", doc.chunk.
↳ crs)
>>> doc.chunk.crs = crs
>>> path = Metashape.app.getSaveFileName("Save Project As")
>>> try:
...     doc.save(path)
... except RuntimeError:
...     Metashape.app.messageBox("Can't save project")
```

class `ConsolePane`
ConsolePane class provides access to the console pane

clear ()
Clear console pane.

contents
Console pane contents.
Type *string*

class `Application.ModelView`

ModelView class provides access to the model view

class `DenseCloudViewMode`

Dense cloud view mode in [`DenseCloudViewColor`, `DenseCloudViewClasses`, `DenseCloudViewConfidence`]

class `Application.ModelView.ModelViewMode`

Model view mode in [`ModelViewShaded`, `ModelViewSolid`, `ModelViewWireframe`, `ModelViewConfidence`, `ModelViewTextured`]

class `Application.ModelView.PointCloudViewMode`

Point cloud view mode in [`PointCloudViewColor`, `PointCloudViewVariance`]

class `Application.ModelView.TiledModelViewMode`

Tiled model view mode in [`TiledModelViewTextured`, `TiledModelViewSolid`, `TiledModelViewWireframe`]

`Application.ModelView.captureView` (`width`][, `height`][, `transparent`][, `hide_items`])

Capture image from model view.

Parameters

- **width** (*int*) – Image width.
- **height** (*int*) – Image height.
- **transparent** (*bool*) – Sets transparent background.
- **hide_items** (*bool*) – Hides all items.

Returns Captured image.

Return type *Image*

`Application.ModelView.dense_cloud_view_mode`

Dense cloud view mode.

Type *DenseCloudViewMode*

`Application.ModelView.model_view_mode`

Model view mode.

Type *ModelViewMode*

`Application.ModelView.point_cloud_view_mode`

Point cloud view mode.

Type *PointCloudViewMode*

`Application.ModelView.texture_view_mode`

Texture view mode.

Type *TextureViewMode*

`Application.ModelView.tiled_model_view_mode`

Tiled model view mode.

Type *TiledModelViewMode*

`Application.ModelView.view_mode`

View mode.

Type *DataSource*

`Application.ModelView.viewpoint`

Viewpoint in the model view.

Type *Viewpoint*

class `Application.OrthoView`

OrthoView class provides access to the ortho view

captureView (*[width]* [*, height*] [*, transparent*] [*, hide_items*])

Capture image from ortho view.

Parameters

- **width** (*int*) – Image width.
- **height** (*int*) – Image height.
- **transparent** (*bool*) – Sets transparent background.
- **hide_items** (*bool*) – Hides all items.

Returns Captured image.

Return type *Image*

view_mode

View mode.

Type *DataSource*

class *Application*.**PhotosPane**

PhotosPane class provides access to the photos pane

resetFilter ()

Reset photos pane filter.

setFilter (*items*)

Set photos pane filter.

Parameters **items** (list of *Camera* or *Marker*) – filter to apply.

class *Application*.**Settings**

PySettings()

Application settings

load ()

Load settings from disk.

log_enable

Enable writing log to file.

Type *bool*

log_path

Log file path.

Type *string*

network_enable

Network processing enabled flag.

Type *bool*

network_host

Network server host name.

Type *string*

network_path

Network data root path.

Type *string*

network_port

Network server control port.

Type *int*

save ()

Save settings on disk.

setValue (*key, value*)

Set settings value. :arg key: Key. :type key: string :arg value: Value. :type value: object

value (*key*)

Return settings value. :arg key: Key. :type key: string :return: Settings value. :rtype: object

`Application.activated`

Metashape activation status.

Type bool

`Application.addItem` (*label*, *func* [, *shortcut*] [, *icon*])

Create a new menu entry.

Parameters

- **label** (*string*) – Menu item label.
- **func** (*function*) – Function to be called.
- **shortcut** (*string*) – Keyboard shortcut.
- **icon** (*string*) – Icon.

`Application.addMenuSeparator` (*label*)

Add menu separator.

Parameters **label** (*string*) – Menu label.

`Application.console_pane`

Console pane.

Type ConsolePane

`Application.cpu_enable`

Use CPU when GPU is active.

Type bool

`Application.document`

Main application document object.

Type *Document*

`Application.enumGPUDevices` ()

Enumerate installed GPU devices.

Returns A list of devices.

Return type list

`Application.getBool` (*label*='')

Prompt user for the boolean value.

Parameters **label** (*string*) – Optional text label for the dialog.

Returns Boolean value selected by the user.

Return type bool

`Application.getCoordinateSystem` ([*label*] [, *value*])

Prompt user for coordinate system.

Parameters

- **label** (*string*) – Optional text label for the dialog.
- **value** (*CoordinateSystem*) – Default value.

Returns Selected coordinate system. If the dialog was cancelled, None is returned.

Return type *CoordinateSystem*

`Application.getExistingDirectory([hint])`

Prompt user for the existing folder.

Parameters `hint` (*string*) – Optional text label for the dialog.

Returns Path to the folder selected. If the input was cancelled, empty string is returned.

Return type *string*

`Application.getFloat(label='', value=0)`

Prompt user for the floating point value.

Parameters

- **label** (*string*) – Optional text label for the dialog.
- **value** (*float*) – Default value.

Returns Floating point value entered by the user.

Return type *float*

`Application.getInt(label='', value=0)`

Prompt user for the integer value.

Parameters

- **label** (*string*) – Optional text label for the dialog.
- **value** (*int*) – Default value.

Returns Integer value entered by the user.

Return type *int*

`Application.getOpenFileName([hint][, filter])`

Prompt user for the existing file.

Parameters

- **hint** (*string*) – Optional text label for the dialog.
- **filter** (*string*) – Optional file filter, e.g. “Text file (.txt)” or “.txt”. Multiple filters are separated with “;”.

Returns Path to the file selected. If the input was cancelled, empty string is returned.

Return type *string*

`Application.getOpenFileNames([hint][, filter])`

Prompt user for one or more existing files.

Parameters

- **hint** (*string*) – Optional text label for the dialog.
- **filter** (*string*) – Optional file filter, e.g. “Text file (.txt)” or “.txt”. Multiple filters are separated with “;”.

Returns List of file paths selected by the user. If the input was cancelled, empty list is returned.

Return type *list*

`Application.getSaveFileName([hint][, filter])`

Prompt user for the file. The file does not have to exist.

Parameters

- **hint** (*string*) – Optional text label for the dialog.
- **filter** (*string*) – Optional file filter, e.g. “Text file (.txt)” or “.txt”. Multiple filters are separated with “;”.

Returns Path to the file selected. If the input was cancelled, empty string is returned.

Return type string

`Application.getString (label='', value='')`

Prompt user for the string value.

Parameters

- **label** (*string*) – Optional text label for the dialog.
- **value** (*string*) – Default value.

Returns String entered by the user.

Return type string

`Application.gpu_mask`

GPU device bit mask: 1 - use device, 0 - do not use (i.e. value 5 enables device number 0 and 2).

Type int

`Application.messageBox (message)`

Display message box to the user.

Parameters **message** (*string*) – Text message to be displayed.

`Application.model_view`

Model view.

Type ModelView

`Application.ortho_view`

Ortho view.

Type OrthoView

`Application.photos_pane`

Photos pane.

Type PhotosPane

`Application.quit ()`

Exit application.

`Application.releaseFreeMemory ()`

Call `malloc_trim` on Linux (does nothing on other OS).

`Application.removeMenuItem (label)`

Remove menu entry with given label (if exists). If there are multiple entries with given label - all of them will be removed.

Parameters **label** (*string*) – Menu item label.

`Application.settings`

Application settings.

Type Settings

`Application.title`

Application name.

Type string

`Application.update()`
Update user interface during long operations.

`Application.version`
Metashape version.

Type string

class `Metashape.BBox`
Axis aligned bounding box

`copy()`
Return a copy of the object.

Returns A copy of the object.

Return type *BBox*

max
Maximum bounding box extent.

Type *Vector*

min
Minimum bounding box extent.

Type *Vector*

size
Bounding box dimension.

Type int

class `Metashape.BlendingMode`
Blending mode in [AverageBlending, MosaicBlending, MinBlending, MaxBlending, DisabledBlending]

class `Metashape.Calibration`
Calibration object contains camera calibration information including image size, focal length, principal point coordinates and distortion coefficients.

b1
Affinity.

Type float

b2
Non-orthogonality.

Type float

`copy()`
Return a copy of the object.

Returns A copy of the object.

Return type *Calibration*

covariance_matrix
Covariance matrix.

Type *Matrix*

covariance_params
Covariance matrix parameters.

Type list of string

cx

Principal point X coordinate.

Type float

cy

Principal point Y coordinate.

Type float

error (*point, proj*)

Return projection error.

Parameters

- **point** (*Vector*) – Coordinates of the point to be projected.
- **proj** (*Vector*) – Pixel coordinates of the point.

Returns 2D projection error.

Return type *Vector*

f

Focal length.

Type float

height

Image height.

Type int

k1

Radial distortion coefficient K1.

Type float

k2

Radial distortion coefficient K2.

Type float

k3

Radial distortion coefficient K3.

Type float

k4

Radial distortion coefficient K4.

Type float

load (*path, format=CalibrationFormatXML*)

Loads calibration from file.

Parameters

- **path** (*string*) – path to calibration file
- **format** (*CalibrationFormat*) – Calibration format.

p1

Decentering distortion coefficient P1.

Type float

- p2**
Decentering distortion coefficient P2.
Type float
- p3**
Decentering distortion coefficient P3.
Type float
- p4**
Decentering distortion coefficient P4.
Type float
- project** (*point*)
Return projected pixel coordinates of the point.
Parameters **point** (*Vector*) – Coordinates of the point to be projected.
Returns 2D projected point coordinates.
Return type *Vector*
- rpc**
RPC model.
Type *RPCModel*
- save** (*path*, *format=CalibrationFormatXML* [, *label*] [, *pixel_size*] [, *focal_length*], *cx = 0*, *cy = 0*)
Saves calibration to file.
Parameters
- **path** (*string*) – path to calibration file
 - **format** (*CalibrationFormat*) – Calibration format.
 - **label** (*string*) – Calibration label used in Australis, CalibCam and CalCam formats.
 - **pixel_size** (*Vector*) – Pixel size in mm used to convert normalized calibration coefficients to Australis and CalibCam coefficients.
 - **focal_length** (*float*) – Focal length (Grid calibration format only).
 - **cx** (*float*) – X principal point coordinate (Grid calibration format only).
 - **cy** (*float*) – Y principal point coordinate (Grid calibration format only).
- type**
Camera model.
Type *Sensor.Type*
- unproject** (*point*)
Return direction corresponding to the image point.
Parameters **point** (*Vector*) – Pixel coordinates of the point.
Returns 3D vector in the camera coordinate system.
Return type *Vector*
- width**
Image width.
Type int

class Metashape.CalibrationFormat

Calibration format in [CalibrationFormatXML, CalibrationFormatAustralis, CalibrationFormatAustralisV7, CalibrationFormatPhotoModeler, CalibrationFormatCalibCam, CalibrationFormatCalCam, CalibrationFormatInpho, CalibrationFormatUSGS, CalibrationFormatPix4D, CalibrationFormatOpenCV, CalibrationFormatPhotomod, CalibrationFormatGrid]

class Metashape.Camera

Camera instance

```
>>> import Metashape
>>> chunk = Metashape.app.document.addChunk()
>>> chunk.addPhotos(["IMG_0001.jpg", "IMG_0002.jpg"])
>>> camera = chunk.cameras[0]
>>> camera.photo.meta["Exif/FocalLength"]
'18'
```

The following example describes how to create multispectral camera layout:

```
>>> import Metashape
>>> doc = Metashape.app.document
>>> chunk = doc.chunk
>>> rgb = ["RGB_0001.JPG", "RGB_0002.JPG", "RGB_0003.JPG"]
>>> nir = ["NIR_0001.JPG", "NIR_0002.JPG", "NIR_0003.JPG"]
>>> images = [[rgb[0], nir[0]], [rgb[1], nir[1]], [rgb[2], nir[2]]]
>>> chunk.addPhotos(images, Metashape.MultiplaneLayout)
```

class Reference

Camera reference data.

accuracy

Camera location accuracy.

Type *Vector*

enabled

Location enabled flag.

Type bool

location

Camera coordinates.

Type *Vector*

location_accuracy

Camera location accuracy.

Type *Vector*

location_enabled

Location enabled flag.

Type bool

rotation

Camera rotation angles.

Type *Vector*

rotation_accuracy

Camera rotation accuracy.

Type *Vector*

rotation_enabled

Rotation enabled flag.

Type bool

class Camera.Type

Camera type in [Regular, Keyframe]

Camera.calibration

Adjusted camera calibration including photo-invariant parameters.

Type *Calibration*

Camera.center

Camera station coordinates for the photo in the chunk coordinate system.

Type *Vector*

Camera.chunk

Chunk the camera belongs to.

Type *Chunk*

Camera.enabled

Enables/disables the photo.

Type bool

Camera.error (*point*, *proj*)

Returns projection error.

Parameters

- **point** (*Vector*) – Coordinates of the point to be projected.
- **proj** (*Vector*) – Pixel coordinates of the point.

Returns 2D projection error.

Return type *Vector*

Camera.frames

Camera frames.

Type list of *Camera*

Camera.group

Camera group.

Type *CameraGroup*

Camera.image ()

Returns image data.

Returns Image data.

Return type *Image*

Camera.key

Camera identifier.

Type int

Camera.label

Camera label.

Type string

Camera.layer_index

Camera layer index.

Type int

Camera.location_covariance

Camera location covariance.

Type *Matrix*

Camera.mask

Camera mask.

Type *Mask*

Camera.master

Master camera.

Type *Camera*

Camera.meta

Camera meta data.

Type *MetaData*

Camera.open (*path* [, *layer*])

Loads specified image file.

Parameters

- **path** (*string*) – Path to the image file to be loaded.
- **layer** (*int*) – Optional layer index in case of multipage files.

Camera.orientation

Image orientation (1 - normal, 6 - 90 degree, 3 - 180 degree, 8 - 270 degree).

Type *int*

Camera.photo

Camera photo.

Type *Photo*

Camera.planes

Camera planes.

Type list of *Camera*

Camera.project (*point*)

Returns coordinates of the point projection on the photo.

Parameters **point** (*Vector*) – Coordinates of the point to be projected.

Returns 2D point coordinates.

Return type *Vector*

Camera.reference

Camera reference data.

Type *CameraReference*

Camera.rotation_covariance

Camera rotation covariance.

Type *Matrix*

Camera.selected

Selects/deselects the photo.

Type *bool*

Camera.**sensor**
Camera sensor.

Type *Sensor*

Camera.**shutter**
Camera shutter.

Type *Shutter*

Camera.**thumbnail**
Camera thumbnail.

Type *Thumbnail*

Camera.**transform**
4x4 matrix describing photo location in the chunk coordinate system.

Type *Matrix*

Camera.**type**
Camera type.

Type *Camera.Type*

Camera.**unproject** (*point*)
Returns coordinates of the point which will have specified projected coordinates.

Parameters **point** (*Vector*) – Projection coordinates.

Returns 3D point coordinates.

Return type *Vector*

Camera.**vignetting**
Vignetting for each band.

Type list of *Vignetting*

class Metashape.**CameraGroup**

CameraGroup objects define groups of multiple cameras. The grouping is established by assignment of a CameraGroup instance to the Camera.group attribute of participating cameras.

The type attribute of CameraGroup instances defines the effect of such grouping on processing results and can be set to Folder (no effect) or Station (coincident projection centers).

class **Type**

Camera group type in [Folder, Station]

CameraGroup.**label**
Camera group label.

Type string

CameraGroup.**selected**
Current selection state.

Type bool

CameraGroup.**type**
Camera group type.

Type *CameraGroup.Type*

class Metashape.**CameraTrack**

Camera track.

chunk

Chunk the camera track belongs to.

Type *Chunk*

duration

Animation duration.

Type float

field_of_view

Vertical field of view in degrees.

Type float

keyframes

Camera track keyframes.

Type list of *Camera*

label

Animation label.

Type string

load (*path* [, *projection*])

Load camera track from file.

Parameters

- **path** (*string*) – Path to camera track file
- **projection** (*CoordinateSystem*) – Camera track coordinate system.

meta

Camera track meta data.

Type *MetaData*

save (*path* [, *projection*])

Save camera track to file.

Parameters

- **path** (*string*) – Path to camera track file
- **projection** (*CoordinateSystem*) – Camera track coordinate system.

class *Metashape*.**CamerasFormat**

Camera orientation format in [CamerasFormatXML, CamerasFormatCHAN, CamerasFormatBoujou, CamerasFormatBundler, CamerasFormatOPK, CamerasFormatPATB, CamerasFormatBINGO, CamerasFormatORIMA, CamerasFormatAeroSys, CamerasFormatInpho, CamerasFormatSummit, CamerasFormatBlocksExchange, CamerasFormatRZML, CamerasFormatVisionMap, CamerasFormatABC, CamerasFormatFBX, CamerasFormatNVM]

class *Metashape*.**Chunk**

A Chunk object:

- provides access to all chunk components (sensors, cameras, camera groups, markers, scale bars)
- contains data inherent to individual frames (point cloud, model, etc)
- implements processing methods (matchPhotos, alignCameras, buildDenseCloud, buildModel, etc)
- provides access to other chunk attributes (transformation matrix, coordinate system, meta-data, etc..)

New components can be created using corresponding addXXX methods (addSensor, addCamera, addCameraGroup, addMarker, addScalebar, addFrame). Removal of components is supported by a single remove method, which can accept lists of various component types.

In case of multi-frame chunks the Chunk object contains an additional reference to the particular chunk frame, initialized to the current frame by default. Various methods that work on a per frame basis (matchPhotos, buildModel, etc) are applied to this particular frame. A frames attribute can be used to obtain a list of Chunk objects that reference all available frames.

The following example performs image matching and alignment for the active chunk:

```
>>> import Metashape
>>> chunk = Metashape.app.document.chunk
>>> for frame in chunk.frames:
...     frame.matchPhotos(downscale=1)
>>> chunk.alignCameras()
```

addCamera ([*sensor*])

Add new camera to the chunk.

Parameters *sensor* (*Sensor*) – Sensor to be assigned to this camera.

Returns Created camera.

Return type *Camera*

addCameraGroup ()

Add new camera group to the chunk.

Returns Created camera group.

Return type *CameraGroup*

addCameraTrack ()

Add new camera track to the chunk.

Returns Created camera track.

Return type *CameraTrack*

addDenseCloud ()

Add new dense cloud to the chunk.

Returns Created dense cloud.

Return type *DenseCloud*

addDepthMaps ()

Add new depth maps set to the chunk.

Returns Created depth maps set.

Return type *DepthMaps*

addElevation ()

Add new elevation model to the chunk.

Returns Created elevation model.

Return type *Elevation*

addFrame ()

Add new frame to the chunk.

Returns Created frame.

Return type `Frame`

addFrames (`[chunk]` [, `frames`], `copy_depth_maps=True`, `copy_dense_cloud=True`,
`copy_model=True`, `copy_tiled_model=True`, `copy_elevation=True`,
`copy_orthomosaic=True` [, `progress`])

Add frames from specified chunk.

Parameters

- **chunk** (`int`) – Chunk to copy frames from.
- **frames** (`list of int`) – List of frame keys to copy.
- **copy_depth_maps** (`bool`) – Copy depth maps.
- **copy_dense_cloud** (`bool`) – Copy dense cloud.
- **copy_model** (`bool`) – Copy model.
- **copy_tiled_model** (`bool`) – Copy tiled model.
- **copy_elevation** (`bool`) – Copy DEM.
- **copy_orthomosaic** (`bool`) – Copy orthomosaic.
- **progress** (`Callable[[float], None]`) – Progress callback.

addMarker (`[point]`, `visibility=False`)

Add new marker to the chunk.

Parameters

- **point** (`Vector`) – Point to initialize marker projections.
- **visibility** (`bool`) – Enables visibility check during projection assignment.

Returns Created marker.

Return type `Marker`

addMarkerGroup ()

Add new marker group to the chunk.

Returns Created marker group.

Return type `MarkerGroup`

addModel ()

Add new model to the chunk.

Returns Created model.

Return type `Model`

addOrthomosaic ()

Add new orthomosaic to the chunk.

Returns Created orthomosaic.

Return type `Orthomosaic`

addPhotos (`[filenames]` [, `filegroups`], `layout=UndefinedLayout` [, `group`], `strip_extensions=True`,
`load_reference=True`, `load_xmp_calibration=True`, `load_xmp_orientation=True`,
`load_xmp_accuracy=False`, `load_xmp_antenna=True`, `load_rpc_txt=False` [, `progress`
])

Add a list of photos to the chunk.

Parameters

- **filenames** (*list of string*) – List of files to add.
- **filegroups** (*list of int*) – List of file groups.
- **layout** (*ImageLayout*) – Image layout.
- **group** (*int*) – Camera group key.
- **strip_extensions** (*bool*) – Strip file extensions from camera labels.
- **load_reference** (*bool*) – Load reference coordinates.
- **load_xmp_calibration** (*bool*) – Load calibration from XMP meta data.
- **load_xmp_orientation** (*bool*) – Load orientation from XMP meta data.
- **load_xmp_accuracy** (*bool*) – Load accuracy from XMP meta data.
- **load_xmp_antenna** (*bool*) – Load GPS/INS offset from XMP meta data.
- **load_rpc_txt** (*bool*) – Load satellite RPC data from auxiliary TXT files.
- **progress** (*Callable[[float], None]*) – Progress callback.

addScalebar (*point1, point2*)

Add new scale bar to the chunk.

Parameters

- **point1** (*Marker* or *Camera*) – First endpoint.
- **point2** – Second endpoint.

Returns Created scale bar.

Return type *Scalebar*

addScalebarGroup ()

Add new scale bar group to the chunk.

Returns Created scale bar group.

Return type *ScalebarGroup*

addSensor (*[source]*)

Add new sensor to the chunk.

Parameters **source** (*Sensor*) – Sensor to copy parameters from.

Returns Created sensor.

Return type *Sensor*

addTiledModel ()

Add new tiled model to the chunk.

Returns Created tiled model.

Return type *TiledModel*

alignCameras (*[cameras]*, *min_image=2*, *adaptive_fitting=False*, *reset_alignment=False*, *subdivide_task=True*, *[progress]*)

Perform photo alignment for the chunk.

Parameters

- **cameras** (*list of int*) – List of cameras to align.
- **min_image** (*int*) – Minimum number of point projections.

- **adaptive_fitting** (*bool*) – Enable adaptive fitting of distortion coefficients.
- **reset_alignment** (*bool*) – Reset current alignment.
- **subdivide_task** (*bool*) – Enable fine-level task subdivision.
- **progress** (*Callable[[float], None]*) – Progress callback.

analyzePhotos (*[cameras]*, *filter_mask=False*, *[progress]*)
Estimate image quality.

Parameters

- **cameras** (*list of int*) – List of cameras to be analyzed.
- **filter_mask** (*bool*) – Constrain analyzed image region by mask.
- **progress** (*Callable[[float], None]*) – Progress callback.

buildContours (*source_data=ElevationData*, *interval=1*, *min_value=-1e+10*, *max_value=1e+10*,
prevent_intersections=False, *[progress]*)
Build contours for the chunk.

Parameters

- **source_data** (*DataSource*) – Source data for contour generation.
- **interval** (*float*) – Contour interval.
- **min_value** (*float*) – Minimum value of contour range.
- **max_value** (*float*) – Maximum value of contour range.
- **prevent_intersections** (*bool*) – Prevent contour intersections.
- **progress** (*Callable[[float], None]*) – Progress callback.

buildDem (*source_data=DenseCloudData*, *interpolation=EnabledInterpolation*, *[projection]*, *[region]*,
[classes], *flip_x=False*, *flip_y=False*, *flip_z=False*, *resolution=0*, *subdivide_task=True*,
workitem_size_tiles=10, *max_workgroup_size=100*, *[progress]*)
Build elevation model for the chunk.

Parameters

- **source_data** (*DataSource*) – Selects between dense point cloud and sparse point cloud.
- **interpolation** (*Interpolation*) – Interpolation mode.
- **projection** (*OrthoProjection*) – Output projection.
- **region** (*BBox*) – Region to be processed.
- **classes** (*list of int*) – List of dense point classes to be used for surface extraction.
- **flip_x** (*bool*) – Flip X axis direction.
- **flip_y** (*bool*) – Flip Y axis direction.
- **flip_z** (*bool*) – Flip Z axis direction.
- **resolution** (*float*) – Output resolution in meters.
- **subdivide_task** (*bool*) – Enable fine-level task subdivision.
- **workitem_size_tiles** (*int*) – Number of tiles in a workitem.
- **max_workgroup_size** (*int*) – Maximum workgroup size.
- **progress** (*Callable[[float], None]*) – Progress callback.

```
buildDenseCloud (point_colors=True, point_confidence=False, keep_depth=True,  
max_neighbors=100, subdivide_task=True, workitem_size_cameras=20,  
max_workgroup_size=100[, progress ])
```

Generate dense cloud for the chunk.

Parameters

- **point_colors** (*bool*) – Enable point colors calculation.
- **point_confidence** (*bool*) – Enable point confidence calculation.
- **keep_depth** (*bool*) – Enable store depth maps option.
- **max_neighbors** (*int*) – Maximum number of neighbor images to use for depth map filtering.
- **subdivide_task** (*bool*) – Enable fine-level task subdivision.
- **workitem_size_cameras** (*int*) – Number of cameras in a workitem.
- **max_workgroup_size** (*int*) – Maximum workgroup size.
- **progress** (*Callable[[float], None]*) – Progress callback.

```
buildDepthMaps (downscale=4, filter_mode=MildFiltering[, cameras ], reuse_depth=False,  
max_neighbors=-1, subdivide_task=True, workitem_size_cameras=20,  
max_workgroup_size=100[, progress ])
```

Generate depth maps for the chunk.

Parameters

- **downscale** (*int*) – Depth map quality.
- **filter_mode** (*FilterMode*) – Depth map filtering mode.
- **cameras** (*list of int*) – List of cameras to process.
- **reuse_depth** (*bool*) – Enable reuse depth maps option.
- **max_neighbors** (*int*) – Maximum number of neighbor images to use for depth map generation.
- **subdivide_task** (*bool*) – Enable fine-level task subdivision.
- **workitem_size_cameras** (*int*) – Number of cameras in a workitem.
- **max_workgroup_size** (*int*) – Maximum workgroup size.
- **progress** (*Callable[[float], None]*) – Progress callback.

```
buildModel (surface_type=Arbitrary, interpolation=EnabledInterpolation,  
face_count=HighFaceCount, face_count_custom=200000,  
source_data=DenseCloudData, vertex_colors=True, vertex_confidence=True, volu-  
metric_masks=False, keep_depth=True, trimming_radius=10[, cameras ][, classes  
], subdivide_task=True, workitem_size_cameras=20, max_workgroup_size=100[,  
progress ])
```

Generate model for the chunk frame.

Parameters

- **surface_type** (*SurfaceType*) – Type of object to be reconstructed.
- **interpolation** (*Interpolation*) – Interpolation mode.
- **face_count** (*FaceCount*) – Target face count.
- **face_count_custom** (*int*) – Custom face count.

- **source_data** (*DataSource*) – Selects between dense point cloud, sparse point cloud and depth maps.
- **vertex_colors** (*bool*) – Enable vertex colors calculation.
- **vertex_confidence** (*bool*) – Enable vertex confidence calculation.
- **volumetric_masks** (*bool*) – Enable strict volumetric masking.
- **keep_depth** (*bool*) – Enable store depth maps option.
- **trimming_radius** (*int*) – Trimming radius (no trimming if zero).
- **cameras** (*list of int*) – List of cameras to process.
- **classes** (*list of int*) – List of dense point classes to be used for surface extraction.
- **subdivide_task** (*bool*) – Enable fine-level task subdivision.
- **workitem_size_cameras** (*int*) – Number of cameras in a workitem.
- **max_workgroup_size** (*int*) – Maximum workgroup size.
- **progress** (*Callable[[float], None]*) – Progress callback.

buildOrthomosaic (*surface_data=ModelData, blending_mode=MosaicBlending, fill_holes=True, cull_faces=False, refine_seamlines=False*[, *projection*][, *region*], *resolution=0, resolution_x=0, resolution_y=0, flip_x=False, flip_y=False, flip_z=False, subdivide_task=True, workitem_size_cameras=20, workitem_size_tiles=10, max_workgroup_size=100*[, *progress*])

Build orthomosaic for the chunk.

Parameters

- **surface_data** (*DataSource*) – Orthorectification surface.
- **blending_mode** (*BlendingMode*) – Orthophoto blending mode.
- **fill_holes** (*bool*) – Enable hole filling.
- **cull_faces** (*bool*) – Enable back-face culling.
- **refine_seamlines** (*bool*) – Refine seamlines based on image content.
- **projection** (*OrthoProjection*) – Output projection.
- **region** (*BBox*) – Region to be processed.
- **resolution** (*float*) – Pixel size in meters.
- **resolution_x** (*float*) – Pixel size in the X dimension in projected units.
- **resolution_y** (*float*) – Pixel size in the Y dimension in projected units.
- **flip_x** (*bool*) – Flip X axis direction.
- **flip_y** (*bool*) – Flip Y axis direction.
- **flip_z** (*bool*) – Flip Z axis direction.
- **subdivide_task** (*bool*) – Enable fine-level task subdivision.
- **workitem_size_cameras** (*int*) – Number of cameras in a workitem.
- **workitem_size_tiles** (*int*) – Number of tiles in a workitem.
- **max_workgroup_size** (*int*) – Maximum workgroup size.
- **progress** (*Callable[[float], None]*) – Progress callback.

buildSeamlines (*epsilon*=1.5[, *progress*])
Generate shapes for orthomosaic seamlines.

Parameters

- **epsilon** (*float*) – Contour simplification threshold.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

buildTexture (*blending_mode*=*MosaicBlending*, *texture_size*=4096, *fill_holes*=*True*, *ghosting_filter*=*True*[, *cameras*], *texture_type*=*DiffuseMap*[, *source_model*], *transfer_texture*=*True*[, *progress*])
Generate texture for the chunk.

Parameters

- **blending_mode** (*BlendingMode*) – Texture blending mode.
- **texture_size** (*int*) – Texture page size.
- **fill_holes** (*bool*) – Enable hole filling.
- **ghosting_filter** (*bool*) – Enable ghosting filter.
- **cameras** (*list of int*) – A list of cameras to be used for texturing.
- **texture_type** (*Model.TextureType*) – Texture type.
- **source_model** (*int*) – Source model.
- **transfer_texture** (*bool*) – Transfer texture.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

buildTiledModel (*pixel_size*=0, *tile_size*=256, *source_data*=*DenseCloudData*, *face_count*=4000, *ghosting_filter*=*False*, *transfer_texture*=*False*, *keep_depth*=*True*[, *classes*], *subdivide_task*=*True*, *workitem_size_cameras*=20, *max_workgroup_size*=100[, *progress*])
Build tiled model for the chunk.

Parameters

- **pixel_size** (*float*) – Target model resolution in meters.
- **tile_size** (*int*) – Size of tiles in pixels.
- **source_data** (*DataSource*) – Selects between dense point cloud and mesh.
- **face_count** (*int*) – Number of faces per megapixel of texture resolution.
- **ghosting_filter** (*bool*) – Enable ghosting filter.
- **transfer_texture** (*bool*) – Transfer source model texture to tiled model.
- **keep_depth** (*bool*) – Enable store depth maps option.
- **classes** (*list of int*) – List of dense point classes to be used for surface extraction.
- **subdivide_task** (*bool*) – Enable fine-level task subdivision.
- **workitem_size_cameras** (*int*) – Number of cameras in a workitem.
- **max_workgroup_size** (*int*) – Maximum workgroup size.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

buildUV (*mapping_mode*=*GenericMapping*, *page_count*=1, *texture_size*=4096[, *camera*][, *progress*])
Generate uv mapping for the model.

Parameters

- **mapping_mode** (*MappingMode*) – Texture mapping mode.
- **page_count** (*int*) – Number of texture pages to generate.
- **texture_size** (*int*) – Expected size of texture page at texture generation step.
- **camera** (*int*) – Camera to be used for texturing in MappingCamera mode.
- **progress** (*Callable[[float], None]*) – Progress callback.

calibrateColors (*source_data=ModelData, white_balance=False[, cameras][, progress]*)
Perform radiometric calibration.

Parameters

- **source_data** (*DataSource*) – Source data for calibration.
- **white_balance** (*bool*) – Calibrate white balance.
- **cameras** (*list of int*) – List of cameras to process.
- **progress** (*Callable[[float], None]*) – Progress callback.

calibrateReflectance (*use_reflectance_panels=True, use_sun_sensor=False[, progress]*)
Calibrate reflectance factors based on calibration panels and/or sun sensor.

Parameters

- **use_reflectance_panels** (*bool*) – Use calibrated reflectance panels.
- **use_sun_sensor** (*bool*) – Apply irradiance sensor measurements.
- **progress** (*Callable[[float], None]*) – Progress callback.

camera_crs

Coordinate system used for camera reference data.

Type *CoordinateSystem*

camera_groups

List of camera groups in the chunk.

Type list of *CameraGroup*

camera_location_accuracy

Expected accuracy of camera coordinates in meters.

Type *Vector*

camera_rotation_accuracy

Expected accuracy of camera orientation angles in degrees.

Type *Vector*

camera_track

Camera track.

Type *CameraTrack*

camera_tracks

List of camera tracks in the chunk.

Type list of *CameraTrack*

cameras

List of Regular and Keyframe cameras in the chunk.

Type list of *Camera*

cir_transform

CIR calibration matrix.

Type *CirTransform*

copy (*[frames][, items]*, *keypoints=True[, progress]*)

Make a copy of the chunk.

Parameters

- **frames** (list of *Frame*) – Optional list of frames to be copied.
- **items** (list of *DataSource*) – A list of items to copy.
- **keypoints** (*bool*) – copy key points data.
- **progress** (*Callable[[float], None]*) – Progress callback.

Returns Copy of the chunk.

Return type *Chunk*

crs

Coordinate system used for reference data.

Type *CoordinateSystem*

decimateModel (*face_count=200000[, asset]*, *apply_to_selection=False[, progress]*)

Decimate the model to the specified face count.

Parameters

- **face_count** (*int*) – Target face count.
- **asset** (*int*) – Model to process.
- **apply_to_selection** (*bool*) – Apply to selection.
- **progress** (*Callable[[float], None]*) – Progress callback.

dense_cloud

Default dense point cloud for the current frame.

Type *DenseCloud*

dense_clouds

List of dense clouds for the current frame.

Type list of *DenseCloud*

depth_maps

Default depth maps set for the current frame.

Type *DepthMaps*

depth_maps_sets

List of depth maps sets for the current frame.

Type list of *DepthMaps*

detectFiducials (*generate_masks=False[, cameras][[, frames][[, progress]]*)

Detect fiducial marks on film cameras.

Parameters

- **generate_masks** (*bool*) – Generate background masks.

- **cameras** (*list of int*) – List of cameras to process.
- **frames** (*list of int*) – List of frames to process.
- **progress** (*Callable[[float], None]*) – Progress callback.

detectMarkers (*target_type=CircularTarget12bit, tolerance=50, filter_mask=False, inverted=False, noparity=False, maximum_residual=5, minimum_size=0, minimum_dist=5* [, *cameras*] [, *frames*] [, *progress*])

Create markers from coded targets.

Parameters

- **target_type** (*TargetType*) – Type of targets.
- **tolerance** (*int*) – Detector tolerance (0 - 100).
- **filter_mask** (*bool*) – Ignore masked image regions.
- **inverted** (*bool*) – Detect markers on black background.
- **noparity** (*bool*) – Disable parity checking.
- **maximum_residual** (*float*) – Maximum residual for non-coded targets in pixels.
- **minimum_size** (*int*) – Minimum target radius in pixels to be detected (CrossTarget type only).
- **minimum_dist** (*int*) – Minimum distance between targets in pixels (CrossTarget type only).
- **cameras** (*list of int*) – List of cameras to process.
- **frames** (*list of int*) – List of frames to process.
- **progress** (*Callable[[float], None]*) – Progress callback.

elevation

Default elevation model for the current frame.

Type *Elevation*

elevations

List of elevation models for the current frame.

Type list of *Elevation*

enabled

Enables/disables the chunk.

Type bool

euler_angles

Euler angles triplet used for rotation reference.

Type *EulerAngles*

exportCameras (*path=''*, *format=CamerasFormatXML* [, *crs*], *save_points=True*, *save_markers=False*, *save_invalid_matches=False*, *use_labels=False*, *use_initial_calibration=False*, *image_orientation=0*, *chan_rotation_order=RotationOrderXYZ*, *binary=False*, *bundler_save_list=True*, *bundler_path_list='list.txt'*, *bingo_save_image=True*, *bingo_save_itera=True*, *bingo_save_geoin=True*, *bingo_save_gps=False*, *bingo_path_itera='itera.dat'*, *bingo_path_image='image.dat'*, *bingo_path_geoin='geoin.dat'*, *bingo_path_gps='gps-imu.dat'* [, *progress*])

Export point cloud and/or camera positions.

Parameters

- **path** (*string*) – Path to output file.
- **format** (*CamerasFormat*) – Export format.
- **crs** (*CoordinateSystem*) – Output coordinate system.
- **save_points** (*bool*) – Enables/disables export of automatic tie points.
- **save_markers** (*bool*) – Enables/disables export of manual matching points.
- **save_invalid_matches** (*bool*) – Enables/disables export of invalid image matches.
- **use_labels** (*bool*) – Enables/disables label based item identifiers.
- **use_initial_calibration** (*bool*) – Transform image coordinates to initial calibration.
- **image_orientation** (*int*) – Image coordinate system (0 - X right, 1 - X up, 2 - X left, 3 - X down).
- **chan_rotation_order** (*RotationOrder*) – Rotation order (CHAN format only).
- **binary** (*bool*) – Enables/disables binary encoding for selected format (if applicable).
- **bundler_save_list** (*bool*) – Enables/disables export of Bundler image list file.
- **bundler_path_list** (*string*) – Path to Bundler image list file.
- **bingo_save_image** (*bool*) – Enables/disables export of BINGO IMAGE COORDINATE file.
- **bingo_save_itera** (*bool*) – Enables/disables export of BINGO ITERA file.
- **bingo_save_geoin** (*bool*) – Enables/disables export of BINGO GEO INPUT file.
- **bingo_save_gps** (*bool*) – Enables/disables export of BINGO GPS/IMU data.
- **bingo_path_itera** (*string*) – Path to BINGO ITERA file.
- **bingo_path_image** (*string*) – Path to BINGO IMAGE COORDINATE file.
- **bingo_path_geoin** (*string*) – Path to BINGO GEO INPUT file.
- **bingo_path_gps** (*string*) – Path to BINGO GPS/IMU file.
- **progress** (*Callable[[float], None]*) – Progress callback.

exportMarkers (*path*='[, crs], *binary*=False[, *progress*])

Export markers.

Parameters

- **path** (*string*) – Path to output file.
- **crs** (*CoordinateSystem*) – Output coordinate system.
- **binary** (*bool*) – Enables/disables binary encoding for selected format (if applicable).
- **progress** (*Callable[[float], None]*) – Progress callback.

exportModel (*path*='', *binary*=True, *precision*=6, *texture_format*=ImageFormatJPEG, *save_texture*=True, *save_uv*=True, *save_normals*=True, *save_colors*=True, *save_confidence*=False, *save_cameras*=True, *save_markers*=True, *save_udim*=False, *save_alpha*=False, *embed_texture*=False, *strip_extensions*=False, *raster_transform*=RasterTransformNone, *colors_rgb_8bit*=True, *comment*='', *save_comment*=True, *format*=ModelFormatNone[, *crs*][, *shift*], *clip_to_boundary*=True[, *viewpoint*][, *progress*])

Export generated model for the chunk.

Parameters

- **path** (*string*) – Path to output model.
- **binary** (*bool*) – Enables/disables binary encoding (if supported by format).
- **precision** (*int*) – Number of digits after the decimal point (for text formats).
- **texture_format** (*ImageFormat*) – Texture format.
- **save_texture** (*bool*) – Enables/disables texture export.
- **save_uv** (*bool*) – Enables/disables uv coordinates export.
- **save_normals** (*bool*) – Enables/disables export of vertex normals.
- **save_colors** (*bool*) – Enables/disables export of vertex colors.
- **save_confidence** (*bool*) – Enables/disables export of vertex confidence.
- **save_cameras** (*bool*) – Enables/disables camera export.
- **save_markers** (*bool*) – Enables/disables marker export.
- **save_udim** (*bool*) – Enables/disables UDIM texture layout.
- **save_alpha** (*bool*) – Enables/disables alpha channel export.
- **embed_texture** (*bool*) – Embeds texture inside the model file (if supported by format).
- **strip_extensions** (*bool*) – Strips camera label extensions during export.
- **raster_transform** (*RasterTransformType*) – Raster band transformation.
- **colors_rgb_8bit** (*bool*) – Convert colors to 8 bit RGB.
- **comment** (*string*) – Optional comment (if supported by selected format).
- **save_comment** (*bool*) – Enables/disables comment export.
- **format** (*ModelFormat*) – Export format.
- **crs** (*CoordinateSystem*) – Output coordinate system.
- **shift** (*Vector*) – Optional shift to be applied to vertex coordinates.
- **clip_to_boundary** (*bool*) – Clip model to boundary shapes.
- **viewpoint** (*Viewpoint*) – Default view.
- **progress** (*Callable[[float], None]*) – Progress callback.

```
exportOrthophotos (path='{filename}.tif'[, cameras ], raster_transform=RasterTransformNone [,
    projection ] [, region ], resolution=0, resolution_x=0, resolution_y=0,
    save_kml=False, save_world=False, save_alpha=True [, image_compression
    ], white_background=True, north_up=True [, progress ])
```

Export orthophotos for the chunk.

Parameters

- **path** (*string*) – Path to output orthophoto.
- **cameras** (*list of int*) – List of cameras to process.
- **raster_transform** (*RasterTransformType*) – Raster band transformation.
- **projection** (*OrthoProjection*) – Output projection.

- **region** (*BBox*) – Region to be exported.
- **resolution** (*float*) – Output resolution in meters.
- **resolution_x** (*float*) – Pixel size in the X dimension in projected units.
- **resolution_y** (*float*) – Pixel size in the Y dimension in projected units.
- **save_kml** (*bool*) – Enable kml file generation.
- **save_world** (*bool*) – Enable world file generation.
- **save_alpha** (*bool*) – Enable alpha channel generation.
- **image_compression** (*ImageCompression*) – Image compression parameters.
- **white_background** (*bool*) – Enable white background.
- **north_up** (*bool*) – Use north-up orientation for export.
- **progress** (*Callable[[float], None]*) – Progress callback.

exportPoints (*path*='', *source_data*=*DenseCloudData*, *binary*=*True*, *save_normals*=*True*,
save_colors=*True*, *save_classes*=*True*, *save_confidence*=*True*,
raster_transform=*RasterTransformNone*, *colors_rgb_8bit*=*True*, *comment*='',
save_comment=*True*, *format*=*PointsFormatNone*, *image_format*=*ImageFormatJPEG*[, *crs*][, *shift*][, *region*], *clip_to_boundary*=*True*,
block_width=*1000*, *block_height*=*1000*, *split_in_blocks*=*False*[, *classes*],
save_images=*False*[, *viewpoint*], *subdivide_task*=*True*[, *progress*])

Export point cloud.

Parameters

- **path** (*string*) – Path to output file.
- **source_data** (*DataSource*) – Selects between dense point cloud and sparse point cloud. If not specified, uses dense cloud if available.
- **binary** (*bool*) – Enables/disables binary encoding for selected format (if applicable).
- **save_normals** (*bool*) – Enables/disables export of point normals.
- **save_colors** (*bool*) – Enables/disables export of point colors.
- **save_classes** (*bool*) – Enables/disables export of point classes.
- **save_confidence** (*bool*) – Enables/disables export of point confidence.
- **raster_transform** (*RasterTransformType*) – Raster band transformation.
- **colors_rgb_8bit** (*bool*) – Convert colors to 8 bit RGB.
- **comment** (*string*) – Optional comment (if supported by selected format).
- **save_comment** (*bool*) – Enable comment export.
- **format** (*PointsFormat*) – Export format.
- **image_format** (*ImageFormat*) – Image data format.
- **crs** (*CoordinateSystem*) – Output coordinate system.
- **shift** (*Vector*) – Optional shift to be applied to point coordinates.
- **region** (*BBox*) – Region to be exported.
- **clip_to_boundary** (*bool*) – Clip point cloud to boundary shapes.
- **block_width** (*float*) – Block width in meters.

- **block_height** (*float*) – Block height in meters.
- **split_in_blocks** (*bool*) – Enable tiled export.
- **classes** (*list of int*) – List of dense point classes to be exported.
- **save_images** (*bool*) – Enable image export.
- **viewpoint** (*Viewpoint*) – Default view.
- **subdivide_task** (*bool*) – Enable fine-level task subdivision.
- **progress** (*Callable[[float], None]*) – Progress callback.

```
exportRaster (path='', format=RasterFormatTiles, image_format=ImageFormatNone,
raster_transform=RasterTransformNone[, projection][, region], resolution=0,
resolution_x=0, resolution_y=0, block_width=10000, block_height=10000,
split_in_blocks=False, width=0, height=0[, world_transform], nodata_value=-32767,
save_kml=False, save_world=False, save_scheme=False, save_alpha=True,
image_description='', [, image_compression], network_links=True,
min_zoom_level=-1, max_zoom_level=-1, white_background=True,
clip_to_boundary=True, title='Orthomosaic', description='Generated by Agisoft Metashape',
source_data=OrthomosaicData, north_up=True, tile_width=256,
tile_height=256[, progress])
```

Export generated raster for the chunk.

Parameters

- **path** (*string*) – Path to output orthomosaic.
- **format** (*RasterFormat*) – Export format.
- **image_format** (*ImageFormat*) – Tile format.
- **raster_transform** (*RasterTransformType*) – Raster band transformation.
- **projection** (*OrthoProjection*) – Output projection.
- **region** (*BBox*) – Region to be exported.
- **resolution** (*float*) – Output resolution in meters.
- **resolution_x** (*float*) – Pixel size in the X dimension in projected units.
- **resolution_y** (*float*) – Pixel size in the Y dimension in projected units.
- **block_width** (*int*) – Raster block width in pixels.
- **block_height** (*int*) – Raster block height in pixels.
- **split_in_blocks** (*bool*) – Split raster in blocks.
- **width** (*int*) – Raster width.
- **height** (*int*) – Raster height.
- **world_transform** (*Matrix*) – 2x3 raster-to-world transformation matrix.
- **nodata_value** (*float*) – No-data value (DEM export only).
- **save_kml** (*bool*) – Enable kml file generation.
- **save_world** (*bool*) – Enable world file generation.
- **save_scheme** (*bool*) – Enable tile scheme files generation.
- **save_alpha** (*bool*) – Enable alpha channel generation.
- **image_description** (*string*) – Optional description to be added to image files.

- **image_compression** (*ImageCompression*) – Image compression parameters.
- **network_links** (*bool*) – Enable network links generation for KMZ format.
- **min_zoom_level** (*int*) – Minimum zoom level (Google Map Tiles, MBTiles and World Wind Tiles formats only).
- **max_zoom_level** (*int*) – Maximum zoom level (Google Map Tiles, MBTiles and World Wind Tiles formats only).
- **white_background** (*bool*) – Enable white background.
- **clip_to_boundary** (*bool*) – Clip raster to boundary shapes.
- **title** (*string*) – Export title.
- **description** (*string*) – Export description.
- **source_data** (*DataSource*) – Selects between DEM and orthomosaic.
- **north_up** (*bool*) – Use north-up orientation for export.
- **tile_width** (*int*) – Tile width in pixels.
- **tile_height** (*int*) – Tile height in pixels.
- **progress** (*Callable[[float], None]*) – Progress callback.

exportReference (*path*='', *format*=*ReferenceFormatNone*[, *items*], *columns*='', *delimiter*=' '[, *progress*])

Export reference data to the specified file.

Parameters

- **path** (*string*) – Path to the output file.
- **format** (*ReferenceFormat*) – Export format.
- **items** (*ReferenceItems*) – Items to export in CSV format.
- **columns** (*string*) – Column order in csv format (n - label, o - enabled flag, x/y/z - coordinates, X/Y/Z - coordinate accuracy, a/b/c - rotation angles, A/B/C - rotation angle accuracy, u/v/w - estimated coordinates, U/V/W - coordinate errors, d/e/f - estimated orientation angles, D/E/F - orientation errors, p/q/r - estimated coordinates variance, i/j/k - estimated orientation angles variance, [] - group of multiple values, | - column separator within group).
- **delimiter** (*string*) – Column delimiter in csv format.
- **progress** (*Callable[[float], None]*) – Progress callback.

exportReport (*path*='', *title*='', *description*='', *page_numbers*=*True*[, *user_settings*][, *progress*])

Export processing report in PDF format.

Parameters

- **path** (*string*) – Path to output report.
- **title** (*string*) – Report title.
- **description** (*string*) – Report description.
- **page_numbers** (*bool*) – Enable page numbers.
- **user_settings** (*list of (string, string) tuples*) – A list of user defined settings to include on the Processing Parameters page.
- **progress** (*Callable[[float], None]*) – Progress callback.

exportShapes (*path*='', *save_points*=False, *save_polylines*=False, *save_polygons*=False[, *groups*], *format*=ShapesFormatNone[, *crs*][, *shift*], *polygons_as_polylines*=False, *save_labels*=True, *save_attributes*=True[, *progress*])

Export shapes layer to file.

Parameters

- **path** (*string*) – Path to shape file.
- **save_points** (*bool*) – Export points.
- **save_polylines** (*bool*) – Export polylines.
- **save_polygons** (*bool*) – Export polygons.
- **groups** (*list of int*) – A list of shape groups to export.
- **format** (*ShapesFormat*) – Export format.
- **crs** (*CoordinateSystem*) – Output coordinate system.
- **shift** (*Vector*) – Optional shift to be applied to vertex coordinates.
- **polygons_as_polylines** (*bool*) – Save polygons as polylines.
- **save_labels** (*bool*) – Export labels.
- **save_attributes** (*bool*) – Export attributes.
- **progress** (*Callable[[float], None]*) – Progress callback.

exportTiledModel (*path*='', *format*=TiledModelFormatNone, *model_format*=ModelFormatCOLLADA, *texture_format*=ImageFormatJPEG, *raster_transform*=RasterTransformNone[, *image_compression*][, *crs*], *clip_to_boundary*=True[, *progress*])

Export generated tiled model for the chunk.

Parameters

- **path** (*string*) – Path to output model.
- **format** (*TiledModelFormat*) – Export format.
- **model_format** (*ModelFormat*) – Model format for zip export.
- **texture_format** (*ImageFormat*) – Texture format.
- **raster_transform** (*RasterTransformType*) – Raster band transformation.
- **image_compression** (*ImageCompression*) – Image compression parameters.
- **crs** (*CoordinateSystem*) – Output coordinate system.
- **clip_to_boundary** (*bool*) – Clip tiled model to boundary shapes.
- **progress** (*Callable[[float], None]*) – Progress callback.

findFrame (*key*)

Find frame by its key.

Returns Found frame.

Return type *Chunk*

frame

Current frame index.

Type *int*

frames

List of frames in the chunk.

Type list of `Frame`

image_brightness

Image brightness as percentage.

Type float

image_contrast

Image contrast as percentage.

Type float

importCameras (*path*='', *format*=`CamerasFormatXML`[, *crs*], *image_orientation*=0, *image_list*='list.txt', *load_image_list*=`False`[, *progress*])

Import camera positions.

Parameters

- **path** (*string*) – Path to the file.
- **format** (`CamerasFormat`) – File format.
- **crs** (`CoordinateSystem`) – Ground coordinate system.
- **image_orientation** (*int*) – Image coordinate system (0 - X right, 1 - X up, 2 - X left, 3 - X down).
- **image_list** (*string*) – Path to image list file (Bundler format only).
- **load_image_list** (*bool*) – Enable Bundler image list import.
- **progress** (`Callable`[[*float*], *None*]) – Progress callback.

importMarkers (*path*='', [, *progress*])

Import markers.

Parameters

- **path** (*string*) – Path to the file.
- **progress** (`Callable`[[*float*], *None*]) – Progress callback.

importMasks (*path*='{filename}_mask.png', *source*=`MaskSourceAlpha`, *operation*=`MaskOperationReplacement`, *tolerance*=10[, *cameras*][, *progress*])

Import masks for multiple cameras.

Parameters

- **path** (*string*) – Mask file name template.
- **source** (`MaskSource`) – Mask source.
- **operation** (`MaskOperation`) – Mask operation.
- **tolerance** (*int*) – Background masking tolerance.
- **cameras** (*list of int*) – Optional list of cameras to be processed.
- **progress** (`Callable`[[*float*], *None*]) – Progress callback.

importModel (*path*='', *format*=`ModelFormatNone`[, *crs*][, *shift*][, *progress*])

Import model from file.

Parameters

- **path** (*string*) – Path to model.

- **format** (*ModelFormat*) – Model format.
- **crs** (*CoordinateSystem*) – Model coordinate system.
- **shift** (*Vector*) – Optional shift to be applied to vertex coordinates.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

importPoints (*path*='', *format*=*PointsFormatNone*, *calculate_normals*=*True*[[, *crs*]][, *shift*][[, *progress*]])
 Import point cloud from file.

Parameters

- **path** (*string*) – Path to point cloud.
- **format** (*PointsFormat*) – Point cloud format.
- **calculate_normals** (*bool*) – Calculate point normals.
- **crs** (*CoordinateSystem*) – Point cloud coordinate system.
- **shift** (*Vector*) – Optional shift to be applied to point coordinates.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

importRaster (*path*=''[[, *crs*]], *raster_type*=*ElevationData*[[, *progress*]])
 Import raster layer from file.

Parameters

- **path** (*string*) – Path to elevation model in GeoTIFF format.
- **crs** (*CoordinateSystem*) – Default coordinate system if not specified in GeoTIFF file.
- **raster_type** (*DataSource*) – Type of raster layer to import.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

importReference (*path*='', *format*=*ReferenceFormatCSV*, *columns*='', *delimiter*='', *group_delimiters*=*False*, *skip_rows*=*0*[[, *items*]][[, *crs*], *ignore_labels*=*False*, *create_markers*=*False*, *threshold*=*0.1*, *shutter_lag*=*0*[[, *progress*]])
 Import reference data from the specified file.

Parameters

- **path** (*string*) – Path to the file with reference data.
- **format** (*ReferenceFormat*) – File format.
- **columns** (*string*) – Column order in csv format (n - label, o - enabled flag, x/y/z - coordinates, X/Y/Z - coordinate accuracy, a/b/c - rotation angles, A/B/C - rotation angle accuracy, [] - group of multiple values, | - column separator within group).
- **delimiter** (*string*) – Column delimiter in csv format.
- **group_delimiters** (*bool*) – Combine consecutive delimiters in csv format.
- **skip_rows** (*int*) – Number of rows to skip in (csv format only).
- **items** (*ReferenceItems*) – List of items to load reference for (csv format only).
- **crs** (*CoordinateSystem*) – Reference data coordinate system (csv format only).
- **ignore_labels** (*bool*) – Matches reference data based on coordinates alone (csv format only).
- **create_markers** (*bool*) – Create markers for missing entries (csv format only).

- **threshold** (*float*) – Error threshold in meters used when `ignore_labels` is set (csv format only).
- **shutter_lag** (*float*) – Shutter lag in seconds (APM format only).
- **progress** (*Callable[[float], None]*) – Progress callback.

```
importShapes (path='', replace=False, boundary_type=NoBoundary, format=ShapesFormatNone,  
              columns='nxyzd', delimiter=' ', group_delimiters=False, skip_rows=0[, crs][,  
              progress])  
Import shapes layer from file.
```

Parameters

- **path** (*string*) – Path to shape file.
- **replace** (*bool*) – Replace current shapes with new data.
- **boundary_type** (*Shape.BoundaryType*) – Boundary type to be applied to imported shapes.
- **format** (*ShapesFormat*) – Shapes format.
- **columns** (*string*) – Column order in csv format (n - label, x/y/z - coordinates, d - description, [] - group of multiple values, | - column separator within group).
- **delimiter** (*string*) – Column delimiter in csv format.
- **group_delimiters** (*bool*) – Combine consecutive delimiters in csv format.
- **skip_rows** (*int*) – Number of rows to skip in (csv format only).
- **crs** (*CoordinateSystem*) – Reference data coordinate system (csv format only).
- **progress** (*Callable[[float], None]*) – Progress callback.

```
importTiledModel (path='', [, progress ])  
Import tiled model from file.
```

Parameters

- **path** (*string*) – Path to tiled model.
- **progress** (*Callable[[float], None]*) – Progress callback.

key

Chunk identifier.

Type int

label

Chunk label.

Type string

```
loadReferenceExif (load_rotation=False, load_accuracy=False)  
Import camera locations from EXIF meta data.
```

Parameters

- **load_rotation** (*bool*) – load yaw, pitch and roll orientation angles.
- **load_accuracy** (*bool*) – load camera location accuracy.

```
loadReflectancePanelCalibration (path[, cameras ])  
Load reflectance panel calibration from CSV file.
```

Parameters

- **path** (*string*) – Path to calibration file.
- **cameras** (list of *Camera*) – List of cameras to process.

locateReflectancePanels (*[progress]*)

Locate reflectance panels based on QR-codes.

Parameters **progress** (*Callable[[float], None]*) – Progress callback.

marker_crs

Coordinate system used for marker reference data.

Type *CoordinateSystem*

marker_groups

List of marker groups in the chunk.

Type list of *MarkerGroup*

marker_location_accuracy

Expected accuracy of marker coordinates in meters.

Type *Vector*

marker_projection_accuracy

Expected accuracy of marker projections in pixels.

Type float

markers

List of Regular, Vertex and Fiducial markers in the chunk.

Type list of *Marker*

masks

Image masks.

Type *Masks*

matchPhotos (*downscale=1, generic_preselection=True, reference_preselection=True, reference_preselection_mode=ReferencePreselectionSource, filter_mask=False, mask_tiepoints=True, keypoint_limit=40000, tiepoint_limit=4000, keep_keypoints=False[, pairs][, cameras], guided_matching=False, reset_matches=False, subdivide_task=True, workitem_size_cameras=20, workitem_size_pairs=80, max_workgroup_size=100[, progress]*)

Perform image matching for the chunk frame.

Parameters

- **downscale** (*int*) – Image alignment accuracy.
- **generic_preselection** (*bool*) – Enable generic preselection.
- **reference_preselection** (*bool*) – Enable reference preselection.
- **reference_preselection_mode** (*ReferencePreselectionMode*) – Reference preselection mode.
- **filter_mask** (*bool*) – Filter points by mask.
- **mask_tiepoints** (*bool*) – Apply mask filter to tie points.
- **keypoint_limit** (*int*) – Key point limit.
- **tiepoint_limit** (*int*) – Tie point limit.
- **keep_keypoints** (*bool*) – Store keypoints in the project.

- **pairs** (*list of (int, int) tuples*) – User defined list of camera pairs to match.
- **cameras** (*list of int*) – List of cameras to match.
- **guided_matching** (*bool*) – Enable guided image matching.
- **reset_matches** (*bool*) – Reset current matches.
- **subdivide_task** (*bool*) – Enable fine-level task subdivision.
- **workitem_size_cameras** (*int*) – Number of cameras in a workitem.
- **workitem_size_pairs** (*int*) – Number of image pairs in a workitem.
- **max_workgroup_size** (*int*) – Maximum workgroup size.
- **progress** (*Callable[[float], None]*) – Progress callback.

meta

Chunk meta data.

Type *MetaData*

model

Default model for the current frame.

Type *Model*

models

List of models for the current frame.

Type list of *Model*

modified

Modified flag.

Type *bool*

optimizeCameras (*fit_f=True, fit_cx=True, fit_cy=True, fit_b1=False, fit_b2=False, fit_k1=True, fit_k2=True, fit_k3=True, fit_k4=False, fit_p1=True, fit_p2=True, fit_corrections=False, adaptive_fitting=False, tiepoint_covariance=False, progress*)

Perform optimization of point cloud / camera parameters.

Parameters

- **fit_f** (*bool*) – Enable optimization of focal length coefficient.
- **fit_cx** (*bool*) – Enable optimization of X principal point coordinates.
- **fit_cy** (*bool*) – Enable optimization of Y principal point coordinates.
- **fit_b1** (*bool*) – Enable optimization of aspect ratio.
- **fit_b2** (*bool*) – Enable optimization of skew coefficient.
- **fit_k1** (*bool*) – Enable optimization of k1 radial distortion coefficient.
- **fit_k2** (*bool*) – Enable optimization of k2 radial distortion coefficient.
- **fit_k3** (*bool*) – Enable optimization of k3 radial distortion coefficient.
- **fit_k4** (*bool*) – Enable optimization of k3 radial distortion coefficient.
- **fit_p1** (*bool*) – Enable optimization of p1 tangential distortion coefficient.
- **fit_p2** (*bool*) – Enable optimization of p2 tangential distortion coefficient.

- **fit_corrections** (*bool*) – Enable optimization of additional corrections.
- **adaptive_fitting** (*bool*) – Enable adaptive fitting of distortion coefficients.
- **tiepoint_covariance** (*bool*) – Estimate tie point covariance matrices.
- **progress** (*Callable[[float], None]*) – Progress callback.

orthomosaic

Default orthomosaic for the current frame.

Type *Orthomosaic*

orthomosaics

List of orthomosaics for the current frame.

Type list of *Orthomosaic*

point_cloud

Generated sparse point cloud.

Type *PointCloud*

primary_channel

Primary channel index (-1 for default).

Type *int*

raster_transform

Raster transform.

Type *RasterTransform*

reduceOverlap (*overlap=30, max_cameras=0, use_selection=False* [, *progress*])

Disable redundant cameras.

Parameters

- **overlap** (*int*) – Overlap level.
- **max_cameras** (*int*) – Maximum cameras to use.
- **use_selection** (*bool*) – Focus on model selection.
- **progress** (*Callable[[float], None]*) – Progress callback.

refineMarkers ([*markers*] [, *progress*])

Refine markers based on images content.

Parameters

- **markers** (*list of int*) – Optional list of markers to be processed.
- **progress** (*Callable[[float], None]*) – Progress callback.

refineMesh (*downscale=4, iterations=10, smoothness=0.5* [, *cameras*] [, *progress*])

Generate model for the chunk frame.

Parameters

- **downscale** (*int*) – Refinement quality.
- **iterations** (*int*) – Number of refinement iterations.
- **smoothness** (*float*) – Smoothing strength. Should be in range [0, 1].
- **cameras** (*list of int*) – List of cameras to process.
- **progress** (*Callable[[float], None]*) – Progress callback.

region

Reconstruction volume selection.

Type *Region*

remove (*items*)

Remove items from the chunk.

Parameters *items* (list of *Frame*, *Sensor*, *CameraGroup*, *MarkerGroup*, *ScalebarGroup*, *Camera*, *Marker*, *Scalebar* or *CameraTrack*) – A list of items to be removed.

removeLighting (*color_mode=False*, *internal_blur=1.5*, *mesh_noise_suppression=1*, *ambient_occlusion_path=''*, *ambient_occlusion_multiplier=1.5* [, *progress*])

Generate model for the chunk frame.

Parameters

- **color_mode** (*bool*) – Enable multi-color processing mode.
- **internal_blur** (*float*) – Internal blur. Should be in range [0, 4].
- **mesh_noise_suppression** (*float*) – Mesh normals noise suppression strength. Should be in range [0, 4].
- **ambient_occlusion_path** (*string*) – Path to ambient occlusion texture atlas. Can be empty.
- **ambient_occlusion_multiplier** (*float*) – Ambient occlusion multiplier. Should be in range [0.25, 4].
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

renderPreview (*width = 2048*, *height = 2048* [, *transform*], *point_size=1* [, *progress*])

Generate preview image for the chunk.

Parameters

- **width** (*int*) – Preview image width.
- **height** (*int*) – Preview image height.
- **transform** (*Matrix*) – 4x4 viewpoint transformation matrix.
- **point_size** (*int*) – Point size.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

Returns Preview image.

Return type *Image*

resetRegion ()

Reset reconstruction volume selector to default position.

scalebar_accuracy

Expected scale bar accuracy in meters.

Type *float*

scalebar_groups

List of scale bar groups in the chunk.

Type list of *ScalebarGroup*

scalebars

List of scale bars in the chunk.

Type list of *Scalebar*

selected

Selects/deselects the chunk.

Type bool

sensors

List of sensors in the chunk.

Type list of *Sensor*

shapes

Shapes for the current frame.

Type *Shapes*

smoothModel (*strength=3, apply_to_selection=False, fix_borders=True[, progress]*)

Smooth mesh using Laplacian smoothing algorithm.

Parameters

- **strength** (*float*) – Smoothing strength.
- **apply_to_selection** (*bool*) – Apply to selected faces.
- **fix_borders** (*bool*) – Fix borders.
- **progress** (*Callable[[float], None]*) – Progress callback.

sortCameras ()

Sorts cameras by their labels.

sortMarkers ()

Sorts markers by their labels.

sortScalebars ()

Sorts scalebars by their labels.

thinPointCloud (*point_limit=1000*)

Remove excessive tracks from the point cloud.

Parameters **point_limit** (*int*) – Maximum number of points for each photo.

thumbnails

Image thumbnails.

Type *Thumbnails*

tiepoint_accuracy

Expected tie point accuracy in pixels.

Type float

tiled_model

Default tiled model for the current frame.

Type *TiledModel*

tiled_models

List of tiled models for the current frame.

Type list of *TiledModel*

trackMarkers (*first_frame=0, last_frame=0[, progress]*)

Track marker projections through the frame sequence.

Parameters

- **first_frame** (*int*) – Starting frame index.
- **last_frame** (*int*) – Ending frame index.
- **progress** (*Callable[[float], None]*) – Progress callback.

transform

4x4 matrix specifying chunk location in the world coordinate system.

Type *ChunkTransform*

triangulatePoints (*max_error=10, min_image=2[, progress]*)

Rebuild point cloud for the chunk.

Parameters

- **max_error** (*float*) – Reprojection error threshold.
- **min_image** (*int*) – Minimum number of point projections.
- **progress** (*Callable[[float], None]*) – Progress callback.

updateTransform ()

Update chunk transformation based on reference data.

world_crs

Coordinate system used as world coordinate system.

Type *CoordinateSystem*

class Metashape.**ChunkTransform**

Transformation between chunk and world coordinates systems.

copy ()

Return a copy of the object.

Returns A copy of the object.

Return type *ChunkTransform*

matrix

Transformation matrix.

Type *Matrix*

rotation

Rotation component.

Type *Matrix*

scale

Scale component.

Type float

translation

Translation component.

Type *Vector*

class Metashape.**CirTransform**

CIR calibration matrix.

calibrate ()

Calibrate CIR matrix based on orthomosaic histogram.

coeffs

Color matrix.

Type *Matrix*

copy ()

Return a copy of the object.

Returns A copy of the object.

Return type *CirTransform*

reset ()

Reset CIR calibration matrix.

class `Metashape.CoordinateSystem`

Coordinate reference system (local, geographic or projected).

The following example changes chunk coordinate system to WGS 84 / UTM zone 41N and loads reference data from file:

```
>>> import Metashape
>>> chunk = Metashape.app.document.chunk
>>> chunk.crs = Metashape.CoordinateSystem("EPSG::32641")
>>> chunk.importReference("gcp.txt", Metashape.ReferenceFormatCSV)
>>> chunk.updateTransform()
```

addGeoid (path)

Register geoid model.

Parameters **path** (*string*) – Path to geoid file.

authority

Authority identifier of the coordinate system.

Type *string*

copy ()

Return a copy of the object.

Returns A copy of the object.

Return type *CoordinateSystem*

geoccs

Base geocentric coordinate system.

Type *CoordinateSystem*

geogcs

Base geographic coordinate system.

Type *CoordinateSystem*

geoid_height

Fixed geoid height to be used instead of interpolated values.

Type *float*

init (crs)

Initialize projection based on specified WKT definition or authority identifier.

Parameters **crs** (*string*) – WKT definition of coordinate system or authority identifier.

listBuiltinCRS ()

Returns a list of builtin coordinate systems.

localframe (*point*)

Returns 4x4 transformation matrix to LSE coordinates at the given point.

Parameters **point** (*Vector*) – Coordinates of the origin in the geocentric coordinates.

Returns Transformation from geocentric coordinates to local coordinates.

Return type *Matrix*

name

Name of the coordinate system.

Type string

proj4

Coordinate system definition in PROJ.4 format.

Type string

project (*point*)

Projects point from geocentric coordinates to projected geographic coordinate system.

Parameters **point** (*Vector*) – 3D point in geocentric coordinates.

Returns 3D point in projected coordinates.

Return type *Vector*

towgs84

TOWGS84 transformation parameters (dx, dy, dz, rx, ry, rz, scale).

Type list of float

ttransform (*point, source, target*)

Transform point coordinates between coordinate systems.

Parameters

- **point** (2 or 3 component *Vector*) – Point coordinates.
- **source** (*CoordinateSystem*) – Source coordinate system.
- **target** (*CoordinateSystem*) – Target coordinate system.

Returns Transformed point coordinates.

Return type *Vector*

transformationMatrix (*point, source, target*)

Local approximation of coordinate transformation from source to target coordinate system at the given point.

Parameters

- **point** (3 component *Vector*) – Point coordinates.
- **source** (*CoordinateSystem*) – Source coordinate system.
- **target** (*CoordinateSystem*) – Target coordinate system.

Returns 4x4 transformation matrix.

Return type *Matrix*

unproject (*point*)

Unprojects point from projected coordinates to geocentric coordinates.

Parameters **point** (*Vector*) – 3D point in projected coordinate system.

Returns 3D point in geocentric coordinates.

Return type *Vector*

wkt

Coordinate system definition in WKT format.

Type string

wkt2

Coordinate system definition in WKT format, version 2.

Type string

class `Metashape.DataSource`

Data source in [PointCloudData, DenseCloudData, DepthMapsData, ModelData, TiledModelData, ElevationData, OrthomosaicData, ImagesData]

class `Metashape.DataType`

Data type in [DataTypeUndefined, DataType8i, DataType8u, DataType16i, DataType16u, DataType16f, DataType32i, DataType32u, DataType32f, DataType64i, DataType64u, DataType64f]

class `Metashape.DenseCloud`

Dense point cloud data.

assignClass (*target=0* [, *source*] [, *progress*])

Assign class to points.

Parameters

- **target** (*PointClass*) – Target class.
- **source** (*PointClass* or list of *PointClass*) – Classes of points to be replaced.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

assignClassToSelection (*target=0* [, *source*] [, *progress*])

Assign class to selected points.

Parameters

- **target** (*PointClass*) – Target class.
- **source** (*PointClass* or list of *PointClass*) – Classes of points to be replaced.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

bands

List of color bands.

Type list of string

classifyGroundPoints (*max_angle=15.0*, *max_distance=1.0*, *cell_size=50.0* [, *source*] [, *progress*])

Classify points into ground and non ground classes.

Parameters

- **max_angle** (*float*) – Maximum angle (degrees).
- **max_distance** (*float*) – Maximum distance (meters).
- **cell_size** (*float*) – Cell size (meters).
- **source** (*PointClass*) – Class of points to be re-classified.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

classifyPoints (*[source]* [*, target*], *confidence=0.0* [*, progress*])
Multiclass classification of points.

Parameters

- **source** (*PointClass*) – Class of points to be re-classified.
- **target** (list of *PointClass*) – Target point classes for classification.
- **confidence** (*float*) – Required confidence level from 0.0 to 1.0.
- **progress** (*Callable[[float], None]*) – Progress callback.

clear ()
Clears dense cloud data.

compactPoints (*[progress]*)
Permanently removes deleted points from dense cloud.

Parameters **progress** (*Callable[[float], None]*) – Progress callback.

copy ()
Create a copy of the dense cloud.

Returns Copy of the dense cloud.

Return type *DenseCloud*

cropSelectedPoints (*[point_classes]* [*, progress*])
Crop selected points.

Parameters

- **point_classes** (*PointClass* or list of *PointClass*) – Classes of points to be removed.
- **progress** (*Callable[[float], None]*) – Progress callback.

crs
Reference coordinate system.

Type *CoordinateSystem* or None

data_type
Data type used to store color values.

Type *DataType*

key
Dense cloud identifier.

Type int

label
Dense cloud label.

Type string

meta
Dense cloud meta data.

Type *MetaData*

modified
Modified flag.

Type bool

pickPoint (*origin, target, endpoints=1*)

Returns ray intersection with the point cloud (point on the ray nearest to some point).

Parameters

- **origin** (*Vector*) – Ray origin.
- **target** (*Vector*) – Point on the ray.
- **endpoints** (*int*) – Number of endpoints to check for (0 - line, 1 - ray, 2 - segment).

Returns Coordinates of the intersection point.

Return type *Vector*

point_count

Number of points in dense cloud.

Type *int*

removePoints (*point_classes[, progress]*)

Remove points.

Parameters

- **point_classes** (*PointClass* or list of *PointClass*) – Classes of points to be removed.
- **progress** (*Callable[[float], None]*) – Progress callback.

removeSelectedPoints (*[point_classes][, progress]*)

Remove selected points.

Parameters

- **point_classes** (*PointClass* or list of *PointClass*) – Classes of points to be removed.
- **progress** (*Callable[[float], None]*) – Progress callback.

renderDepth (*transform, calibration, point_size=1, resolution=1, cull_points=False, add_alpha=True*)

Render dense cloud depth image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **point_size** (*int*) – Point size.
- **resolution** (*float*) – Level of detail resolution in screen pixels.
- **cull_points** (*bool*) – Enable normal based culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.

Returns Rendered image.

Return type *Image*

renderImage (*transform, calibration, point_size=1, resolution=1, cull_points=False, add_alpha=True, raster_transform=RasterTransformNone*)

Render dense cloud image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.

- **calibration** (*Calibration*) – Camera calibration.
- **point_size** (*int*) – Point size.
- **resolution** (*float*) – Level of detail resolution in screen pixels.
- **cull_points** (*bool*) – Enable normal based culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.
- **raster_transform** (*RasterTransformType*) – Raster band transformation.

Returns Rendered image.

Return type *Image*

renderMask (*transform, calibration, point_size=1, resolution=1, cull_points=False*)

Render dense cloud mask image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **point_size** (*int*) – Point size.
- **resolution** (*float*) – Level of detail resolution in screen pixels.
- **cull_points** (*bool*) – Enable normal based culling.

Returns Rendered image.

Return type *Image*

renderNormalMap (*transform, calibration, point_size=1, resolution=1, cull_points=False, add_alpha=True*)

Render image with dense cloud normals for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **point_size** (*int*) – Point size.
- **resolution** (*float*) – Level of detail resolution in screen pixels.
- **cull_points** (*bool*) – Enable normal based culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.

Returns Rendered image.

Return type *Image*

renderPreview (*width = 2048, height = 2048*[, *transform*], *point_size=1*[, *progress*])

Generate dense cloud preview image.

Parameters

- **width** (*int*) – Preview image width.
- **height** (*int*) – Preview image height.
- **transform** (*Matrix*) – 4x4 viewpoint transformation matrix.
- **point_size** (*int*) – Point size.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

Returns Preview image.

Return type *Image*

resetFilters ()

Reset filters.

restorePoints (*[point_classes]* [, *progress*])

Restore deleted points.

Parameters

- **point_classes** (*PointClass* or list of *PointClass*) – Classes of points to be restored.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

selectMaskedPoints (*cameras*, *softness=4* [, *progress*])

Select dense points based on image masks.

Parameters

- **cameras** (list of *Camera*) – A list of cameras to use for selection.
- **softness** (*float*) – Mask edge softness.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

selectPointsByColor (*color*, *tolerance=10*, *channels='RGB'* [, *progress*])

Select dense points based on point colors.

Parameters

- **color** (*list of int*) – Color to select.
- **tolerance** (*int*) – Color tolerance.
- **channels** (*string*) – Combination of color channels to compare in ['R', 'G', 'B', 'H', 'S', 'V'].
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

setClassesFilter (*point_classes*)

Set filter by point classes.

Parameters **point_classes** (*PointClass* or list of *PointClass*) – List of point classes.

setConfidenceFilter (*min_confidence*, *max_confidence*)

Set filter by confidence.

Parameters

- **min_confidence** (*int*) – Minimum confidence value.
- **max_confidence** (*int*) – Maximum confidence value.

setSelectionFilter ()

Set filter by selection.

transform

4x4 dense cloud transformation matrix.

Type *Matrix*

updateStatistics ([*progress*])

Updates dense cloud statistics.

Parameters **progress** (*Callable[[float], None]*) – Progress callback.

class `Metashape.DepthMap`

Depth map data.

calibration

Depth map calibration.

Type *Calibration*

copy ()

Returns a copy of the depth map.

Returns Copy of the depth map.

Return type *DepthMap*

getCalibration (*level=0*)

Returns calibration data.

Parameters **level** (*int*) – Level index.

Returns Calibration data.

Return type *Calibration*

image (*[level]*)

Returns image data.

Parameters **level** (*int*) – Level index.

Returns Image data.

Return type *Image*

setCalibration (*calibration, level=0*)

Parameters

- **calibration** (*Calibration*) – Calibration data.
- **level** (*int*) – Level index.

setImage (*image, level=0*)

Parameters

- **image** (*Image*) – Image object with depth map data.
- **level** (*int*) – Level index.

class `Metashape.DepthMaps`

A set of depth maps generated for a chunk frame.

clear ()

Clears depth maps data.

copy ()

Create a copy of the depth maps.

Returns Copy of the depth maps.

Return type *DepthMaps*

items ()

List of items.

key
Depth maps identifier.

Type int

keys ()
List of item keys.

label
Depth maps label.

Type string

meta
Depth maps meta data.

Type *MetaData*

modified
Modified flag.

Type bool

values ()
List of item values.

class *Metashape.Document*
Metashape project.

Contains list of chunks available in the project. Implements processing operations that work with multiple chunks. Supports saving/loading project files.

The project currently opened in Metashape window can be accessed using *Metashape.app.document* attribute. Additional Document objects can be created as needed.

The following example saves active chunk from the opened project in a separate project:

```
>>> import Metashape
>>> doc = Metashape.app.document
>>> doc.save(path = "project.psz", chunks = [doc.chunk])
```

addChunk ()
Add new chunk to the document.

Returns Created chunk.

Return type *Chunk*

alignChunks (*chunks* [], *reference* [], *method*=0, *fit_scale*=True, *downscale*=1, *generic_preselection*=False, *filter_mask*=False, *mask_tiepoints*=False, *key_point_limit*=40000 [, *markers* [] [, *progress*]])

Align specified set of chunks.

Parameters

- **chunks** (*list of int*) – List of chunks to be aligned.
- **reference** (*int*) – Chunk to be used as a reference.
- **method** (*int*) – Alignment method.
- **fit_scale** (*bool*) – Fit chunk scale during alignment.
- **downscale** (*int*) – Alignment accuracy.
- **generic_preselection** (*bool*) – Enables image pair preselection.

- **filter_mask** (*bool*) – Filter points by mask.
- **mask_tiepoints** (*bool*) – Apply mask filter to tie points.
- **keypoint_limit** (*int*) – Maximum number of points for each photo.
- **markers** (*list of int*) – List of markers to be used for marker based alignment.
- **progress** (*Callable[[float], None]*) – Progress callback.

append (*document* [, *chunks*] [, *progress*])

Append the specified Document object to the current document.

Parameters

- **document** (*Document*) – Document object to be appended.
- **chunks** (list of *Chunk*) – List of chunks to append.
- **progress** (*Callable[[float], None]*) – Progress callback.

chunk

Active chunk.

Type *Chunk*

chunks

List of chunks in the document.

Type *Chunks*

clear ()

Clear the contents of the Document object.

copy ()

Return a copy of the document.

Returns A copy of the document.

Return type *Document*

findChunk (*key*)

Find chunk by its key.

Returns Found chunk.

Return type *Chunk*

mergeChunks (*merge_markers=False*, *merge_tiepoints=False*, *merge_depth_maps=False*,
merge_dense_clouds=True, *merge_models=False*, *merge_elevations=False*,
merge_orthomosaics=False [, *chunks*] [, *progress*])

Merge specified set of chunks.

Parameters

- **merge_markers** (*bool*) – Merge markers.
- **merge_tiepoints** (*bool*) – Merge tie points.
- **merge_depth_maps** (*bool*) – Merge depth maps.
- **merge_dense_clouds** (*bool*) – Merge dense clouds.
- **merge_models** (*bool*) – Merge models.
- **merge_elevations** (*bool*) – Merge DEMs.
- **merge_orthomosaics** (*bool*) – Merge orthomosaics.

- **chunks** (*list of int*) – List of chunks to process.
- **progress** (*Callable[[float], None]*) – Progress callback.

meta

Document meta data.

Type *MetaData*

modified

Modified flag.

Type bool

open (*path, read_only=False, ignore_lock=False*)

Load document from the specified file.

Parameters

- **path** (*string*) – Path to the file.
- **read_only** (*bool*) – Open document in read-only mode.
- **ignore_lock** (*bool*) – Ignore lock state for project modifications.

path

Path to the document file.

Type string

read_only

Read only status.

Type bool

remove (*items*)

Remove a set of items from the document.

Parameters **items** (*list of Chunk*) – A list of items to be removed.

save (*[path][, chunks], compression = 6, absolute_paths = False[, version]*)

Save document to the specified file.

Parameters

- **path** (*string*) – Optional path to the file.
- **chunks** (*list of Chunk*) – List of chunks to be saved.
- **compression** (*int*) – Project compression level.
- **absolute_paths** (*bool*) – Store absolute image paths.
- **version** (*string*) – Project version to save.

class Metashape.**Elevation**

Digital elevation model.

altitude (*point*)

Return elevation value at the specified point.

Parameters **point** (*Vector*) – Point coordinates in the elevation coordinate system.

Returns Elevation value.

Return type float

bottom

Y coordinate of the bottom side.

Type float

clear()

Clears elevation model data.

copy()

Create a copy of the elevation model.

Returns Copy of the elevation model.

Return type *Elevation*

crs

Coordinate system of elevation model.

Type *CoordinateSystem*

height

Elevation model height.

Type int

key

Elevation model identifier.

Type int

label

Elevation model label.

Type string

left

X coordinate of the left side.

Type float

max

Maximum elevation value.

Type float

meta

Elevation model meta data.

Type *MetaData*

min

Minimum elevation value.

Type float

modified

Modified flag.

Type bool

palette

Color palette.

Type dict

projection

Projection of elevation model.

Type *OrthoProjection*

resolution

DEM resolution in meters.

Type float

right

X coordinate of the right side.

Type float

top

Y coordinate of the top side.

Type float

width

Elevation model width.

Type int

class *Metashape*.**EulerAngles**

Euler angles in [EulerAnglesYPR, EulerAnglesOPK, EulerAnglesPOK, EulerAnglesANK]

class *Metashape*.**FaceCount**

Face count in [LowFaceCount, MediumFaceCount, HighFaceCount, CustomFaceCount]

class *Metashape*.**FilterMode**

Depth filtering mode in [NoFiltering, MildFiltering, ModerateFiltering, AggressiveFiltering]

class *Metashape*.**Image** (*width*, *height*, *channels*, *datatype*='U8')

n-channel image

Parameters

- **width** (*int*) – image width
- **height** (*int*) – image height
- **channels** (*string*) – color channel layout, e.g. 'RGB', 'RGBA', etc.
- **datatype** (*string*) – pixel data type in ['U8', 'U16', 'U32', 'F16', 'F32', 'F64']

channels

Channel mapping for the image.

Type string

cn

Number of color channels.

Type int

convert (*channels*[, *datatype*])

Convert image to specified data type and channel layout.

Parameters

- **channels** (*string*) – color channels to be loaded, e.g. 'RGB', 'RGBA', etc.
- **datatype** (*string*) – pixel data type in ['U8', 'U16', 'U32', 'F16', 'F32', 'F64']

Returns Converted image.

Return type *Image*

copy()

Return a copy of the image.

Returns copy of the image

Return type *Image*

data_type

Data type used to store pixel values.

Type string

fromstring(data, width, height, channels, datatype='U8')

Create image from byte array.

Parameters

- **data** (*string*) – raw image data
- **width** (*int*) – image width
- **height** (*int*) – image height
- **channels** (*string*) – color channel layout, e.g. 'RGB', 'RGBA', etc.
- **datatype** (*string*) – pixel data type in ['U8', 'U16', 'U32', 'F16', 'F32', 'F64']

Returns Created image.

Return type *Image*

gaussianBlur(radius)

Smooth image with a gaussian filter.

Parameters **radius** (*float*) – smoothing radius.

Returns Smoothed image.

Return type *Image*

height

Image height.

Type int

open(path, layer=0, datatype='U8', channels, x, y, w, h)

Load image from file.

Parameters

- **path** (*string*) – path to the image file
- **layer** (*int*) – image layer in case of multipage file
- **datatype** (*string*) – pixel data type in ['U8', 'U16', 'U32', 'F16', 'F32', 'F64']
- **channels** (*string*) – color channels to be loaded, e.g. 'RGB', 'RGBA', etc.
- **x** (*int*) – x offset of image region.
- **y** (*int*) – y offset of image region.
- **w** (*int*) – width of image region.
- **h** (*int*) – height of image region.

Returns Loaded image.

Return type *Image*

resize (*width, height*)

Resize image to specified dimensions.

Parameters

- **width** (*int*) – new image width
- **height** (*int*) – new image height

Returns resized image

Return type *Image*

save (*path* [, *compression*])

Save image to the file.

Parameters

- **path** (*string*) – path to the image file
- **compression** (*ImageCompression*) – compression options

tostring ()

Convert image to byte array.

Returns Raw image data.

Return type string

undistort (*calib, center_principal_point = True, square_pixels = True*)

Undistort image using provided calibration.

Parameters

- **calib** (*Calibration*) – lens calibration
- **center_principal_point** (*bool*) – moves principal point to the image center
- **square_pixels** (*bool*) – create image with square pixels

Returns undistorted image

Return type *Image*

uniformNoise (*amplitude*)

Add uniform noise with specified amplitude.

Parameters **amplitude** (*float*) – noise amplitude.

Returns Image with added noise.

Return type *Image*

warp (*calib0, trans0, calib1, trans1*)

Warp image by rotating virtual viewpoint.

Parameters

- **calib0** (*Calibration*) – initial calibration
- **trans0** (*Matrix*) – initial camera orientation as 4x4 matrix
- **calib1** (*Calibration*) – final calibration
- **trans1** (*Matrix*) – final camera orientation as 4x4 matrix

Returns warped image

Return type *Image*

width

Image width.

Type int

class Metashape.**ImageCompression**

Image compression parameters

class **TiffCompression**

Tiff compression in [TiffCompressionNone, TiffCompressionLZW, TiffCompressionJPEG, TiffCompressionPackbits, TiffCompressionDeflate]

ImageCompression.copy()

Return a copy of the object.

Returns A copy of the object.

Return type *Viewpoint*

ImageCompression.jpeg_quality

JPEG quality.

Type int

ImageCompression.tiff_big

Enable BigTIFF compression for TIFF files.

Type bool

ImageCompression.tiff_compression

Tiff compression.

Type int

ImageCompression.tiff_overviews

Enable image pyramid deneneration for TIFF files.

Type bool

ImageCompression.tiff_tiled

Export tiled TIFF.

Type bool

class Metashape.**ImageFormat**

Image format in [ImageFormatNone, ImageFormatJPEG, ImageFormatTIFF, ImageFormatPNG, ImageFormatBMP, ImageFormatEXR, ImageFormatPNM, ImageFormatSGI, ImageFormatCR2, ImageFormatSEQ, ImageFormatBIL, ImageFormatXYZ, ImageFormatARA, ImageFormatTGA, ImageFormatDDS, ImageFormatJP2, ImageFormatWebP]

class Metashape.**ImageLayout**

Image layout in [UndefinedLayout, FlatLayout, MultiframeLayout, MultiplaneLayout]

class Metashape.**Interpolation**

Interpolation mode in [DisabledInterpolation, EnabledInterpolation, Extrapolated]

class Metashape.**License**

License information.

activate (*license_key*)

Activate software online using a license key.

Parameters **key** (*string*) – Activation key.

activateOffline (*license_key*)

Create a request for offline activation.

Parameters **key** (*string*) – Activation key.

Returns Activation request.

Return type string

deactivate ()

Deactivate software online.

deactivateOffline ()

Create a request for offline deactivation.

Returns Deactivation request.

Return type string

valid

Metashape activation status.

Type bool

class Metashape.**MappingMode**

UV mapping mode in [LegacyMapping, GenericMapping, OrthophotoMapping, AdaptiveOrthophotoMapping, SphericalMapping, CameraMapping]

class Metashape.**Marker**

Marker instance

class **Projection**

Marker data().

coord

Point coordinates in pixels.

Type *Vector*

pinned

Pinned flag.

Type bool

valid

Valid flag.

Type bool

class Marker.**Projections**

Collection of projections specified for the marker

items ()

List of items.

keys ()

List of item keys.

values ()

List of item values.

class Marker.**Reference**

Marker reference data.

accuracy

Marker location accuracy.

Type *Vector*

enabled

Enabled flag.

Type bool

location

Marker coordinates.

Type *Vector*

class `Marker.Type`

Marker type in [Regular, Vertex, Fiducial]

`Marker.chunk`

Chunk the marker belongs to.

Type *Chunk*

`Marker.enabled`

Enables/disables the marker.

Type bool

`Marker.frames`

Marker frames.

Type list of *Marker*

`Marker.group`

Marker group.

Type *MarkerGroup*

`Marker.key`

Marker identifier.

Type int

`Marker.label`

Marker label.

Type string

`Marker.meta`

Marker meta data.

Type *MetaData*

`Marker.position`

Marker position in the current frame.

Type *Vector*

`Marker.position_covariance`

Marker position covariance.

Type *Matrix*

`Marker.projections`

List of marker projections.

Type *MarkerProjections*

`Marker.reference`

Marker reference data.

Type *MarkerReference*

Marker.selected
Selects/deselects the marker.

Type bool

Marker.sensor
Fiducial mark sensor.

Type *Sensor*

Marker.type
Marker type.

Type *Marker.Type*

class Metashape.MarkerGroup

MarkerGroup objects define groups of multiple markers. The grouping is established by assignment of a MarkerGroup instance to the Marker.group attribute of participating markers.

label
Marker group label.

Type string

selected
Current selection state.

Type bool

class Metashape.Mask

Mask instance

copy ()
Returns a copy of the mask.

Returns Copy of the mask.

Return type *Mask*

image ()
Returns image data.

Returns Image data.

Return type *Image*

invert ()
Create inverted copy of the mask.

Returns Inverted copy of the mask.

Return type *Mask*

load (path[, layer])
Loads mask from file.

Parameters

- **path** (*string*) – Path to the image file to be loaded.
- **layer** (*int*) – Optional layer index in case of multipage files.

setImage (image)

Parameters **image** (*Image*) – Image object with mask data.

class `Metashape.MaskOperation`
Mask operation in [`MaskOperationReplacement`, `MaskOperationUnion`, `MaskOperationIntersection`, `MaskOperationDifference`]

class `Metashape.MaskSource`
Mask source in [`MaskSourceAlpha`, `MaskSourceFile`, `MaskSourceBackground`, `MaskSourceModel`]

class `Metashape.Masks`
A set of masks for a chunk frame.

items ()
List of items.

keys ()
List of item keys.

meta
Thumbnails meta data.

Type `MetaData`

modified
Modified flag.

Type `bool`

values ()
List of item values.

class `Metashape.Matrix`
m-by-n matrix

```
>>> import Metashape
>>> m1 = Metashape.Matrix.Diag( (1,2,3,4) )
>>> m3 = Metashape.Matrix( [[1,2,3,4], [1,2,3,4], [1,2,3,4], [1,2,3,4]] )
>>> m2 = m1.inv()
>>> m3 = m1 * m2
>>> x = m3.det()
>>> if x == 1:
...     Metashape.app.messageBox("Diagonal matrix dimensions: " + str(m3.size))
```

Diag (*vector*)
Create a diagonal matrix.

Parameters **vector** (*Vector* or list of floats) – The vector of diagonal entries.

Returns A diagonal matrix.

Return type *Matrix*

Rotation (*matrix*)
Create a rotation matrix.

Parameters **matrix** (*Matrix*) – The 3x3 rotation matrix.

Returns 4x4 matrix representing rotation.

Return type *Matrix*

Scale (*scale*)
Create a scale matrix.

Parameters **scale** (*Vector*) – The scale vector.

Returns A matrix representing scale.

Return type *Matrix*

Translation (*vector*)

Create a translation matrix.

Parameters **vector** (*Vector*) – The translation vector.

Returns A matrix representing translation.

Return type *Matrix*

col (*index*)

Returns column of the matrix.

Returns matrix column.

Return type *Vector*

copy ()

Returns a copy of this matrix.

Returns an instance of itself

Return type *Matrix*

det ()

Return the determinant of a matrix.

Returns Return a the determinant of a matrix.

Return type float

inv ()

Returns an inverted copy of the matrix.

Returns inverted matrix.

Return type *Matrix*

mulp (*point*)

Transforms a point in homogeneous coordinates.

Parameters **point** (*Vector*) – The point to be transformed.

Returns transformed point.

Return type *Vector*

mulv (*vector*)

Transforms vector in homogeneous coordinates.

Parameters **vector** (*Vector*) – The vector to be transformed.

Returns transformed vector.

Return type *Vector*

rotation ()

Returns rotation component of the 4x4 matrix.

Returns rotation component

Return type *Matrix*

row (*index*)

Returns row of the matrix.

Returns matrix row.

Return type *Vector*

scale ()

Returns scale component of the 4x4 matrix.

Returns scale component

Return type float

size

Matrix dimensions.

Type tuple

svd ()

Returns singular value decomposition of the matrix.

Returns u, s, v tuple where $a = u * \text{diag}(s) * v$

Return type *Matrix Vector Matrix* tuple

t ()

Return a new, transposed matrix.

Returns a transposed matrix

Return type *Matrix*

translation ()

Returns translation component of the 4x4 matrix.

Returns translation component

Return type *Vector*

zero ()

Set all matrix elements to zero.

class Metashape.**MetaData** (*object*)

Collection of object properties

copy ()

Return a copy of the object.

Returns A copy of the object.

Return type *MetaData*

items ()

List of items.

keys ()

List of item keys.

values ()

List of item values.

class Metashape.**Model**

Triangular mesh model instance

class **Face**

Triangular face of the model

hidden

Face visibility flag.

Type bool

selected
Face selection flag.
Type bool

tex_index
Texture page index.
Type int

tex_vertices
Texture vertex indices.
Type tuple of 3 int

vertices
Vertex indices.
Type tuple of 3 int

class `Model.Faces`
Collection of model faces

resize (*count*)
Resize faces list.
Parameters `count` (*int*) – new face count

class `Model.Statistics`
Mesh statistics

components
Number of connected components.
Type int

degenerate_faces
Number of degenerate faces.
Type int

duplicate_faces
Number of duplicate faces.
Type int

faces
Total number of faces.
Type int

flipped_normals
Number of edges with flipped normals.
Type int

free_vertices
Number of free vertices.
Type int

multiple_edges
Number of edges connecting more than 2 faces.
Type int

open_edges
Number of open edges.
Type int

out_of_range_indices
Number of out of range indices.
Type int

similar_vertices
Number of similar vertices.
Type int

vertices
Total number of vertices.
Type int

zero_faces
Number of zero faces.
Type int

class `Model.TexVertex`
Texture vertex of the model

coord
Vertex coordinates.
Type tuple of 2 float

class `Model.TexVertices`
Collection of model texture vertices

resize (*count*)
Resize vertex list.
Parameters `count` (*int*) – new vertex count

class `Model.Texture`
Model texture.

image (*page=0*)
Return texture image.
Parameters `page` (*int*) – Texture index for multitextured models.
Returns Texture image.
Return type *Image*

label
Animation label.
Type string

meta
Camera track meta data.
Type *MetaData*

model
Model the texture belongs to.
Type *Model*

setImage (*image, page=0*)
Initialize texture from image data.
Parameters

- **image** (*Image*) – Texture image.
- **page** (*int*) – Texture index for multitextured models.

type
Texture type.
Type *Model.TextureType*

class `Model.TextureType`
Texture type in [DiffuseMap, NormalMap, OcclusionMap]

class `Model.Vertex`

Vertex of the model

color

Vertex color.

Type tuple of 3 int

confidence

Vertex confidence.

Type float

coord

Vertex coordinates.

Type *Vector*

class `Model.Vertices`

Collection of model vertices

resize (*count*)

Resize vertex list.

Parameters **count** (*int*) – new vertex count

`Model.addTexture` (*type=Model.DiffuseMap*)

Add new texture to the model.

Parameters **type** (*Model.TextureType*) – Texture type.

Returns Created texture.

Return type *Model.Texture*

`Model.area` ()

Return area of the model surface.

Returns Model area.

Return type float

`Model.bands`

List of color bands.

Type list of string

`Model.clear` ()

Clears model data.

`Model.closeHoles` (*level = 30*)

Fill holes in the model surface.

Parameters **level** (*int*) – Hole size threshold in percents.

`Model.copy` ()

Create a copy of the model.

Returns Copy of the model.

Return type *Model*

`Model.cropSelection` ()

Crop selected faces and free vertices from the mesh.

`Model.data_type`

Data type used to store color values.

Type *DataType*

Model.faces

Collection of mesh faces.

Type MeshFaces

Model.fixTopology()

Remove polygons causing topological problems.

Model.getActiveTexture (*type=Model.DiffuseMap*)

Return active texture.

Parameters **type** (*Model.TextureType*) – Texture type.

Returns Texture image.

Return type *Image*

Model.key

Model identifier.

Type int

Model.label

Model label.

Type string

Model.loadTexture (*path*)

Load texture from the specified file.

Parameters **path** (*string*) – Path to the image file.

Model.meta

Model meta data.

Type *MetaData*

Model.modified

Modified flag.

Type bool

Model.pickPoint (*origin, target, endpoints=1*)

Return ray intersection with mesh.

Parameters

- **origin** (*Vector*) – Ray origin.
- **target** (*Vector*) – Point on the ray.
- **endpoints** (*int*) – Number of endpoints to check for (0 - line, 1 - ray, 2 - segment).

Returns Coordinates of the intersection point.

Return type *Vector*

Model.remove (*items*)

Remove textures from the model.

Parameters **items** (list of *Model.Texture*) – A list of textures to be removed.

Model.removeComponents (*size*)

Remove small connected components.

Parameters **size** (*int*) – Threshold on the polygon count of the components to be removed.

`Model.removeSelection()`

Remove selected faces and free vertices from the mesh.

`Model.renderDepth(transform, calibration, cull_faces=True, add_alpha=True)`

Render model depth image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **cull_faces** (*bool*) – Enable back-face culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.

Returns Rendered image.

Return type *Image*

`Model.renderImage(transform, calibration, cull_faces=True, add_alpha=True, raster_transform=RasterTransformNone)`

Render model image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **cull_faces** (*bool*) – Enable back-face culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.
- **raster_transform** (*RasterTransformType*) – Raster band transformation.

Returns Rendered image.

Return type *Image*

`Model.renderMask(transform, calibration, cull_faces=True)`

Render model mask image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **cull_faces** (*bool*) – Enable back-face culling.

Returns Rendered image.

Return type *Image*

`Model.renderNormalMap(transform, calibration, cull_faces=True, add_alpha=True)`

Render image with model normals for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **cull_faces** (*bool*) – Enable back-face culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.

Returns Rendered image.

Return type *Image*

`Model.renderPreview` (*width* = 2048, *height* = 2048[, *transform*][, *progress*])
Generate model preview image.

Parameters

- **width** (*int*) – Preview image width.
- **height** (*int*) – Preview image height.
- **transform** (*Matrix*) – 4x4 viewpoint transformation matrix.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

Returns Preview image.

Return type *Image*

`Model.saveTexture` (*path*)
Save texture to the specified file.

Parameters **path** (*string*) – Path to the image file.

`Model.setActiveTexture` (*texture*, *type*=*Model.DiffuseMap*)
Set active texture.

Parameters

- **texture** (*Model.Texture*) – Texture to set.
- **type** (*Model.TextureType*) – Texture type.

`Model.statistics` ([*progress*])
Return mesh statistics.

Parameters **progress** (*Callable*[[*float*], *None*]) – Progress callback.

Returns Mesh statistics.

Return type *Model.Statistics*

`Model.tex_vertices`
Collection of mesh texture vertices.

Type *MeshTexVertices*

`Model.textures`
List of model textures.

Type list of *Model.Texture*

`Model.transform` (*transform*)
Transform vertex coordinates.

Parameters **transform** (*Matrix*) – 4x4 transformation matrix.

`Model.vertices`
Collection of mesh vertices.

Type *MeshVertices*

`Model.volume` ()
Return volume of the closed model surface.

Returns Model volume.

Return type *float*

class `Metashape.ModelFormat`

Model format in [`ModelFormatNone`, `ModelFormatOBJ`, `ModelFormat3DS`, `ModelFormatVRML`, `ModelFormatPLY`, `ModelFormatCOLLADA`, `ModelFormatU3D`, `ModelFormatPDF`, `ModelFormatDXF`, `ModelFormatFBX`, `ModelFormatKMZ`, `ModelFormatCTM`, `ModelFormatSTL`, `ModelFormatDXF_3DF`, `ModelFormatTLS`, `ModelFormatABC`, `ModelFormatOSGB`, `ModelFormatGLTF`, `ModelFormatX3D`]

class `Metashape.NetworkClient`

`NetworkClient` class provides access to the network processing server and allows to create and manage tasks.

The following example connects to the server and lists active tasks:

```
>>> import Metashape
>>> client = Metashape.NetworkClient()
>>> client.connect('127.0.0.1')
>>> client.batchList()
```

abortBatch (*batch_id*)

Abort batch.

Parameters `batch_id` (*int*) – Batch id.

abortNode (*node_id*)

Abort node.

Parameters `node_id` (*int*) – Node id.

batchList (*revision=0*)

Get list of batches.

Parameters `revision` (*int*) – First revision to get.

Returns List of batches.

Return type dict

batchStatus (*batch_id*, *revision=0*)

Get batch status.

Parameters

- `batch_id` (*int*) – Batch id.
- `revision` (*int*) – First revision to get.

Returns Batch status.

Return type dict

connect (*host*, *port=5840*)

Connect to the server.

Parameters

- `host` (*string*) – Server hostname.
- `port` (*int*) – Communication port.

createBatch (*path*, *tasks*[, *meta*])

Create new batch.

Parameters

- `path` (*string*) – Project path relative to root folder.
- `tasks` (list of `NetworkTask`) – Project path relative to root folder.

- **meta** (*MetaData*) – Batch metadata.

Returns Batch id.

Return type int

disconnect ()

Disconnect from the server.

dumpBatches (*[batch_ids]*)

Dump current state of batches.

Parameters **batch_ids** (*list of int*) – List of batch ids to dump.

Returns Batches data.

Return type string

findBatch (*path*)

Get batch id based on project path.

Parameters **path** (*string*) – Project path relative to root folder.

Returns Batch id.

Return type int

loadBatches (*data*)

Load batches from dump.

Parameters **data** (*string*) – Batches data.

nodeList (*revision=0*)

Get list of nodes.

Parameters **revision** (*int*) – First revision to get.

Returns List of nodes.

Return type dict

nodeStatus (*node_id, revision=0*)

Get node status.

Parameters

- **node_id** (*int*) – Node id.
- **revision** (*int*) – First revision to get.

Returns Node status.

Return type dict

pauseBatch (*batch_id*)

Pause batch.

Parameters **batch_id** (*int*) – Batch id.

pauseNode (*node_id*)

Pause node.

Parameters **node_id** (*int*) – Node id.

quitNode (*node_id*)

Quit node.

Parameters **node_id** (*int*) – Node id.

resumeBatch (*batch_id*)

Resume batch.

Parameters **batch_id** (*int*) – Batch id.

resumeNode (*node_id*)

Resume node.

Parameters **node_id** (*int*) – Node id.

serverInfo ()

Get server information.

Returns Server information.

Return type dict

setBatchNodeLimit (*batch_id, node_limit*)

Set node limit of the batch.

Parameters

- **batch_id** (*int*) – Batch id.
- **node_limit** (*int*) – Node limit of the batch (0 - unlimited).

setBatchPriority (*batch_id, priority*)

Set batch priority.

Parameters

- **batch_id** (*int*) – Batch id.
- **priority** (*int*) – Batch priority (2 - Highest, 1 - High, 0 - Normal, -1 - Low, -2 - Lowest).

setMasterServer ([*host*])

Set or reset master server.

Parameters **host** (*string*) – Master server hostname.

setNodeCPUEnable (*node_id, cpu_enable*)

Set node CPU enable flag.

Parameters

- **node_id** (*int*) – Node id.
- **cpu_enable** (*bool*) – CPU enable flag.

setNodeCapability (*node_id, capability*)

Set node capability.

Parameters

- **node_id** (*int*) – Node id.
- **capability** (*int*) – Node capability (1 - CPU, 2 - GPU, 3 - Any).

setNodeGPUMask (*node_id, gpu_mask*)

Set node GPU mask.

Parameters

- **node_id** (*int*) – Node id.
- **gpu_mask** (*int*) – GPU device mask.

setNodePriority (*node_id*, *priority*)

Set node priority.

Parameters

- **node_id** (*int*) – Node id.
- **priority** (*int*) – Node priority (2 - Highest, 1 - High, 0 - Normal, -1 - Low, -2 - Lowest).

class Metashape.**NetworkTask**

NetworkTask class contains information about network task and its parameters.

The following example creates a new processing task and submits it to the server:

```
>>> import Metashape
>>> task = Metashape.NetworkTask()
>>> task.name = 'MatchPhotos'
>>> task.params['keypoint_limit'] = 40000
>>> client = Metashape.NetworkClient()
>>> client.connect('127.0.0.1')
>>> batch_id = client.createBatch('processing/project.psx', [task])
>>> client.resumeBatch(batch_id)
```

chunks

List of chunks.

Type list

encode ()

Create a dictionary with task parameters.

frames

List of frames.

Type list

name

Task name.

Type string

params

Task parameters.

Type dict

supports_gpu

GPU support flag.

Type bool

class Metashape.**OrthoProjection**

Orthographic projection.

class **Type**

Projection type in [Planar, Cylindrical]

OrthoProjection.copy ()

Return a copy of the object.

Returns A copy of the object.

Return type *OrthoProjection*

`OrthoProjection.crs`
Base coordinate system.

Type *CoordinateSystem*

`OrthoProjection.matrix`
Ortho transformation matrix.

Type *Matrix*

`OrthoProjection.radius`
Cylindrical projection radius.

Type float

`OrthoProjection.transform` (*point, source, target*)
Transform point coordinates between coordinate systems.

Parameters

- **point** (2 or 3 component *Vector*) – Point coordinates.
- **source** (*OrthoProjection*) – Source coordinate system.
- **target** (*OrthoProjection*) – Target coordinate system.

Returns Transformed point coordinates.

Return type *Vector*

`OrthoProjection.type`
Projection type.

Type *OrthoProjection.Type*

class `Metashape.Orthomosaic`
Orthomosaic data.

The following sample assigns to the first shape in the chunk the image from the first camera for the orthomosaic patch and updates the mosaic:

```
>>> import Metashape
>>> chunk = Metashape.app.document.chunk
>>> ortho = chunk.orthomosaic
>>> camera = chunk.cameras[0]
>>> shape = chunk.shapes[0]
>>> patch = Metashape.Orthomosaic.Patch()
>>> patch.image_keys = [camera.key]
>>> ortho.patches[shape] = patch
>>> ortho.update()
```

class `Patch`
Orthomosaic patch.

copy ()
Returns a copy of the patch.
Returns Copy of the patch.
Return type *Orthomosaic.Patch*

excluded
Excluded flag.
Type bool

image_keys

Image keys.

Type list of int

class Orthomosaic.**Patches**

A set of orthomosaic patches.

items ()

List of items.

keys ()

List of item keys.

values ()

List of item values.

Orthomosaic.**bands**

List of color bands.

Type list of string

Orthomosaic.**bottom**

Y coordinate of the bottom side.

Type float

Orthomosaic.**clear** ()

Clears orthomosaic data.

Orthomosaic.**copy** ()

Create a copy of the orthomosaic.

Returns Copy of the orthomosaic.

Return type *Orthomosaic*

Orthomosaic.**crs**

Coordinate system of orthomosaic.

Type *CoordinateSystem*

Orthomosaic.**data_type**

Data type used to store color values.

Type *DataType*

Orthomosaic.**height**

Orthomosaic height.

Type int

Orthomosaic.**key**

Orthomosaic identifier.

Type int

Orthomosaic.**label**

Orthomosaic label.

Type string

Orthomosaic.**left**

X coordinate of the left side.

Type float

`Orthomosaic.meta`

Orthomosaic meta data.

Type *MetaData*

`Orthomosaic.modified`

Modified flag.

Type bool

`Orthomosaic.patches`

Orthomosaic patches.

Type *Orthomosaic.Patches*

`Orthomosaic.projection`

Orthomosaic projection.

Type *OrthoProjection*

`Orthomosaic.removeOrthophotos()`

Remove orthorectified images from orthomosaic.

`Orthomosaic.renderPreview(width = 2048, height = 2048[, progress])`

Generate orthomosaic preview image. :arg width: Preview image width. :type width: int :arg height: Preview image height. :type height: int :arg progress: Progress callback. :type progress: Callable[[float], None] :return: Preview image. :rtype: *Image*

`Orthomosaic.reset([progress])`

Reset all edits to orthomosaic.

Parameters `progress` (*Callable[[float], None]*) – Progress callback.

`Orthomosaic.resolution`

Orthomosaic resolution in meters.

Type float

`Orthomosaic.right`

X coordinate of the right side.

Type float

`Orthomosaic.top`

Y coordinate of the top side.

Type float

`Orthomosaic.update([progress])`

Apply edits to orthomosaic.

Parameters `progress` (*Callable[[float], None]*) – Progress callback.

`Orthomosaic.width`

Orthomosaic width.

Type int

class `Metashape.Photo`

Photo instance

`alpha()`

Returns alpha channel data.

Returns Alpha channel data.

Return type *Image*

copy ()

Returns a copy of the photo.

Returns Copy of the photo.

Return type *Photo*

image ([*channels*] [, *datatype*])

Returns image data.

Parameters

- **datatype** (*string*) – pixel data type in ['U8', 'U16', 'U32', 'F16', 'F32', 'F64']
- **channels** (*string*) – color channels to be loaded, e.g. 'RGB', 'RGBA', etc.

Returns Image data.

Return type *Image*

imageMeta ()

Returns image meta data.

Returns Image meta data.

Return type *MetaData*

layer

Layer index in the image file.

Type int

meta

Frame meta data.

Type *MetaData*

open (*path* [, *layer*])

Loads specified image file.

Parameters

- **path** (*string*) – Path to the image file to be loaded.
- **layer** (*int*) – Optional layer index in case of multipage files.

path

Path to the image file.

Type string

thumbnail (*width=192, height=192*)

Creates new thumbnail with specified dimensions.

Returns Thumbnail data.

Return type *Thumbnail*

class *Metashape*.**PointCloud**

Point class in [Created, Unclassified, Ground, LowVegetation, MediumVegetation, HighVegetation, Building, LowPoint, ModelKeyPoint, Water, Rail, RoadSurface, OverlapPoints, WireGuard, WireConductor, TransmissionTower, WireConnector, BridgeDeck, HighNoise, Car, Manmade]

class *Metashape*.**PointCloud**

Sparse point cloud instance

class Cameras

Collection of *PointCloud.Projections* objects indexed by corresponding cameras

class PointCloud.Filter

Sparse point cloud filter

The following example selects all points of the sparse cloud from the active chunk that have reprojection error higher than defined threshold:

```
>>> chunk = Metashape.app.document.chunk # active chunk
>>> threshold = 0.5
>>> f = Metashape.PointCloud.Filter()
>>> f.init(chunk, criterion = Metashape.PointCloud.Filter.ReprojectionError)
>>> f.selectPoints(threshold)
```

class Criterion

Point filtering criterion in [ReprojectionError, ReconstructionUncertainty, ImageCount, ProjectionAccuracy]

`PointCloud.Filter.init` (*points*, *criterion*, *progress*)

Initialize point cloud filter based on specified criterion.

Parameters

- **points** (*PointCloud* or *Chunk*) – Point cloud to filter.
- **criterion** (*PointCloud.Filter.Criterion*) – Point filter criterion.
- **progress** (*Callable[[float], None]*) – Progress callback.

`PointCloud.Filter.max_value`

Maximum value.

Type int or double

`PointCloud.Filter.min_value`

Minimum value.

Type int or double

`PointCloud.Filter.removePoints` (*threshold*)

Remove points based on specified threshold.

Parameters **threshold** (*float*) – Criterion threshold.

`PointCloud.Filter.resetSelection` ()

Reset previously made selection.

`PointCloud.Filter.selectPoints` (*threshold*)

Select points based on specified threshold.

Parameters **threshold** (*float*) – Criterion threshold.

`PointCloud.Filter.values`

List of values.

Type list of int or list of double

class PointCloud.Point

3D point in the point cloud

coord

Point coordinates.

Type *Vector*

cov

Point coordinates covariance matrix.

Type *Matrix*

selected
Point selection flag.
Type bool

track_id
Track index.
Type int

valid
Point valid flag.
Type bool

class `PointCloud.Points`
Collection of 3D points in the point cloud

copy ()
Returns a copy of points buffer.
Returns Copy of points buffer.
Return type `PointCloud.Points`

resize (*count*)
Resize points list.
Parameters **count** (*int*) – new point count

class `PointCloud.Projection`
Projection of the 3D point on the photo

coord
Projection coordinates.
Type tuple of 2 float

size
Point size.
Type float

track_id
Track index.
Type int

class `PointCloud.Projections`
Collection of `PointCloud.Projection` for the camera

copy ()
Returns a copy of projections buffer.
Returns Copy of projections buffer.
Return type `PointCloud.Projections`

resize (*count*)
Resize projections list.
Parameters **count** (*int*) – new projections count

class `PointCloud.Track`
Track in the point cloud

color
Track color.
Type tuple of 3 int

class `PointCloud.Tracks`
Collection of tracks in the point cloud

copy()
Returns a copy of tracks buffer.
Returns Copy of tracks buffer.
Return type *PointCloud.Tracks*

resize(count)
Resize track list.
Parameters **count** (*int*) – new track count

PointCloud.bands
List of color bands.
Type list of string

PointCloud.cleanup([progress])
Remove points with insufficient number of projections.
Parameters **progress** (*Callable[[float], None]*) – Progress callback.

PointCloud.copy(keypoints=True)
Returns a copy of the point cloud.
Parameters **keypoints** (*bool*) – copy key points data.
Returns Copy of the point cloud.
Return type *PointCloud*

PointCloud.cropSelectedPoints()
Crop selected points.

PointCloud.cropSelectedTracks()
Crop selected tie points.

PointCloud.data_type
Data type used to store color values.
Type *DataType*

PointCloud.export(path, format='obj'[, projection])
Export point cloud.
Parameters

- **path** (*string*) – Path to output file.
- **format** (*string*) – Export format in ['obj', 'ply'].
- **projection** (*Matrix* or *CoordinateSystem*) – Sets output projection.

PointCloud.meta
Point cloud meta data.
Type *MetaData*

PointCloud.modified
Modified flag.
Type *bool*

PointCloud.pickPoint(origin, target, endpoints=1)
Returns ray intersection with the point cloud (point on the ray nearest to some point).
Parameters

- **origin** (*Vector*) – Ray origin.

- **target** (*Vector*) – Point on the ray.
- **endpoints** (*int*) – Number of endpoints to check for (0 - line, 1 - ray, 2 - segment).

Returns Coordinates of the intersection point.

Return type *Vector*

PointCloud.points

List of points.

Type *PointCloud.Points*

PointCloud.projections

Point projections for each photo.

Type *PointCloud.Projections*

PointCloud.removeKeypoints ()

Remove keypoints from point cloud.

PointCloud.removeSelectedPoints ()

Remove selected points.

PointCloud.removeSelectedTracks ()

Remove selected tie points.

PointCloud.renderDepth (*transform*, *calibration*, *point_size=1*, *cull_points=False*,
add_alpha=True)

Render point cloud depth image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **point_size** (*int*) – Point size.
- **cull_points** (*bool*) – Enable normal based culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.

Returns Rendered image.

Return type *Image*

PointCloud.renderImage (*transform*, *calibration*, *point_size=1*, *cull_points=False*,
add_alpha=True, *raster_transform=RasterTransformNone*)

Render point cloud image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **point_size** (*int*) – Point size.
- **cull_points** (*bool*) – Enable normal based culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.
- **raster_transform** (*RasterTransformType*) – Raster band transformation.

Returns Rendered image.

Return type *Image*

`PointCloud.renderMask` (*transform*, *calibration*, *point_size=1*, *cull_points=False*)
Render point cloud mask image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **point_size** (*int*) – Point size.
- **cull_points** (*bool*) – Enable normal based culling.

Returns Rendered image.

Return type *Image*

`PointCloud.renderNormalMap` (*transform*, *calibration*, *point_size=1*, *cull_points=False*,
add_alpha=True)
Render image with point cloud normals for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **point_size** (*int*) – Point size.
- **cull_points** (*bool*) – Enable normal based culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.

Returns Rendered image.

Return type *Image*

`PointCloud.renderPreview` (*width = 2048*, *height = 2048* [, *transform*], *point_size=1* [, *progress*])
Generate point cloud preview image.

Parameters

- **width** (*int*) – Preview image width.
- **height** (*int*) – Preview image height.
- **transform** (*Matrix*) – 4x4 viewpoint transformation matrix.
- **point_size** (*int*) – Point size.
- **progress** (*Callable[[float], None]*) – Progress callback.

Returns Preview image.

Return type *Image*

`PointCloud.tracks`
List of tracks.

Type *PointCloud.Tracks*

class `Metashape.PointsFormat`

Point cloud format in [PointsFormatNone, PointsFormatOBJ, PointsFormatPLY, PointsFormatXYZ, PointsFormatLAS, PointsFormatExpe, PointsFormatU3D, PointsFormatPDF, PointsFormatE57, PointsFormatOC3, PointsFormatPotree, PointsFormatLAZ, PointsFormatCL3, PointsFormatPTS, PointsFormatPTX, PointsFormatDXF, PointsFormatCesium, PointsFormatPCD]

class `Metashape.Preselection`
Image pair preselection in [NoPreselection, GenericPreselection, ReferencePreselection]

class `Metashape.RPCModel`
Rational polynomial model.

copy ()
Return a copy of the object.
Returns A copy of the object.
Return type `RPCModel`

error (*point*, *proj*)
Returns projection error.
Parameters

- **point** (`Vector`) – Coordinates of the point to be projected.
- **proj** (`Vector`) – Pixel coordinates of the point.

Returns 2D projection error.
Return type `Vector`

image_offset
Image coordinate offset.
Type `Vector`

image_scale
Image coordinate scale.
Type `Vector`

line_den_coeff
Line denominator.
Type `Vector`

line_num_coeff
Line numerator.
Type `Vector`

load (*path*)
Load RPC model from file.
Parameters **path** (`string`) – path to RPC model file

object_offset
Object coordinate offset.
Type `Vector`

object_scale
Object coordinate scale.
Type `Vector`

project (*point*)
Returns projected pixel coordinates of the point.
Parameters **point** (`Vector`) – Coordinates of the point to be projected.
Returns 2D projected point coordinates.

Return type *Vector*

samp_den_coeff

Sample denominator.

Type *Vector*

samp_num_coeff

Sample numerator.

Type *Vector*

save (*path*)

Save RPC model to file.

Parameters **path** (*string*) – path to RPC model file

unproject (*point*)

Returns direction corresponding to the image point.

Parameters **point** (*Vector*) – Pixel coordinates of the point.

Returns 3D vector in the camera coordinate system.

Return type *Vector*

class `Metashape.RasterFormat`

Raster format in [RasterFormatNone, RasterFormatTiles, RasterFormatKMZ, RasterFormatXYZ, RasterFormatMBTiles, RasterFormatWW, RasterFormatTMS, RasterFormatGeoPackage]

class `Metashape.RasterTransform`

Raster transform definition.

calibrateRange ()

Auto detect range based on orthomosaic histogram.

copy ()

Return a copy of the object.

Returns A copy of the object.

Return type *RasterTransform*

enabled

Enable flag.

Type bool

false_color

False color channels.

Type list

formula

Raster calculator expression.

Type string

interpolation

Interpolation enable flag.

Type bool

palette

Color palette.

Type dict

range

Palette mapping range.

Type tuple

reset ()

Reset raster transform.

class Metashape.**RasterTransformType**

Raster transformation type in [RasterTransformNone, RasterTransformValue, RasterTransformPalette]

class Metashape.**ReferenceFormat**

Reference format in [ReferenceFormatNone, ReferenceFormatXML, ReferenceFormatTEL, ReferenceFormatCSV, ReferenceFormatMavinci, ReferenceFormatBramor, ReferenceFormatAPM]

class Metashape.**ReferenceItems**

Reference items in [ReferenceItemsCameras, ReferenceItemsMarkers, ReferenceItemsScalebars]

class Metashape.**ReferencePreselectionMode**

Reference preselection mode in [ReferencePreselectionSource, ReferencePreselectionEstimated, ReferencePreselectionSequential]

class Metashape.**Region**

Region parameters

center

Region center coordinates.

Type *Vector*

copy ()

Return a copy of the object.

Returns A copy of the object.

Return type *Region*

rot

Region rotation matrix.

Type *Matrix*

size

Region size.

Type *Vector*

class Metashape.**RotationOrder**

Rotation order in [RotationOrderXYZ, RotationOrderXZY, RotationOrderYXZ, RotationOrderYZX, RotationOrderZXY, RotationOrderZYX]

class Metashape.**Scalebar**

Scale bar instance

class **Reference**

Scale bar reference data

accuracy

Scale bar length accuracy.

Type float

distance

Scale bar length.

Type float

enabled

Enabled flag.

Type boolScalebar.**chunk**

Chunk the scalebar belongs to.

Type *Chunk*Scalebar.**frames**

Scale bar frames.

Type list of *Scalebar*Scalebar.**group**

Scale bar group.

Type *ScalebarGroup*Scalebar.**key**

Scale bar identifier.

Type intScalebar.**label**

Scale bar label.

Type stringScalebar.**meta**

Scale bar meta data.

Type *MetaData*Scalebar.**point0**

Start of the scale bar.

Type *Marker*Scalebar.**point1**

End of the scale bar.

Type *Marker*Scalebar.**reference**

Scale bar reference data.

Type *ScalebarReference*Scalebar.**selected**

Selects/deselects the scale bar.

Type bool**class** Metashape.**ScalebarGroup**

ScalebarGroup objects define groups of multiple scale bars. The grouping is established by assignment of a ScalebarGroup instance to the Scalebar.group attribute of participating scale bars.

label

Scale bar group label.

Type string**selected**

Current selection state.

Type bool

class `Metashape.Sensor`

Sensor instance

class `Reference`

Sensor reference data.

accuracy

Sensor location accuracy.

Type `Vector`

enabled

Location enabled flag.

Type bool

location

Sensor coordinates.

Type `Vector`

location_accuracy

Sensor location accuracy.

Type `Vector`

location_enabled

Location enabled flag.

Type bool

rotation

Sensor rotation angles.

Type `Vector`

rotation_accuracy

Sensor rotation accuracy.

Type `Vector`

rotation_enabled

Rotation enabled flag.

Type bool

class `Sensor.Type`

Sensor type in [Frame, Fisheye, Spherical, RPC]

`Sensor.antenna`

GPS antenna correction.

Type `Antenna`

`Sensor.bands`

List of color bands.

Type list of string

`Sensor.black_level`

Black level for each band.

Type list of float

`Sensor.calibrateFiducials` (*resolution=0.014*)

Fit fiducial coordinates to image measurements.

Parameters `resolution` (*float*) – Scanning resolution in mm/pix.

Sensor.calibration
Adjusted calibration of the photo.
Type *Calibration*

Sensor.chunk
Chunk the sensor belongs to.
Type *Chunk*

Sensor.data_type
Data type used to store color values.
Type *DataType*

Sensor.fiducials
Fiducial marks.
Type list of *Marker*

Sensor.film_camera
Film camera flag.
Type bool

Sensor.fixed
Fix calibration flag.
Type bool

Sensor.fixed_calibration
Fix calibration flag.
Type bool

Sensor.fixed_location
Fix location flag.
Type bool

Sensor.fixed_params
List of fixed calibration parameters.
Type list of string

Sensor.fixed_rotation
Fix rotation flag.
Type bool

Sensor.focal_length
Focal length in mm.
Type float

Sensor.height
Image height.
Type int

Sensor.key
Sensor identifier.
Type int

Sensor.label
Sensor label.

Type string

Sensor.layer_index
Sensor layer index.

Type int

Sensor.location
Sensor plane location.

Type *Vector*

Sensor.location_covariance
Sensor plane location covariance.

Type *Matrix*

Sensor.master
Master sensor.

Type *Sensor*

Sensor.normalize_sensitivity
Enable sensitivity normalization.

Type bool

Sensor.normalize_to_float
Convert pixel values to floating point after normalization.

Type bool

Sensor.photo_params
List of image-variant calibration parameters.

Type list of string

Sensor.pixel_height
Pixel height in mm.

Type float

Sensor.pixel_size
Pixel size in mm.

Type *Vector*

Sensor.pixel_width
Pixel width in mm.

Type float

Sensor.planes
Sensor planes.

Type list of *Sensor*

Sensor.reference
Sensor reference data.

Type SensorReference

Sensor.rolling_shutter
Enable rolling shutter compensation.

Type bool

Sensor.rotation
Sensor plane rotation.

Type *Matrix*

Sensor.rotation_covariance
Sensor plane rotation covariance.

Type *Matrix*

Sensor.sensitivity
Sensitivity for each band.

Type list of float

Sensor.type
Sensor projection model.

Type *Sensor.Type*

Sensor.user_calib
Custom calibration used as initial calibration during photo alignment.

Type *Calibration*

Sensor.vignetting
Vignetting for each band.

Type list of *Vignetting*

Sensor.width
Image width.

Type int

class Metashape.Shape
Shape data.

class BoundaryType
Shape boundary type in [NoBoundary, OuterBoundary, InnerBoundary]

class Shape.Type
Shape type in [Point, Polyline, Polygon]

class Shape.Vertices
Collection of shape vertices

Shape.area ()
Return area of the shape on DEM.

Returns Shape area.

Return type float

Shape.attributes
Shape attributes.

Type *MetaData*

Shape.boundary_type
Shape boundary type.

Type *Shape.BoundaryType*

Shape.group
Shape group.

Type *ShapeGroup*

Shape.has_z

Z enable flag.

Type bool

Shape.key

Shape identifier.

Type int

Shape.label

Shape label.

Type string

Shape.perimeter2D()

Return perimeter of the shape on DEM.

Returns Shape perimeter.

Return type float

Shape.perimeter3D()

Return perimeter of the shape.

Returns Shape perimeter.

Return type float

Shape.selected

Selects/deselects the shape.

Type bool

Shape.type

Shape type.

Type *Shape.Type*

Shape.vertex_ids

List of shape vertex ids.

Type ShapeVertices

Shape.vertices

List of shape vertices.

Type ShapeVertices

Shape.volume (*level='bestfit'*)

Return volume of the shape measured on DEM above and below best fit, mean level or custom level plane.

Parameters **level** (*float*) – Plane level: 'bestfit', 'mean' or custom value.

Returns Shape volumes.

Return type dict

class Metashape.**ShapeGroup**

ShapeGroup objects define groups of multiple shapes. The grouping is established by assignment of a ShapeGroup instance to the Shape.group attribute of participating shapes.

color

Shape group color.

Type tuple of 3 int

enabled

Enable flag.

Type bool

key

Shape group identifier.

Type int

label

Shape group label.

Type string

selected

Current selection state.

Type bool

show_labels

Shape labels visibility flag.

Type bool

class `Metashape.Shapes`

A set of shapes for a chunk frame.

addGroup()

Add new shape group to the set of shapes.

Returns Created shape group.

Return type *ShapeGroup*

addShape()

Add new shape to the set of shapes.

Returns Created shape.

Return type *Shape*

crs

Shapes coordinate system.

Type *CoordinateSystem*

groups

List of shape groups.

Type list of *ShapeGroup*

items()

List of items.

meta

Shapes meta data.

Type *MetaData*

modified

Modified flag.

Type bool

projection

Shapes projection.

Type *OrthoProjection*

remove (*items*)

Remove items from the shape layer.

Parameters *items* (list of *Shape* or *ShapeGroup*) – A list of items to be removed.

shapes

List of shapes.

Type list of *Shape*

updateAltitudes (*items* [, *progress*])

Update altitudes for items.

Parameters

- **items** (list of *Shape* or *ShapeGroup*) – A list of items to be updated.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

class *Metashape*.**ShapesFormat**

Shapes format in [*ShapesFormatNone*, *ShapesFormatSHP*, *ShapesFormatKML*, *ShapesFormatDXF*, *ShapesFormatGeoJSON*, *ShapesFormatGeoPackage*, *ShapesFormatCSV*]

class *Metashape*.**Shutter**

Shutter object contains estimated parameters of the rolling shutter correction model.

copy ()

Return a copy of the object.

Returns A copy of the object.

Return type *Shutter*

rotation

Rotation matrix of the rolling shutter model.

Type *Matrix*

translation

Translation vector of the rolling shutter model.

Type *Vector*

class *Metashape*.**SurfaceType**

Surface type in [*Arbitrary*, *HeightField*]

class *Metashape*.**Target**

Target parameters

code

Target code.

Type *int*

coord

Target location.

Type *Vector*

copy ()

Return a copy of the object.

Returns A copy of the object.

Return type *Target*

radius

Target radius.

Type float

class `Metashape.TargetType`

Target type in [CircularTarget12bit, CircularTarget14bit, CircularTarget16bit, CircularTarget20bit, CircularTarget, CrossTarget]

class `Metashape.Tasks`

Task classes.

class `AddFrames`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

chunk

Chunk to copy frames from.

Type int

copy_dense_cloud

Copy dense cloud.

Type bool

copy_depth_maps

Copy depth maps.

Type bool

copy_elevation

Copy DEM.

Type bool

copy_model

Copy model.

Type bool

copy_orthomosaic

Copy orthomosaic.

Type bool

copy_tiled_model

Copy tiled model.

Type bool

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON()
Create a JSON string with task parameters.

frames
List of frame keys to copy.
Type list of int

name
Task name.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.AddPhotos*
Task class containing processing parameters.

apply(*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

decode(*dict*)
Initialize task parameters with a dictionary.

decodeJSON(*json*)
Initialize task parameters from a JSON string.

encode()
Create a dictionary with task parameters.

encodeJSON()
Create a JSON string with task parameters.

filegroups
List of file groups.
Type list of int

filenames
List of files to add.
Type list of string

group
Camera group key.
Type int

layout
Image layout.
Type *ImageLayout*

load_reference
Load reference coordinates.
Type bool

load_rpc_txt
Load satellite RPC data from auxiliary TXT files.
Type bool

load_xmp_accuracy
Load accuracy from XMP meta data.
Type bool

load_xmp_antenna
Load GPS/INS offset from XMP meta data.
Type bool

load_xmp_calibration
Load calibration from XMP meta data.
Type bool

load_xmp_orientation
Load orientation from XMP meta data.
Type bool

name
Task name.
Type string

strip_extensions
Strip file extensions from camera labels.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.AlignCameras*
Task class containing processing parameters.

adaptive_fitting
Enable adaptive fitting of distortion coefficients.
Type bool

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras
List of cameras to align.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

min_image
Minimum number of point projections.
Type int

name
Task name.
Type string

reset_alignment
Reset current alignment.
Type bool

subdivide_task
Enable fine-level task subdivision.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.AlignChunks*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

chunks
List of chunks to be aligned.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

downscale
Alignment accuracy.

Type int

encode()
Create a dictionary with task parameters.

encodeJSON()
Create a JSON string with task parameters.

filter_mask
Filter points by mask.
Type bool

fit_scale
Fit chunk scale during alignment.
Type bool

generic_preselection
Enables image pair preselection.
Type bool

keypoint_limit
Maximum number of points for each photo.
Type int

markers
List of markers to be used for marker based alignment.
Type list of int

mask_tiepoints
Apply mask filter to tie points.
Type bool

method
Alignment method.
Type int

name
Task name.
Type string

reference
Chunk to be used as a reference.
Type int

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class `Tasks.AnalyzePhotos`
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable[[float], None]*) – Progress callback.

cameras

List of cameras to be analyzed.

Type list of int

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

filter_mask

Constrain analyzed image region by mask.

Type bool

name

Task name.

Type string

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class *Tasks*.**BuildContours**

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable[[float], None]*) – Progress callback.

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

interval
Contour interval.
Type float

max_value
Maximum value of contour range.
Type float

min_value
Minimum value of contour range.
Type float

name
Task name.
Type string

prevent_intersections
Prevent contour intersections.
Type bool

source_data
Source data for contour generation.
Type *DataSource*

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks*.**BuildDem**
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

classes
List of dense point classes to be used for surface extraction.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

flip_x
Flip X axis direction.
Type bool

flip_y
Flip Y axis direction.
Type bool

flip_z
Flip Z axis direction.
Type bool

interpolation
Interpolation mode.
Type *Interpolation*

max_workgroup_size
Maximum workgroup size.
Type int

name
Task name.
Type string

projection
Output projection.
Type *OrthoProjection*

region
Region to be processed.
Type *BBox*

resolution
Output resolution in meters.
Type float

source_data
Selects between dense point cloud and sparse point cloud.
Type *DataSource*

subdivide_task
Enable fine-level task subdivision.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

workitem_size_tiles
Number of tiles in a workitem.
Type int

class `Tasks.BuildDenseCloud`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

keep_depth

Enable store depth maps option.

Type bool

max_neighbors

Maximum number of neighbor images to use for depth map filtering.

Type int

max_workgroup_size

Maximum workgroup size.

Type int

name

Task name.

Type string

point_colors

Enable point colors calculation.

Type bool

point_confidence

Enable point confidence calculation.

Type bool

subdivide_task

Enable fine-level task subdivision.

Type bool

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

workitem_size_cameras

Number of cameras in a workitem.

Type int**class** Tasks.**BuildDepthMaps**

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

cameras

List of cameras to process.

Type list of int**decode** (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

downscale

Depth map quality.

Type int**encode** ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

filter_mode

Depth map filtering mode.

Type *FilterMode***max_neighbors**

Maximum number of neighbor images to use for depth map generation.

Type int**max_workgroup_size**

Maximum workgroup size.

Type int**name**

Task name.

Type string**reuse_depth**

Enable reuse depth maps option.

Type bool**subdivide_task**

Enable fine-level task subdivision.

Type bool**supports_gpu**

GPU support flag.

Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

workitem_size_cameras
Number of cameras in a workitem.
Type int

class *Tasks*.**BuildModel**
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras
List of cameras to process.
Type list of int

classes
List of dense point classes to be used for surface extraction.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

face_count
Target face count.
Type *FaceCount*

face_count_custom
Custom face count.
Type int

interpolation
Interpolation mode.
Type *Interpolation*

keep_depth
Enable store depth maps option.
Type bool

max_workgroup_size
Maximum workgroup size.
Type int

name
Task name.
Type string

source_data
Selects between dense point cloud, sparse point cloud and depth maps.
Type *DataSource*

subdivide_task
Enable fine-level task subdivision.
Type bool

supports_gpu
GPU support flag.
Type bool

surface_type
Type of object to be reconstructed.
Type *SurfaceType*

target
Task target.
Type *Tasks.TargetType*

trimming_radius
Trimming radius (no trimming if zero).
Type int

vertex_colors
Enable vertex colors calculation.
Type bool

vertex_confidence
Enable vertex confidence calculation.
Type bool

volumetric_masks
Enable strict volumetric masking.
Type bool

workitem_count
Work item count.
Type int

workitem_size_cameras
Number of cameras in a workitem.
Type int

class *Tasks.BuildOrthomosaic*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

blending_mode
Orthophoto blending mode.
Type *BlendingMode*

cull_faces
Enable back-face culling.
Type bool

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

fill_holes
Enable hole filling.
Type bool

flip_x
Flip X axis direction.
Type bool

flip_y
Flip Y axis direction.
Type bool

flip_z
Flip Z axis direction.
Type bool

max_workgroup_size
Maximum workgroup size.
Type int

name
Task name.
Type string

projection
Output projection.
Type *OrthoProjection*

refine_seamlines
Refine seamlines based on image content.
Type bool

region
Region to be processed.
Type *BBox*

resolution
Pixel size in meters.
Type float

resolution_x
Pixel size in the X dimension in projected units.
Type float

resolution_y
Pixel size in the Y dimension in projected units.

Type float

subdivide_task
Enable fine-level task subdivision.
Type bool

supports_gpu
GPU support flag.
Type bool

surface_data
Orthorectification surface.
Type *DataSource*

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

workitem_size_cameras
Number of cameras in a workitem.
Type int

workitem_size_tiles
Number of tiles in a workitem.
Type int

class *Tasks*.**BuildSeamlines**
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

epsilon
Contour simplification threshold.
Type float

name
Task name.
Type string

supports_gpu
GPU support flag.

Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks*.**BuildTexture**
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

blending_mode
Texture blending mode.
Type *BlendingMode*

cameras
A list of cameras to be used for texturing.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

fill_holes
Enable hole filling.
Type bool

ghosting_filter
Enable ghosting filter.
Type bool

name
Task name.
Type string

source_model
Source model.
Type int

supports_gpu
GPU support flag.
Type bool

target
Task target.

Type *Tasks.TargetType*

texture_size
Texture page size.
Type int

texture_type
Texture type.
Type *Model.TextureType*

transfer_texture
Transfer texture.
Type bool

workitem_count
Work item count.
Type int

class *Tasks.BuildTiledModel*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

classes
List of dense point classes to be used for surface extraction.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

face_count
Number of faces per megapixel of texture resolution.
Type int

ghosting_filter
Enable ghosting filter.
Type bool

keep_depth
Enable store depth maps option.
Type bool

max_workgroup_size
Maximum workgroup size.
Type int

name
Task name.

Type string

pixel_size
Target model resolution in meters.
Type float

source_data
Selects between dense point cloud and mesh.
Type *DataSource*

subdivide_task
Enable fine-level task subdivision.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

tile_size
Size of tiles in pixels.
Type int

transfer_texture
Transfer source model texture to tiled model.
Type bool

workitem_count
Work item count.
Type int

workitem_size_cameras
Number of cameras in a workitem.
Type int

class *Tasks*.**BuildUV**
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

camera
Camera to be used for texturing in MappingCamera mode.
Type int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON()
Create a JSON string with task parameters.

mapping_mode
Texture mapping mode.
Type *MappingMode*

name
Task name.
Type string

page_count
Number of texture pages to generate.
Type int

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

texture_size
Expected size of texture page at texture generation step.
Type int

workitem_count
Work item count.
Type int

class *Tasks.CalibrateColors*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

cameras
List of cameras to process.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

source_data
Source data for calibration.
Type *DataSource*

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

white_balance
Calibrate white balance.
Type bool

workitem_count
Work item count.
Type int

class *Tasks.CalibrateLens*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

border
Border size to ignore.
Type int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

fit_b1
Enable optimization of aspect ratio.
Type bool

fit_b2
Enable optimization of skew coefficient.
Type bool

fit_cxcy
Enable optimization of principal point coordinates.
Type bool

fit_f
Enable optimization of focal length coefficient.
Type bool

fit_k1
Enable optimization of k1 radial distortion coefficient.
Type bool

fit_k2
Enable optimization of k2 radial distortion coefficient.
Type bool

fit_k3
Enable optimization of k3 radial distortion coefficient.
Type bool

fit_k4
Enable optimization of k4 radial distortion coefficient.
Type bool

fit_p1
Enable optimization of p1 tangential distortion coefficient.
Type bool

fit_p2
Enable optimization of p2 tangential distortion coefficient.
Type bool

name
Task name.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class `Tasks.CalibrateReflectance`
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

use_reflectance_panels
Use calibrated reflectance panels.
Type bool

use_sun_sensor
Apply irradiance sensor measurements.
Type bool

workitem_count
Work item count.
Type int

class *Tasks.ClassifyGroundPoints*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

cell_size
Cell size (meters).
Type float

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

max_angle
Maximum angle (degrees).
Type float

max_distance
Maximum distance (meters).
Type float

name
Task name.
Type string

source_class
Class of points to be re-classified.
Type int

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.ClassifyPoints*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

confidence
Required confidence level.
Type float

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

source_class
Class of points to be re-classified.
Type int

subdivide_task
Enable fine-level task subdivision.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

target_classes
Target point classes for classification.
Type list of int

workitem_count
Work item count.
Type int

class `Tasks.CloseHoles`
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

level
Hole size threshold in percents.
Type int

name
Task name.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class `Tasks.ColorizeDenseCloud`
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

source_data
Source data to extract colors from.
Type *DataSource*

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.ColorizeModel*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

source_data
Source data to extract colors from.
Type *DataSource*

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks*.**CompactDenseCloud**
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks*.**ConvertImages**
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras
List of cameras to process.
Type list of int

color_correction
Apply color correction.
Type bool

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

fix_pixel_aspect
Fix pixel aspect.
Type bool

fix_principal_point
Fix principal point.
Type bool

image_compression
Image compression parameters.
Type *ImageCompression*

name
Task name.
Type string

path
Path to output file.
Type string

remove_distortions
Remove distortions.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

update_gps_tags
Update GPS tags.
Type bool

use_initial_calibration
Transform to initial calibration.
Type bool

workitem_count
Work item count.

Type int

class `Tasks.DecimateModel`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

apply_to_selection

Apply to selection.

Type bool

asset

Model to process.

Type int

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

face_count

Target face count.

Type int

name

Task name.

Type string

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class `Tasks.DetectFiducials`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras
List of cameras to process.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

frames
List of frames to process.
Type list of int

generate_masks
Generate background masks.
Type bool

name
Task name.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.DetectMarkers*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras
List of cameras to process.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON()
Create a JSON string with task parameters.

filter_mask
Ignore masked image regions.
Type bool

frames
List of frames to process.
Type list of int

inverted
Detect markers on black background.
Type bool

maximum_residual
Maximum residual for non-coded targets in pixels.
Type float

minimum_dist
Minimum distance between targets in pixels (CrossTarget type only).
Type int

minimum_size
Minimum target radius in pixels to be detected (CrossTarget type only).
Type int

name
Task name.
Type string

noparity
Disable parity checking.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

target_type
Type of targets.
Type *TargetType*

tolerance
Detector tolerance (0 - 100).
Type int

workitem_count
Work item count.
Type int

class *Tasks.DuplicateChunk*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable[[float], None]*) – Progress callback.

chunk

Chunk to copy.

Type int

copy_dense_clouds

Copy dense clouds.

Type bool

copy_depth_maps

Copy depth maps.

Type bool

copy_elevations

Copy DEMs.

Type bool

copy_keypoints

Copy keypoints.

Type bool

copy_models

Copy models.

Type bool

copy_orthomosaics

Copy orthomosaics.

Type bool

copy_tiled_models

Copy tiled models.

Type bool

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

frames

List of frame keys to copy.

Type list of int

label

New chunk label.

Type string

name

Task name.

Type string

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class *Tasks.ExportCameras*

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

binary

Enables/disables binary encoding for selected format (if applicable).

Type bool

bingo_path_geoin

Path to BINGO GEO INPUT file.

Type string

bingo_path_gps

Path to BINGO GPS/IMU file.

Type string

bingo_path_image

Path to BINGO IMAGE COORDINATE file.

Type string

bingo_path_itera

Path to BINGO ITERA file.

Type string

bingo_save_geoin

Enables/disables export of BINGO GEO INPUT file.

Type bool

bingo_save_gps

Enables/disables export of BINGO GPS/IMU data.

Type bool

bingo_save_image

Enables/disables export of BINGO IMAGE COORDINATE file.

Type bool

bingo_save_itera

Enables/disables export of BINGO ITERA file.

Type bool

bundler_path_list

Path to Bundler image list file.

Type string

bundler_save_list
Enables/disables export of Bundler image list file.
Type bool

chan_rotation_order
Rotation order (CHAN format only).
Type *RotationOrder*

crs
Output coordinate system.
Type *CoordinateSystem*

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

format
Export format.
Type *CamerasFormat*

image_orientation
Image coordinate system (0 - X right, 1 - X up, 2 - X left, 3 - X down).
Type int

name
Task name.
Type string

path
Path to output file.
Type string

save_invalid_matches
Enables/disables export of invalid image matches.
Type bool

save_markers
Enables/disables export of manual matching points.
Type bool

save_points
Enables/disables export of automatic tie points.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

use_initial_calibration
Transform image coordinates to initial calibration.

Type bool

use_labels

Enables/disables label based item identifiers.

Type bool

workitem_count

Work item count.

Type int

class `Tasks.ExportDepth`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

cameras

List of cameras to process.

Type list of int

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

export_depth

Enable export of depth map.

Type bool

export_diffuse

Enable export of diffuse map.

Type bool

export_normals

Enable export of normal map.

Type bool

name

Task name.

Type string

path_depth

Path to depth map.

Type string

path_diffuse

Path to diffuse map.

Type string

path_normals

Path to normal map.

Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.ExportMarkers*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

binary
Enables/disables binary encoding for selected format (if applicable).
Type bool

crs
Output coordinate system.
Type *CoordinateSystem*

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

path
Path to output file.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.

Type int

class `Tasks.ExportMasks`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras

List of cameras to process.

Type list of int

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

name

Task name.

Type string

path

Path to output file.

Type string

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class `Tasks.ExportModel`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

binary

Enables/disables binary encoding (if supported by format).

Type bool

clip_to_boundary
Clip model to boundary shapes.
Type bool

colors_rgb_8bit
Convert colors to 8 bit RGB.
Type bool

comment
Optional comment (if supported by selected format).
Type string

crs
Output coordinate system.
Type *CoordinateSystem*

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

embed_texture
Embeds texture inside the model file (if supported by format).
Type bool

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

format
Export format.
Type *ModelFormat*

name
Task name.
Type string

path
Path to output model.
Type string

precision
Number of digits after the decimal point (for text formats).
Type int

raster_transform
Raster band transformation.
Type *RasterTransformType*

save_alpha
Enables/disables alpha channel export.
Type bool

save_cameras
Enables/disables camera export.
Type bool

save_colors
Enables/disables export of vertex colors.

Type bool

save_comment
Enables/disables comment export.
Type bool

save_confidence
Enables/disables export of vertex confidence.
Type bool

save_markers
Enables/disables marker export.
Type bool

save_normals
Enables/disables export of vertex normals.
Type bool

save_texture
Enables/disables texture export.
Type bool

save_udim
Enables/disables UDIM texture layout.
Type bool

save_uv
Enables/disables uv coordinates export.
Type bool

shift
Optional shift to be applied to vertex coordinates.
Type *Vector*

strip_extensions
Strips camera label extensions during export.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

texture_format
Texture format.
Type *ImageFormat*

viewpoint
Default view.
Type *Viewpoint*

workitem_count
Work item count.
Type int

class `Tasks.ExportOrthophotos`
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras

List of cameras to process.

Type list of int

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

image_compression

Image compression parameters.

Type *ImageCompression*

name

Task name.

Type string

north_up

Use north-up orientation for export.

Type bool

path

Path to output orthophoto.

Type string

projection

Output projection.

Type *OrthoProjection*

raster_transform

Raster band transformation.

Type *RasterTransformType*

region

Region to be exported.

Type *BBox*

resolution

Output resolution in meters.

Type float

resolution_x

Pixel size in the X dimension in projected units.

Type float

resolution_y

Pixel size in the Y dimension in projected units.

Type float

save_alpha
Enable alpha channel generation.
Type bool

save_kml
Enable kml file generation.
Type bool

save_world
Enable world file generation.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

white_background
Enable white background.
Type bool

workitem_count
Work item count.
Type int

class *Tasks.ExportPanorama*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

camera_groups
List of camera groups to process.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

height
Height of output panorama.
Type int

image_compression
Image compression parameters.

Type *ImageCompression*

name

Task name.

Type string

path

Path to output file.

Type string

region

Region to be exported.

Type *BBox*

rotation

Panorama 3x3 orientation matrix.

Type *Matrix*

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

width

Width of output panorama.

Type int

workitem_count

Work item count.

Type int

class *Tasks.ExportPoints*

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

binary

Enables/disables binary encoding for selected format (if applicable).

Type bool

block_height

Block height in meters.

Type float

block_width

Block width in meters.

Type float

classes

List of dense point classes to be exported.

Type list of int

clip_to_boundary
Clip point cloud to boundary shapes.
Type bool

colors_rgb_8bit
Convert colors to 8 bit RGB.
Type bool

comment
Optional comment (if supported by selected format).
Type string

crs
Output coordinate system.
Type *CoordinateSystem*

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

format
Export format.
Type *PointsFormat*

image_format
Image data format.
Type *ImageFormat*

name
Task name.
Type string

path
Path to output file.
Type string

raster_transform
Raster band transformation.
Type *RasterTransformType*

region
Region to be exported.
Type *BBox*

save_classes
Enables/disables export of point classes.
Type bool

save_colors
Enables/disables export of point colors.
Type bool

save_comment
Enable comment export.

Type bool

save_confidence

Enables/disables export of point confidence.

Type bool

save_images

Enable image export.

Type bool

save_normals

Enables/disables export of point normals.

Type bool

shift

Optional shift to be applied to point coordinates.

Type *Vector*

source_data

Selects between dense point cloud and sparse point cloud. If not specified, uses dense cloud if available.

Type *DataSource*

split_in_blocks

Enable tiled export.

Type bool

subdivide_task

Enable fine-level task subdivision.

Type bool

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

viewpoint

Default view.

Type *Viewpoint*

workitem_count

Work item count.

Type int

class *Tasks.ExportRaster*

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

block_height

Raster block height in pixels.

Type int

block_width

Raster block width in pixels.

Type int

clip_to_boundary

Clip raster to boundary shapes.

Type bool

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

description

Export description.

Type string

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

format

Export format.

Type *RasterFormat*

height

Raster height.

Type int

image_compression

Image compression parameters.

Type *ImageCompression*

image_description

Optional description to be added to image files.

Type string

image_format

Tile format.

Type *ImageFormat*

max_zoom_level

Maximum zoom level (Google Map Tiles, MBTiles and World Wind Tiles formats only).

Type int

min_zoom_level

Minimum zoom level (Google Map Tiles, MBTiles and World Wind Tiles formats only).

Type int

name

Task name.

Type string

network_links

Enable network links generation for KMZ format.

Type bool

nodata_value

No-data value (DEM export only).

Type float

north_up
Use north-up orientation for export.
Type bool

path
Path to output orthomosaic.
Type string

projection
Output projection.
Type *OrthoProjection*

raster_transform
Raster band transformation.
Type *RasterTransformType*

region
Region to be exported.
Type *BBox*

resolution
Output resolution in meters.
Type float

resolution_x
Pixel size in the X dimension in projected units.
Type float

resolution_y
Pixel size in the Y dimension in projected units.
Type float

save_alpha
Enable alpha channel generation.
Type bool

save_kml
Enable kml file generation.
Type bool

save_scheme
Enable tile scheme files generation.
Type bool

save_world
Enable world file generation.
Type bool

source_data
Selects between DEM and orthomosaic.
Type *DataSource*

split_in_blocks
Split raster in blocks.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

tile_height
Tile height in pixels.
Type int

tile_width
Tile width in pixels.
Type int

title
Export title.
Type string

white_background
Enable white background.
Type bool

width
Raster width.
Type int

workitem_count
Work item count.
Type int

world_transform
2x3 raster-to-world transformation matrix.
Type *Matrix*

class *Tasks.ExportReference*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

columns

Column order in csv format (n - label, o - enabled flag, x/y/z - coordinates, X/Y/Z - coordinate accuracy, a/b/c - rotation angles, A/B/C - rotation angle accuracy, u/v/w - estimated coordinates, U/V/W - coordinate errors, d/e/f - estimated orientation angles, D/E/F - orientation errors, p/q/r - estimated coordinates variance, i/j/k - estimated orientation angles variance, [] - group of multiple values, | - column separator within group).

Type string

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

delimiter
Column delimiter in csv format.
Type string

encode()
Create a dictionary with task parameters.

encodeJSON()
Create a JSON string with task parameters.

format
Export format.
Type *ReferenceFormat*

items
Items to export in CSV format.
Type *ReferenceItems*

name
Task name.
Type string

path
Path to the output file.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.ExportReport*
Task class containing processing parameters.

apply(*object*[, *workitem*][, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

decode(*dict*)
Initialize task parameters with a dictionary.

decodeJSON(*json*)
Initialize task parameters from a JSON string.

description
Report description.
Type string

encode()
Create a dictionary with task parameters.

encodeJSON()
Create a JSON string with task parameters.

name
Task name.

Type string

page_numbers
Enable page numbers.
Type bool

path
Path to output report.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

title
Report title.
Type string

user_settings
A list of user defined settings to include on the Processing Parameters page.
Type list of (string, string) tuples

workitem_count
Work item count.
Type int

class *Tasks.ExportShapes*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

crs
Output coordinate system.
Type *CoordinateSystem*

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

format
Export format.
Type *ShapesFormat*

groups
A list of shape groups to export.

Type list of int

name
Task name.
Type string

path
Path to shape file.
Type string

polygons_as_polylines
Save polygons as polylines.
Type bool

save_attributes
Export attributes.
Type bool

save_labels
Export labels.
Type bool

save_points
Export points.
Type bool

save_polygons
Export polygons.
Type bool

save_polylines
Export polylines.
Type bool

shift
Optional shift to be applied to vertex coordinates.
Type *Vector*

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class `Tasks.ExportTexture`
Task class containing processing parameters.

apply (*object*[, *workitem*][, *progress*])
Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

path
Path to output file.
Type string

save_alpha
Enable alpha channel export.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

texture_type
Texture type.
Type *Model.TextureType*

workitem_count
Work item count.
Type int

class *Tasks.ExportTiledModel*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

clip_to_boundary
Clip tiled model to boundary shapes.
Type bool

crs
Output coordinate system.
Type *CoordinateSystem*

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

format
Export format.
Type *TiledModelFormat*

image_compression
Image compression parameters.
Type *ImageCompression*

model_format
Model format for zip export.
Type *ModelFormat*

name
Task name.
Type string

path
Path to output model.
Type string

raster_transform
Raster band transformation.
Type *RasterTransformType*

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

texture_format
Texture format.
Type *ImageFormat*

workitem_count
Work item count.
Type int

class *Tasks*.**FilterDenseCloud**
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

asset
Dense cloud key to filter.

Type int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

point_spacing
Desired point spacing (m).
Type float

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.ImportCameras*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

crs
Ground coordinate system.
Type *CoordinateSystem*

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

format
File format.

Type *CamerasFormat*

image_list

Path to image list file (Bundler format only).

Type string

image_orientation

Image coordinate system (0 - X right, 1 - X up, 2 - X left, 3 - X down).

Type int

load_image_list

Enable Bundler image list import.

Type bool

name

Task name.

Type string

path

Path to the file.

Type string

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class *Tasks.ImportMarkers*

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

name

Task name.

Type string

path

Path to the file.

Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.ImportMasks*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras
Optional list of cameras to be processed.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

operation
Mask operation.
Type *MaskOperation*

path
Mask file name template.
Type string

source
Mask source.
Type *MaskSource*

supports_gpu
GPU support flag.
Type bool

target
Task target.

Type *Tasks.TargetType*

tolerance

Background masking tolerance.

Type int

workitem_count

Work item count.

Type int

class *Tasks.ImportModel*

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

crs

Model coordinate system.

Type *CoordinateSystem*

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

format

Model format.

Type *ModelFormat*

name

Task name.

Type string

path

Path to model.

Type string

shift

Optional shift to be applied to vertex coordinates.

Type *Vector*

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class `Tasks.ImportPoints`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

calculate_normals

Calculate point normals.

Type bool

crs

Point cloud coordinate system.

Type *CoordinateSystem*

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

format

Point cloud format.

Type *PointsFormat*

name

Task name.

Type string

path

Path to point cloud.

Type string

shift

Optional shift to be applied to point coordinates.

Type *Vector*

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class `Tasks.ImportRaster`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

crs

Default coordinate system if not specified in GeoTIFF file.

Type *CoordinateSystem*

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

name

Task name.

Type string

path

Path to elevation model in GeoTIFF format.

Type string

raster_type

Type of raster layer to import.

Type *DataSource*

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class *Tasks.ImportReference*

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

columns

Column order in csv format (n - label, o - enabled flag, x/y/z - coordinates, X/Y/Z - coordinate accuracy, a/b/c - rotation angles, A/B/C - rotation angle accuracy, [] - group of multiple values, | - column separator within group).

Type string

create_markers

Create markers for missing entries (csv format only).

Type bool

crs

Reference data coordinate system (csv format only).

Type *CoordinateSystem*

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

delimiter

Column delimiter in csv format.

Type string

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

format

File format.

Type *ReferenceFormat*

group_delimiters

Combine consecutive delimiters in csv format.

Type bool

ignore_labels

Matches reference data based on coordinates alone (csv format only).

Type bool

items

List of items to load reference for (csv format only).

Type *ReferenceItems*

name

Task name.

Type string

path

Path to the file with reference data.

Type string

shutter_lag

Shutter lag in seconds (APM format only).

Type float

skip_rows

Number of rows to skip in (csv format only).

Type int

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType***threshold**

Error threshold in meters used when ignore_labels is set (csv format only).

Type float**workitem_count**

Work item count.

Type int**class** *Tasks.ImportShapes*

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

boundary_type

Boundary type to be applied to imported shapes.

Type *Shape.BoundaryType***columns**

Column order in csv format (n - label, x/y/z - coordinates, d - description, [] - group of multiple values, | - column separator within group).

Type string**crs**

Reference data coordinate system (csv format only).

Type *CoordinateSystem***decode** (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

delimiter

Column delimiter in csv format.

Type string**encode** ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

format

Shapes format.

Type *ShapesFormat***group_delimiters**

Combine consecutive delimiters in csv format.

Type bool**name**

Task name.

Type string

path
Path to shape file.
Type string

replace
Replace current shapes with new data.
Type bool

skip_rows
Number of rows to skip in (csv format only).
Type int

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.ImportTiledModel*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

path
Path to tiled model.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class *Tasks.InvertMasks*

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras

List of cameras to process.

Type list of int

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

name

Task name.

Type string

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class *Tasks.LoadProject*

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

path
Path to project file.
Type string

read_only
Open project in read only mode.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.MatchPhotos*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras
List of cameras to match.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

downscale
Image alignment accuracy.
Type int

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

filter_mask
Filter points by mask.
Type bool

generic_preselection
Enable generic preselection.
Type bool

guided_matching
Enable guided image matching.
Type bool

keep_keypoints
Store keypoints in the project.
Type bool

keypoint_limit
Key point limit.
Type int

mask_tiepoints
Apply mask filter to tie points.
Type bool

max_workgroup_size
Maximum workgroup size.
Type int

name
Task name.
Type string

pairs
User defined list of camera pairs to match.
Type list of (int, int) tuples

reference_preselection
Enable reference preselection.
Type bool

reference_preselection_mode
Reference preselection mode.
Type *ReferencePreselectionMode*

reset_matches
Reset current matches.
Type bool

subdivide_task
Enable fine-level task subdivision.
Type bool

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

tiepoint_limit

Tie point limit.

Type int

workitem_count

Work item count.

Type int

workitem_size_cameras

Number of cameras in a workitem.

Type int

workitem_size_pairs

Number of image pairs in a workitem.

Type int

class `Tasks.MergeAssets`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

assets

List of assets to process.

Type list of int

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

name

Task name.

Type string

source_data

Asset type.

Type *DataSource*

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class `Tasks.MergeChunks`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

chunks

List of chunks to process.

Type list of int

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

merge_dense_clouds

Merge dense clouds.

Type bool

merge_depth_maps

Merge depth maps.

Type bool

merge_elevations

Merge DEMs.

Type bool

merge_markers

Merge markers.

Type bool

merge_models

Merge models.

Type bool

merge_orthomosaics

Merge orthomosaics.

Type bool

merge_tiepoints

Merge tie points.

Type bool

name

Task name.

Type string

supports_gpu

GPU support flag.

Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.OptimizeCameras*
Task class containing processing parameters.

adaptive_fitting
Enable adaptive fitting of distortion coefficients.
Type bool

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

fit_b1
Enable optimization of aspect ratio.
Type bool

fit_b2
Enable optimization of skew coefficient.
Type bool

fit_corrections
Enable optimization of additional corrections.
Type bool

fit_cx
Enable optimization of X principal point coordinates.
Type bool

fit_cy
Enable optimization of Y principal point coordinates.
Type bool

fit_f
Enable optimization of focal length coefficient.
Type bool

fit_k1
Enable optimization of k1 radial distortion coefficient.
Type bool

fit_k2
Enable optimization of k2 radial distortion coefficient.
Type bool

fit_k3
Enable optimization of k3 radial distortion coefficient.
Type bool

fit_k4
Enable optimization of k3 radial distortion coefficient.
Type bool

fit_p1
Enable optimization of p1 tangential distortion coefficient.
Type bool

fit_p2
Enable optimization of p2 tangential distortion coefficient.
Type bool

name
Task name.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

tiepoint_covariance
Estimate tie point covariance matrices.
Type bool

workitem_count
Work item count.
Type int

class `Tasks.PlanMission`
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

capture_distance
Image capture distance (m).
Type float

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode()
Create a dictionary with task parameters.

encodeJSON()
Create a JSON string with task parameters.

max_pitch
Maximum camera pitch angle.
Type int

max_waypoints
Maximum waypoints per flight.
Type int

min_altitude
Minimum altitude (m).
Type float

min_pitch
Minimum camera pitch angle.
Type int

min_waypoint_spacing
Minimum waypoint spacing (m).
Type float

name
Task name.
Type string

overlap
Overlap percent.
Type int

safety_distance
Safety distance (m).
Type float

sensor
Sensor key.
Type int

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

use_selection
Focus on model selection.
Type bool

workitem_count
Work item count.
Type int

class *Tasks.ReduceOverlap*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

max_cameras

Maximum cameras to use.

Type int

name

Task name.

Type string

overlap

Overlap level.

Type int

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

use_selection

Focus on model selection.

Type bool

workitem_count

Work item count.

Type int

class *Tasks.RefineMesh*

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras

List of cameras to process.

Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

downscale
Refinement quality.
Type int

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

iterations
Number of refinement iterations.
Type int

name
Task name.
Type string

smoothness
Smoothing strength. Should be in range [0, 1].
Type float

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.RemoveLighting*
Task class containing processing parameters.

ambient_occlusion_multiplier
Ambient occlusion multiplier. Should be in range [0.25, 4].
Type float

ambient_occlusion_path
Path to ambient occlusion texture atlas. Can be empty.
Type string

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

color_mode
Enable multi-color processing mode.
Type bool

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

internal_blur
Internal blur. Should be in range [0, 4].
Type float

mesh_noise_suppression
Mesh normals noise suppression strength. Should be in range [0, 4].
Type float

name
Task name.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.ResetMasks*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.
Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

cameras
List of cameras to process.
Type list of int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class *Tasks.RunScript*
Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])
Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

args
Script arguments.
Type string

code
Script code.
Type string

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

path
Script path.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

workitem_count
Work item count.
Type int

class `Tasks.SaveProject`
Task class containing processing parameters.

absolute_paths
Store absolute image paths.
Type bool

apply (`object`[, `workitem`][, `progress`])
Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable[[float], None]*) – Progress callback.

chunks
List of chunks to be saved.
Type list of int

compression
Project compression level.
Type int

decode (*dict*)
Initialize task parameters with a dictionary.

decodeJSON (*json*)
Initialize task parameters from a JSON string.

encode ()
Create a dictionary with task parameters.

encodeJSON ()
Create a JSON string with task parameters.

name
Task name.
Type string

path
Path to project.
Type string

supports_gpu
GPU support flag.
Type bool

target
Task target.
Type *Tasks.TargetType*

version
Project version to save.
Type string

workitem_count
Work item count.
Type int

class `Tasks.SmoothModel`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable* [[*float*], *None*]) – Progress callback.

apply_to_selection

Apply to selected faces.

Type `bool`

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

fix_borders

Fix borders.

Type `bool`

name

Task name.

Type `string`

strength

Smoothing strength.

Type `float`

supports_gpu

GPU support flag.

Type `bool`

target

Task target.

Type `Tasks.TargetType`

workitem_count

Work item count.

Type `int`

class `Tasks.TargetType`

Task target type in [`DocumentTarget`, `ChunkTarget`, `FrameTarget`]

class `Tasks.TrackMarkers`

Task class containing processing parameters.

apply (*object* [, *workitem*] [, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.

- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

first_frame

Starting frame index.

Type int

last_frame

Ending frame index.

Type int

name

Task name.

Type string

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

class *Tasks.TriangulatePoints*

Task class containing processing parameters.

apply (*object*[, *workitem*][, *progress*])

Apply task to specified object.

Parameters

- **object** (*Chunk* or *Document*) – Chunk or Document object to be processed.
- **workitem** (*int*) – Workitem index.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

decode (*dict*)

Initialize task parameters with a dictionary.

decodeJSON (*json*)

Initialize task parameters from a JSON string.

encode ()

Create a dictionary with task parameters.

encodeJSON ()

Create a JSON string with task parameters.

max_error

Reprojection error threshold.

Type float

min_image

Minimum number of point projections.

Type int

name

Task name.

Type string

supports_gpu

GPU support flag.

Type bool

target

Task target.

Type *Tasks.TargetType*

workitem_count

Work item count.

Type int

`Tasks.createTask (name)`

Create task object by its name.

Parameters **name** (*string*) – Task name.

Returns Task object.

Return type object

class `Metashape.Thumbnail`

Thumbnail instance

copy ()

Returns a copy of thumbnail.

Returns Copy of thumbnail.

Return type *Thumbnail*

image ()

Returns image data.

Returns Image data.

Return type *Image*

load (path[, layer])

Loads thumbnail from file.

Parameters

- **path** (*string*) – Path to the image file to be loaded.
- **layer** (*int*) – Optional layer index in case of multipage files.

setImage (image)

Parameters **image** (*Image*) – Image object with thumbnail data.

class `Metashape.Thumbnails`

A set of thumbnails generated for a chunk frame.

items ()

List of items.

keys ()
List of item keys.

meta
Thumbnails meta data.
Type *MetaData*

modified
Modified flag.
Type bool

values ()
List of item values.

class `Metashape.TiledModel`
Tiled model data.

class `FaceCount`
Tiled model face count in [`LowFaceCount`, `MediumFaceCount`, `HighFaceCount`]

`TiledModel.bands`
List of color bands.

Type list of string

`TiledModel.clear ()`
Clears tiled model data.

`TiledModel.copy ()`
Create a copy of the tiled model.

Returns Copy of the tiled model.

Return type *TiledModel*

`TiledModel.crs`
Reference coordinate system.

Type *CoordinateSystem* or None

`TiledModel.data_type`
Data type used to store color values.

Type *DataType*

`TiledModel.key`
Tiled model identifier.

Type int

`TiledModel.label`
Tiled model label.

Type string

`TiledModel.meta`
Tiled model meta data.

Type *MetaData*

`TiledModel.modified`
Modified flag.

Type bool

`TiledModel.pickPoint` (*origin, target, endpoints=1*)

Returns ray intersection with the tiled model.

Parameters

- **origin** (*Vector*) – Ray origin.
- **target** (*Vector*) – Point on the ray.
- **endpoints** (*int*) – Number of endpoints to check for (0 - line, 1 - ray, 2 - segment).

Returns Coordinates of the intersection point.

Return type *Vector*

`TiledModel.renderDepth` (*transform, calibration, resolution=1, cull_faces=True, add_alpha=True*)

Render tiled model depth image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **resolution** (*float*) – Level of detail resolution in screen pixels.
- **cull_faces** (*bool*) – Enable back-face culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.

Returns Rendered image.

Return type *Image*

`TiledModel.renderImage` (*transform, calibration, resolution=1, cull_faces=True, add_alpha=True, raster_transform=RasterTransformNone*)

Render tiled model image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **resolution** (*float*) – Level of detail resolution in screen pixels.
- **cull_faces** (*bool*) – Enable back-face culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.
- **raster_transform** (*RasterTransformType*) – Raster band transformation.

Returns Rendered image.

Return type *Image*

`TiledModel.renderMask` (*transform, calibration, resolution=1, cull_faces=True*)

Render tiled model mask image for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **resolution** (*float*) – Level of detail resolution in screen pixels.
- **cull_faces** (*bool*) – Enable back-face culling.

Returns Rendered image.

Return type *Image*

`TiledModel.renderNormalMap` (*transform*, *calibration*, *resolution=1*, *cull_faces=True*,
add_alpha=True)

Render image with tiled model normals for specified viewpoint.

Parameters

- **transform** (*Matrix*) – Camera location.
- **calibration** (*Calibration*) – Camera calibration.
- **resolution** (*float*) – Level of detail resolution in screen pixels.
- **cull_faces** (*bool*) – Enable back-face culling.
- **add_alpha** (*bool*) – Generate image with alpha channel.

Returns Rendered image.

Return type *Image*

`TiledModel.renderPreview` (*width = 2048*, *height = 2048* [, *transform*] [, *progress*])

Generate tiled model preview image.

Parameters

- **width** (*int*) – Preview image width.
- **height** (*int*) – Preview image height.
- **transform** (*Matrix*) – 4x4 viewpoint transformation matrix.
- **progress** (*Callable*[[*float*], *None*]) – Progress callback.

Returns Preview image.

Return type *Image*

`TiledModel.transform`

4x4 dense cloud transformation matrix.

Type *Matrix*

class `Metashape.TiledModelFormat`

Tiled model format in [`TiledModelFormatNone`, `TiledModelFormatTLS`, `TiledModelFormatLOD`, `TiledModelFormatZIP`, `TiledModelFormatCesium`, `TiledModelFormatSLPK`, `TiledModelFormatOSGB`]

class `Metashape.Utils`

Utility functions.

createChessboardImage (*calib*, *cell_size=150*, *max_tilt=30*)

Synthesizes photo of a chessboard.

Parameters

- **calib** (*Calibration*) – Camera calibration.
- **cell_size** (*float*) – Chessboard cell size.
- **max_tilt** (*float*) – Maximum camera tilt in degrees.

Returns Resulting image.

Return type *Image*

createDifferenceMask (*image*, *background*, *tolerance=10*, *fit_colors=True*)

Creates mask from a pair of images or an image and specified color.

Parameters

- **image** (*Image*) – Image to be masked.
- **background** (*Image* or color tuple) – Background image or color value.
- **tolerance** (*int*) – Tolerance value.
- **fit_colors** (*bool*) – Enables white balance correction.

Returns Resulting mask.

Return type *Image*

createMarkers (*chunk*, *projections*)

Creates markers from a list of non coded projections.

Parameters

- **chunk** (*Chunk*) – Chunk to create markers in.
- **projections** (list of (*Camera*, *Target*) tuples) – List of marker projections.

detectTargets (*image*, *type=TargetCircular12bit*, *tolerance=50*, *inverted=False*, *noparity=False* [, *minimum_size*] [, *minimum_dist*])

Detect targets on the image.

Parameters

- **image** (*Image*) – Image to process.
- **type** (*TargetType*) – Type of targets.
- **tolerance** (*int*) – Detector tolerance (0 - 100).
- **inverted** (*bool*) – Detect markers on black background.
- **noparity** (*bool*) – Disable parity checking.
- **minimum_size** (*int*) – Minimum target radius in pixels to be detected (CrossTarget type only).
- **minimum_dist** (*int*) – Minimum distance between targets in pixels (CrossTarget type only).

Returns List of detected targets.

Return type list of *Target*

estimateImageQuality (*image* [, *mask*])

Estimate image sharpness.

Parameters

- **image** (*Image*) – Image to be analyzed.
- **mask** (*Image*) – Mask of the analyzed image region.

Returns Quality metric.

Return type float

euler2mat (*rotation*, *euler_angles=EulerAnglesYPR*)

Calculate camera to world rotation matrix from euler rotation angles.

Parameters

- **rotation** (*Vector*) – Rotation vector.
- **euler_angles** (*EulerAngles*) – Euler angles to use.

Returns Rotation matrix.

Return type *Matrix*

mat2euler (*R*, *euler_angles=EulerAnglesYPR*)

Calculate euler rotation angles from camera to world rotation matrix.

Parameters

- **R** (*Matrix*) – Rotation matrix.
- **euler_angles** (*EulerAngles*) – Euler angles to use.

Returns Rotation angles in degrees.

Return type *Vector*

mat2opk (*R*)

Calculate omega, phi, kappa from camera to world rotation matrix.

Parameters **R** (*Matrix*) – Rotation matrix.

Returns Omega, phi, kappa angles in degrees.

Return type *Vector*

mat2ypr (*R*)

Calculate yaw, pitch, roll from camera to world rotation matrix.

Parameters **R** (*Matrix*) – Rotation matrix.

Returns Yaw, pitch roll angles in degrees.

Return type *Vector*

opk2mat (*angles*)

Calculate camera to world rotation matrix from omega, phi, kappa angles.

Parameters **angles** (*Vector*) – Omega, phi, kappa angles in degrees.

Returns Rotation matrix.

Return type *Matrix*

ypr2mat (*angles*)

Calculate camera to world rotation matrix from yaw, pitch, roll angles.

Parameters **angles** (*Vector*) – Yaw, pitch, roll angles in degrees.

Returns Rotation matrix.

Return type *Matrix*

class Metashape.**Vector**

n-component vector

```
>>> import Metashape
>>> vect = Metashape.Vector( (1, 2, 3) )
>>> vect2 = vect.copy()
>>> vect2.size = 4
>>> vect2.w = 5
>>> vect2 *= -1.5
>>> vect.size = 4
```

```
>>> vect.normalize()  
>>> Metashape.app.messageBox("Scalar product is " + str(vect2 * vect))
```

copy()

Return a copy of the vector.

Returns A copy of the vector.

Return type *Vector*

cross(a, b)

Cross product of 2 vectors.

Parameters

- **a** (*Vector*) – First vector.
- **b** (*Vector*) – Second vector.

Returns Cross product.

Return type *Vector*

norm()

Return norm of the vector.

norm2()

Return squared norm of the vector.

normalize()

Normalize vector to the unit length.

normalized()

Return a new, normalized vector.

Returns a normalized copy of the vector

Return type *Vector*

size

Vector dimensions.

Type int

w

Vector W component.

Type float

x

Vector X component.

Type float

y

Vector Y component.

Type float

z

Vector Z component.

Type float

zero()

Set all elements to zero.

class `Metashape.Version`

Version object contains application version numbers.

build

Build number.

Type `int`

copy()

Return a copy of the object.

Returns A copy of the object.

Return type `Version`

major

Major version number.

Type `int`

micro

Micro version number.

Type `int`

minor

Minor version number.

Type `int`

class `Metashape.Viewpoint` (*app*)

Represents viewpoint in the model view

center

Camera center.

Type `Vector`

coo

Center of orbit.

Type `Vector`

copy()

Return a copy of the object.

Returns A copy of the object.

Return type `Viewpoint`

fov

Camera vertical field of view in degrees.

Type `float`

height

OpenGL window height.

Type `int`

mag

Camera magnification defined by distance to the center of rotation.

Type `float`

rot

Camera rotation matrix.

Type *Matrix*

width

OpenGL window width.

Type int

class `Metashape.Vignetting`

Vignetting polynomial

copy ()

Return a copy of the object.

Returns A copy of the object.

Return type *Vignetting*

PYTHON API CHANGE LOG

3.1 Metashape version 1.6.4

- Added Model.Vertex.confidence attribute
- Added ConvertImages.use_initial_calibration attribute
- Added image_orientation, save_invalid_matches and use_initial_calibration to ExportCameras class
- Added ExportModel.save_confidence attribute
- Added crs and image_orientation attributes to ImportCameras class
- Added CalibrationFormatPhotomod to CalibrationFormat enum
- Added save_invalid_matches, use_initial_calibration and image_orientation arguments to Chunk.exportCameras() method
- Added save_confidence argument to Chunk.exportModel() method
- Added crs and image_orientation arguments to Chunk.importCameras() method
- Removed BuildUV.adaptive_resolution attribute
- Removed adaptive_resolution argument from Chunk.buildUV() method

3.2 Metashape version 1.6.3

- Added renderPreview() methods to DenseCloud, Model, Orthomosaic, PointCloud and TiledModel classes
- Added BuildUV.texture_size attribute
- Added DecimateModel.apply_to_selection attribute
- Added DetectFiducials.cameras, DetectFiducials.frames and DetectFiducials.generate_masks attributes
- Added ExportModel.embed_texture attribute
- Added clip_to_boundary attribute to ExportPoints, ExportModel, ExportTiledModel and ExportRaster classes
- Added RasterFormatGeoPackage to RasterFormat enum
- Added ShapesFormatGeoPackage to ShapesFormat enum
- Added source argument to Chunk.addSensor() method
- Added texture_size argument to Chunk.buildUV() method
- Added apply_to_selection argument to Chunk.decimateModel() method

- Added generate_masks, cameras and frames arguments to Chunk.detectFiducials() method
- Added embed_texture argument to Chunk.exportModel() method
- Added width, height, point_size and progress arguments to Chunk.renderPreview() method
- Added clip_to_boundary argument to Chunk.exportPoints(), Chunk.exportModel(), Chunk.exportTiledModel() and Chunk.exportRaster() methods
- Added meta argument to NetworkClient.createBatch() method
- Removed CalibrateLens.fit_p3 and CalibrateLens.fit_p4 attributes

3.3 Metashape version 1.6.2

- Added Application.ModelView and Application.OrthoView classes
- Added Application.removeMenuItem() method
- Added Model.transform() method
- Added PointCloud.cleanup() method
- Added Application.model_view and Application.ortho_view attributes
- Added BuildTexture.transfer_texture attribute
- Added PlanMission.min_pitch and PlanMission.max_pitch attributes
- Added columns, crs, delimiter, group_delimiters and skip_rows attributes to ImportShapes class
- Added CamerasFormatNVM to CamerasFormat enum
- Added PointsFormatPTX to PointsFormat enum
- Added ShapesFormatCSV to ShapesFormat enum
- Added transfer_texture argument to Chunk.buildTexture() method
- Added columns, crs, delimiter, group_delimiters and skip_rows arguments to Chunk.importShapes() method
- Moved ModelViewMode enum to ModelView class
- Renamed Application.console attribute to console_pane
- Renamed Application.captureModelView() method to ModelView.captureView()
- Renamed Application.captureOrthoView() method to OrthoView.captureView()
- Renamed Application.viewpoint attribute to ModelView.viewpoint
- Removed ReduceOverlap.capture_distance attribute
- Removed capture_distance argument from Chunk.reduceOverlap() method
- Changed default values of AlignCameras.reset_alignment and MatchPhotos.reset_matches attributes to False
- Changed default value of reset_alignment argument in Chunk.alignCameras() method to False
- Changed default value of reset_matches argument in Chunk.matchPhotos() method to False

3.4 Metashape version 1.6.1

- Added `Application.releaseFreeMemory()` method
- Added `CoordinateSystem.towgs84` attribute
- Added `Marker.enabled` attribute
- Added `BuildModel.subdivide_task` attribute
- Added `subdivide_task` argument to `Chunk.buildModel()` method
- Changed default value of `keep_depth` argument in `Chunk.buildModel()` and `Chunk.buildTiledModel()` to `True`

3.5 Metashape version 1.6.0

- Added `BBox`, `ImageCompression`, `RPCModel` and `Model.Texture` classes
- Added `Tasks.ImportTiledModel` and `Task.ColorizeModel` classes
- Added `CalibrationFormat` and `ReferencePreselectionMode` enums
- Added `Model.addTexture()` and `Model.remove()` methods
- Added `Model.getActiveTexture()` and `Model.setActiveTexture()` methods
- Added `NetworkClient.setMasterServer()` method
- Added `setClassesFilter()`, `setConfidenceFilter()`, `setSelectionFilter()` and `resetFilters()` methods to `DenseCloud` class
- Added `renderDepth()`, `renderImage()`, `renderMask()` and `renderNormalMap()` methods to `PointCloud`, `DenseCloud` and `TiledModel` classes
- Added `Chunk.renderPreview()` method
- Added `Utils.euler2mat()` and `Utils.mat2euler()` methods
- Added `Calibration.rpc` attribute
- Added `Marker.position_covariance` attribute
- Added `Model.textures` attribute
- Added `TiledModel.crs` and `TiledModel.transform` attributes
- Added `EulerAnglesPOK` and `EulerAnglesANK` values to `EulerAngles` enum
- Added `PointsFormatPCD` to `PointsFormat` enum
- Added `ShapesFormatGeoJSON` to `ShapesFormat` enum
- Added `RPC` to `Sensor.Type` enum
- Added `image_compression` attribute to `ExportOrthophotos`, `ExportRaster`, `ExportTiledModel` and `UndistortPhotos` classes
- Added `AddPhotos.load_rpc_txt` attribute
- Added `AlignCameras.min_image` attribute
- Added `BuildDenseCloud.point_confidence` attribute
- Added `BuildModel.vertex_confidence`, `BuildModel.max_workgroup_size` and `BuildModel.workitem_size_cameras` attributes

- Added BuildTexture.source_model and BuildTexture.texture_type attributes
- Added BuildUV.adaptive_resolution attribute
- Added DecimateModel.asset attribute
- Added ExportPanorama.image_compression attribute
- Added ExportPoints.save_classes and ExportPoints.save_confidence attributes
- Added ExportTexture.texture_type attribute
- Added ExportTiledModel.crs attribute
- Added ImportCameras.image_list and ImportCameras.load_image_list attributes
- Added ImportPoints.calculate_normals attribute
- Added MatchPhotos.guided_matching and MatchPhotos.reference_preselection_mode attributes
- Added MergeChunks.merge_depth_maps, MergeChunks.merge_elevations and MergeChunks.merge_orthomosaics attributes
- Added OptimizeCameras.fit_corrections attribute
- Added TriangulatePoints.max_error and TriangulatePoints.min_image attributes
- Added endpoints argument to PointCloud.pickPoint(), DenseCloud.pickPoint(), Model.pickPoint() and Tiled-Model.pickPoint() methods
- Added compression argument to Image.save() method
- Added cull_faces and add_alpha arguments to Model.renderDepth() method
- Added cull_faces, add_alpha and raster_transform arguments to Model.renderImage() method
- Added cull_faces argument to Model.renderMask() method
- Added cull_faces and add_alpha arguments to Model.renderNormalMap() method
- Moved TiffCompression enum to ImageCompression class
- Renamed Tasks.UndistortPhotos class to Tasks.ConvertImages
- Renamed Chunk.estimateImageQuality() method to Chunk.analyzePhotos()
- Renamed Chunk.buildPoints() method to Chunk.triangulatePoints()
- Renamed Chunk.loadReference() method to Chunk.importReference()
- Renamed Chunk.saveReference() method to Chunk.exportReference()
- Renamed Chunk.refineModel() method to Chunk.refineMesh()
- Renamed network_distribute tasks attribute to subdivide_task
- Renamed AlignChunks.align_method attribute to method
- Renamed AlignChunks.match_downscale attribute to downscale
- Renamed AlignChunks.match_filter_mask attribute to filter_mask
- Renamed AlignChunks.match_mask_tiepoints attribute to mask_tiepoints
- Renamed AlignChunks.match_point_limit attribute to keypoint_limit
- Renamed AlignChunks.match_select_pairs attribute to generic_preselection
- Renamed BuildDenseCloud.store_depth attribute to keep_depth
- Renamed BuildModel.store_depth attribute to keep_depth

- Renamed BuildOrthomosaic.ortho_surface attribute to surface_data
- Renamed BuildTiledModel.store_depth attribute to keep_depth
- Renamed BuildUV.texture_count attribute to page_count
- Renamed CalibrateColors.data_source attribute to source_data
- Renamed CalibrateColors.calibrate_color_balance attribute to white_balance
- Renamed ClassifyGroundPoints.cls_from attribute to source_class
- Renamed ClassifyPoints.cls_from attribute to source_class
- Renamed ClassifyPoints.cls_to attribute to target_classes
- Renamed DecimateModel.target_face_count attribute to face_count
- Renamed DuplicateChunk.copy_dense_cloud attribute to copy_dense_clouds
- Renamed ClassifyPoints.copy_elevation attribute to copy_elevations
- Renamed ClassifyPoints.copy_model attribute to copy_models
- Renamed ClassifyPoints.copy_orthomosaic attribute to copy_orthomosaics
- Renamed ClassifyPoints.copy_tiled_model attribute to copy_tiled_models
- Renamed ExportCameras.bingo_export_geoin attribute to bingo_save_geoin
- Renamed ExportCameras.bingo_export_gps attribute to bingo_save_gps
- Renamed ExportCameras.bingo_export_image attribute to bingo_save_image
- Renamed ExportCameras.bingo_export_itera attribute to bingo_save_itera
- Renamed ExportCameras.bundler_export_list attribute to bundler_save_list
- Renamed ExportCameras.chan_order_rotate attribute to chan_rotation_order
- Renamed ExportCameras.coordinates attribute to crs
- Renamed ExportCameras.export_markers attribute to save_markers
- Renamed ExportCameras.export_points attribute to save_points
- Renamed ExportMarkers.coordinates attribute to crs
- Renamed ExportModel.coordinates attribute to crs
- Renamed ExportModel.export_alpha attribute to save_alpha
- Renamed ExportModel.export_cameras attribute to save_cameras
- Renamed ExportModel.export_colors attribute to save_colors
- Renamed ExportModel.export_comment attribute to save_comment
- Renamed ExportModel.export_markers attribute to save_markers
- Renamed ExportModel.export_normals attribute to save_normals
- Renamed ExportModel.export_texture attribute to save_texture
- Renamed ExportModel.export_udim attribute to save_udim
- Renamed ExportModel.export_uv attribute to save_uv
- Renamed ExportOrthophotos.write_alpha attribute to save_alpha
- Renamed ExportOrthophotos.write_kml attribute to save_kml

- Renamed `ExportOrthophotos.write_world` attribute to `save_world`
- Renamed `ExportPoints.coordinates` attribute to `crs`
- Renamed `ExportPoints.data_source` attribute to `source_data`
- Renamed `ExportPoints.export_colors` attribute to `save_colors`
- Renamed `ExportPoints.export_comment` attribute to `save_comment`
- Renamed `ExportPoints.export_images` attribute to `save_images`
- Renamed `ExportPoints.export_normals` attribute to `save_normals`
- Renamed `ExportPoints.tile_height` attribute to `block_height`
- Renamed `ExportPoints.tile_width` attribute to `block_width`
- Renamed `ExportPoints.write_tiles` attribute to `split_in_blocks`
- Renamed `ExportRaster.data_source` attribute to `source_data`
- Renamed `ExportRaster.kmz_section_enable` attribute to `network_links`
- Renamed `ExportRaster.tile_width` attribute to `block_width`
- Renamed `ExportRaster.tile_height` attribute to `block_height`
- Renamed `ExportRaster.write_alpha` attribute to `save_alpha`
- Renamed `ExportRaster.write_kml` attribute to `save_kml`
- Renamed `ExportRaster.write_scheme` attribute to `save_scheme`
- Renamed `ExportRaster.write_tiles` attribute to `split_in_blocks`
- Renamed `ExportRaster.write_world` attribute to `save_world`
- Renamed `ExportRaster.xyz_level_min` attribute to `min_zoom_level`
- Renamed `ExportRaster.xyz_level_max` attribute to `max_zoom_level`
- Renamed `ExportShapes.coordinates` attribute to `crs`
- Renamed `ExportShapes.export_attributes` attribute to `save_attributes`
- Renamed `ExportShapes.export_labels` attribute to `save_labels`
- Renamed `ExportShapes.export_points` attribute to `save_points`
- Renamed `ExportShapes.export_polygons` attribute to `save_polygons`
- Renamed `ExportShapes.export_polylines` attribute to `save_polylines`
- Renamed `ExportTexture.write_alpha` attribute to `save_alpha`
- Renamed `ExportTiledModel.mesh_format` attribute to `model_format`
- Renamed `ImportMasks.method` attribute to `source`
- Renamed `ImportModel.coordinates` attribute to `crs`
- Renamed `ImportPoints.coordinates` attribute to `crs`
- Renamed `ImportReference.coordinates` attribute to `crs`
- Renamed `MatchPhotos.preselection_generic` attribute to `generic_preselection`
- Renamed `MatchPhotos.preselection_reference` attribute to `reference_preselection`
- Renamed `MatchPhotos.store_keypoints` attribute to `keep_keypoints`

- Renamed RefineMesh.niterations attribute to iterations
- Renamed SmoothModel.apply_to_selected attribute to apply_to_selection
- Renamed TrackMarkers.frame_start attribute to first_frame
- Renamed TrackMarkers.frame_end attribute to last_frame
- Renamed processing methods arguments to match task parameters names (e.g. dx/dy -> resolution_x/resolution_y, write_xxx -> save_xxx, export_xxx -> save_xxx, import_xxx -> load_xxx, preselection_generic -> generic_preselection, preselection_reference -> reference_preselection, source_data -> data_source, etc.)
- Replaced Chunk.importDem() method with Chunk.importRaster() method
- Replaced Chunk.exportDem() and Chunk.exportOrthomosaic() methods with Chunk.exportRaster() method
- Removed Accuracy and Quality enums
- Removed Model.texture() and Model.setTexture() methods
- Removed ExportPoints.precision attribute
- Removed OptimizeCameras.fit_p3 and OptimizeCameras.fit_p4 attributes
- Removed PlanMission.max_cameras and PlanMission.use_cameras attributes
- Removed tiff_big, tiff_tiled and tiff_overviews attributes from ExportOrthophotos and ExportRaster classes
- Removed tiff_compression attribute from ExportOrthophotos, ExportRaster and UndistortPhotos classes
- Removed jpeg_quality attribute from ExportOrthophotos, ExportRaster, ExportTiledModel and UndistortPhotos classes

3.6 Metashape version 1.5.5

No Python API changes

3.7 Metashape version 1.5.4

- Added Tasks.FilterDenseCloud class
- Added TiledModel.FaceCount enum
- Added copy() method to Antenna, Calibration, ChunkTransform, CirTransform, CoordinateSystem, Document, MetaData, OrthoProjection, RasterTransform, Region, Shutter, Target, Version, Viewpoint and Vignetting classes
- Added CameraTrack.save() and CameraTrack.load() methods
- Added Chunk.reduceOverlap() method
- Added location_enabled and rotation_enabled attributes to Sensor.Reference class
- Added CameraTrack.chunk and CameraTrack.meta attributes
- Added BuildTiledModel.ghosting_filter and BuildTiledModel.transfer_texture attributes
- Added ExportPoints.network_distribute and ExportPoints.region attributes
- Added ExportTiledModel.jpeg_quality and ExportTiledModel.texture_format attributes
- Added prevent_intersections argument to Chunk.buildContours() method

- Added `transfer_texture` argument to `Chunk.buildTiledModel()` method
- Added `region` argument to `Chunk.exportPoints()` method
- Added `texture_format` and `jpeg_quality` arguments to `Chunk.exportTiledModel()` method
- Added `progress` argument to `Chunk.importMarkers()` method
- Added `ImageFormatWebP` to `ImageFormat` enum

3.8 Metashape version 1.5.3

- Added `DepthMap.getCalibration()` and `DepthMap.setCalibration()` methods
- Added `NetworkClient.dumpBatches()`, `NetworkClient.loadBatches()` and `NetworkClient.setBatchNodeLimit()` methods
- Added `location_enabled` and `rotation_enabled` attributes to `Camera.Reference` class
- Added `keep_depth` argument to `Chunk.buildTiledModel()` method
- Added `uv` argument to `Chunk.exportModel()` method
- Added `level` argument to `DepthMap.image()` and `DepthMap.setImage()` methods
- Changed default value of `keep_depth` argument in `Chunk.buildDenseCloud()` and `Chunk.buildModel()` methods to `True`
- Changed default value of `max_neighbors` argument in `Chunk.buildDenseCloud()` method to 100

3.9 Metashape version 1.5.2

- Added `CameraTrack` class
- Added `Tasks.PlanMission` and `Tasks.ReduceOverlap` classes
- Added `Camera.Type` enum
- Added `Chunk.addCameraTrack()` method
- Added `Application.title` attribute
- Added `Camera.type` attribute
- Added `Chunk.camera_track` and `Chunk.camera_tracks` attributes
- Added `BuildModel.trimming_radius` attribute
- Added `DetectMarkers.filter_mask` attribute
- Added `ImportReference.shutter_lag` attribute
- Added `Bundler` and `BINGO` specific attributes to `ExportCameras` class
- Added `supports_gpu` attribute to task classes
- Added `x`, `y`, `w`, `h` arguments to `Image.open()` method
- Added `filter_mask` argument to `Chunk.detectMarkers()` method
- Added `image_list` argument to `Chunk.importCameras()` method
- Added `shutter_lag` argument to `Chunk.loadReference()` method

- Added ImageFormatBIL, ImageFormatXYZ, ImageFormatDDS to ImageFormat enum
- Removed Tasks.PlanMotion class
- Removed Animation class
- Removed Chunk.animation attribute
- Removed smoothness attribute from Tasks.BuildModel and Tasks.BuildTiledModel classes
- Removed quality and reuse_depth arguments from Chunk.buildModel() method
- Removed downscale, filter_mode, max_neighbors, max_workgroup_size, network_distribute, reuse_depth, workitem_size_cameras from Tasks.BuildModel class

3.10 Metashape version 1.5.1

- Added License class
- Added Tasks.MergeAssets class
- Added Metashape.license attribute
- Renamed Tasks.OptimizeCoverage class to Tasks.PlanMotion

3.11 Metashape version 1.5.0

- Added Sensor.Reference class
- Added Tasks.ClassifyPoints and Tasks.OptimizeCoverage classes
- Added DataType enum
- Added Model.TextureType enum
- Added Tasks.TargetType enum
- Added Animation.Track.resize() method
- Added Chunk.findFrame() method
- Added DenseCloud.classifyPoints() method
- Added Document.findChunk() method
- Added Model.Faces.resize(), Model.Vertices.resize() and Model.TexVertices.resize() methods
- Added Tasks.createTask() method
- Added decode(), decodeJSON(), encodeJSON() methods to task classes
- Added Antenna.location_covariance and Antenna.rotation_covariance attributes
- Added Camera.calibration, Camera.location_covariance and Camera.rotation_covariance attributes
- Added Chunk.image_contrast attribute
- Added DenseCloud.bands and DenseCloud.data_type attributes
- Added Model.bands and Model.data_type attributes
- Added Elevation.palette attribute
- Added Model.Face.tex_index attribute

- Added Orthomosaic.bands and Orthomosaic.data_type attributes
- Added PointCloud.Point.cov attribute
- Added PointCloud.bands and PointCloud.data_type attributes
- Added Sensor.data_type, Sensor.film_camera, Sensor.location_covariance, Sensor.reference and Sensor.rotation_covariance attributes
- Added Sensor.fixed_params and Sensor.photo_params attributes
- Added TiledModel.bands and TiledModel.data_type attributes
- Added AlignChunks.markers and AlignChunks.match_mask_tiepoints attributes
- Added BuildOrthomosaic.refine_seamlines attribute
- Added DetectMarkers.cameras and DetectMarkers.maximum_residual attributes
- Added ExportModel.colors_rgb_8bit and ExportPoints.colors_rgb_8bit attributes
- Added ExportOrthophotos.tiff_tiled and ExportRaster.tiff_tiled attributes
- Added OptimizeCameras.tiepoint_covariance attribute
- Added BuildModel.smoothness and BuildTiledModel.smoothness attributes
- Added target and workitem_count attributes to task classes
- Added max_workgroup_size and workitem_size_tiles attributes to Tasks.BuildDem class
- Added max_workgroup_size and workitem_size_cameras attributes to Tasks.BuildDenseCloud class
- Added max_workgroup_size and workitem_size_cameras attributes to Tasks.BuildDepthMaps class
- Added max_workgroup_size and workitem_size_cameras attributes to Tasks.BuildModel class
- Added max_workgroup_size, workitem_size_cameras and workitem_size_tiles attributes to Tasks.BuildOrthomosaic class
- Added max_workgroup_size, workitem_size_cameras and face_count attributes to Tasks.BuildTiledModel class
- Added max_workgroup_size, workitem_size_cameras and workitem_size_pairs attributes to Tasks.MatchPhotos class
- Added refine_seamlines argument to Chunk.buildOrthomosaic() method
- Added face_count argument to Chunk.buildTiledModel() method
- Added keypoints argument to Chunk.copy() method
- Added maximum_residual and cameras arguments to Chunk.detectMarkers() method
- Added tiff_tiled argument to Chunk.exportDem(), Chunk.exportOrthomosaic() and Chunk.exportOrthophotos() methods
- Added colors_rgb_8bit argument to Chunk.exportModel() and Chunk.exportPoints() methods
- Added tiepoint_covariance argument to Chunk.optimizeCameras() method
- Added confidence argument to DenseCloud.classifyPoints() method
- Added mask_tiepoints and markers arguments to Document.alignChunks() method
- Added ignore_lock argument to Document.open() method
- Added type argument to Model.setTexture() and Model.texture() methods
- Added workitem argument to Task.apply() method

- Added ModelFormatGLTF and ModelFormatX3D to ModelFormat enum
- Added Car and Manmade to PointClass enum
- Changed default value of filter argument in Chunk.buildDepthMaps() to MildFiltering
- Removed Tasks.BuildModel.visibility_mesh attribute

3.12 PhotoScan version 1.4.4

- Added AddPhotos.strip_extensions attribute
- Added ExportRaster.image_description attribute
- Added ExportShapes.export_attributes, ExportShapes.export_labels and ExportShapes.polygons_as_polylines attributes
- Added image_description argument to Chunk.exportDem() and Chunk.exportOrthomosaic() methods
- Added format, polygons_as_polylines, export_labels and export_attributes arguments to Chunk.exportShapes() method
- Added format argument to Chunk.importShapes() method
- Added RasterFormatTMS to RasterFormat enum

3.13 PhotoScan version 1.4.3

- Added Version class
- Added Tasks.DetectFiducials class
- Added Chunk.detectFiducials() method
- Added Sensor.calibrateFiducials() method
- Added CoordinateSystem.addGeoid() method
- Added PhotoScan.version attribute
- Added Sensor.normalize_to_float attribute
- Added minimum_dist attribute to Tasks.DetectMarkers class
- Added minimum_dist argument to Chunk.detectMarkers() and Utils.detectTargets() methods
- Added keypoints argument to PointCloud.copy() method
- Changed default value of adaptive_fitting argument in Chunk.alignCameras() to False

3.14 PhotoScan version 1.4.2

- Added Tasks.ColorizeDenseCloud class
- Added PointCloud.removeKeypoints() method
- Added CoordinateSystem.transformationMatrix() method
- Added Vector.cross() method

- Added `Shapes.updateAltitudes()` method
- Added `log_enable`, `log_path`, `network_enable`, `network_host`, `network_path` and `network_port` attributes to `Application.Settings` class
- Added `covariance_matrix` and `covariance_params` attributes to `Calibration` class
- Added `flip_x`, `flip_y`, `flip_z` attributes to `Tasks.BuildDem` and `Tasks.BuildOrthomosaic` classes
- Added `max_neighbors` attribute to `Tasks.BuildDenseCloud`, `Tasks.BuildDepthMaps` and `Tasks.BuildModel` classes
- Added `jpeg_quality`, `tiff_compression` and `update_gps_tags` attributes to `Tasks.UndistortPhotos` class
- Added `copy_keypoints` attribute to `Tasks.DuplicateChunk` class
- Added `width`, `height` and `world_transform` attributes to `Tasks.ExportRaster` class
- Added `store_depth` attribute to `Tasks.BuildTiledModel` class
- Added `DenseCloud.crs` and `DenseCloud.transform` attributes
- Added `CoordinateSystem.wkt2` attribute
- Added `keep_keypoints` argument to `Chunk.matchPhotos()` method
- Added `flip_x`, `flip_y`, `flip_z` arguments to `Chunk.buildDem()` and `Chunk.buildOrthomosaic()` methods
- Added `max_neighbors` argument to `Chunk.buildDenseCloud()` and `Chunk.buildDepthMaps()` methods
- Added `cull_faces` argument to `Chunk.buildOrthomosaic()` method
- Added `reuse_depth` and `ghosting_filter` arguments to `Chunk.buildTiledModel()` method
- Added `use_reflectance_panels` and `use_sun_sensor` arguments to `Chunk.calibrateReflectance()` method
- Added `width`, `height` and `world_transform` arguments to `Chunk.exportDem()` and `Chunk.exportOrthomosaic()` methods
- Added `filter_mask` argument to `Chunk.estimateImageQuality()` method
- Added `revision` argument to `NetworkClient.nodeList()` method
- Added `ImagesData` to `DataSource` enum
- Added `ModelFormatOSGB` to `ModelFormat` enum
- Added `TiledModelFormatOSGB` to `TiledModelFormat` enum

3.15 PhotoScan version 1.4.1

- Added `OrthoProjection.Type` enum
- Added `Camera.image()` method
- Added `Chunk.loadReflectancePanelCalibration()` method
- Added `PointCloud.Points.copy()` and `PointCloud.Points.resize()` methods
- Added `PointCloud.Projections.resize()` method
- Added `PointCloud.Tracks.copy()` and `PointCloud.Tracks.resize()` methods
- Added `OrthoProjection.matrix`, `OrthoProjection.radius` and `OrthoProjection.type` attributes
- Added `Tasks.AnalyzePhotos.filter_mask` attribute

- Added `Tasks.CalibrateReflectance.use_reflectance_panels` and `Tasks.CalibrateReflectance.use_sun_sensor` attributes
- Added `Tasks.MatchPhotos.mask_tiepoints` attribute
- Added `Tasks.OptimizeCameras.adaptive_fitting` attribute
- Added `strip_extensions` argument to `Chunk.addPhotos()` method
- Added `keep_depth` argument to `Chunk.buildDenseCloud()` method
- Added `adaptive_resolution` argument to `Chunk.buildUV()` method
- Added `alpha` argument to `Chunk.exportModel()` method
- Added `mask_tiepoints` argument to `Chunk.matchPhotos()` method
- Added `adaptive_fitting` argument to `Chunk.optimizeCameras()` method
- Added `mask` argument to `Utils.estimateImageQuality()` method
- Added `CamerasFormatABC` and `CamerasFormatFBX` to `CamerasFormat` enum
- Added `ImageFormatJP2` to `ImageFormat` enum
- Added `LegacyMapping` to `MappingMode` enum

3.16 PhotoScan version 1.4.0

- Added `Tasks` classes
- Added `Animation`, `OrthoProjection`, `Target` and `Vignetting` classes
- Added `ShapesFormat` enum
- Added `Marker.Type` enum
- Added `Chunk.calibrateColors()`, `Chunk.calibrateReflectance()` and `Chunk.locateReflectancePanels()` methods
- Added `Chunk.buildDepthMaps()`, `Chunk.importPoints()`, `Chunk.refineModel()` and `Chunk.removeLighting()` methods
- Added `Chunk.addDenseCloud()`, `Chunk.addDepthMaps()`, `Chunk.addElevation()`, `Chunk.addModel()`, `Chunk.addOrthomosaic()` and `Chunk.addTiledModel()` methods
- Added `Chunk.sortCameras()`, `Chunk.sortMarkers()` and `Chunk.sortScalebars()` methods
- Added `DenseCloud.clear()` method
- Added `DepthMaps.clear()` and `DepthMaps.copy()` methods
- Added `Elevation.clear()` and `Elevation.copy()` methods
- Added `Model.clear()` method
- Added `Orthomosaic.clear()` and `Orthomosaic.copy()` methods
- Added `TiledModel.clear()` and `TiledModel.copy()` methods
- Added `Image.gaussianBlur()` and `Image.uniformNoise()` methods
- Added `NetworkTask.encode()` method
- Added `Utils.createChessboardImage()` and `Utils.detectTargets()` methods
- Added `Camera.Reference.location_accuracy` and `Camera.Reference.rotation_accuracy` attributes

- Added Camera.layer_index, Camera.master and Camera.vignetting attributes
- Added Chunk.dense_clouds, Chunk.depth_maps_sets, Chunk.elevations, Chunk.models, Chunk.orthomosaics and Chunk.tiled_models attributes
- Added Chunk.animation, Chunk.camera_crs, Chunk.marker_crs and Chunk.world_crs attributes
- Added CoordinateSystem.geoccs and CoordinateSystem.geoid_height attributes
- Added Marker.Projection.valid attribute
- Added Sensor.black_level, Sensor.fiducials, Sensor.fixed_calibration, Sensor.fixed_location, Sensor.fixed_rotation, Sensor.layer_index, Sensor.location, Sensor.master, Sensor.normalize_sensitivity, Sensor.rolling_shutter, Sensor.rotation, Sensor.sensitivity and Sensor.vignetting attributes
- Added Camera.chunk, Marker.chunk, Scalebar.chunk and Sensor.chunk attributes
- Added Marker.sensor and Marker.type attributes
- Added Elevation.projection, Orthomosaic.projection and Shapes.projection attributes
- Added DenseCloud.key and DenseCloud.label attributes
- Added DepthMaps.key and DepthMaps.label attributes
- Added Elevation.key and Elevation.label attributes
- Added Model.key and Model.label attributes
- Added Orthomosaic.key and Orthomosaic.label attributes
- Added TiledModel.key and TiledModel.label attributes
- Added point_colors argument to Chunk.buildDenseCloud() method
- Added ghosting_filter argument to Chunk.buildTexture() method
- Added minimum_size argument to Chunk.detectMarkers() method
- Added raster_transform argument to Chunk.exportModel(), Chunk.exportPoints(), Chunk.exportTiledModel() methods
- Added tiff_overviews argument to Chunk.exportDem(), Chunk.exportOrthomosaic() and Chunk.exportOrthophotos() methods
- Added min_zoom_level and max_zoom_level arguments to Chunk.exportDem() and Chunk.exportOrthomosaic() methods
- Added cameras argument to Chunk.exportOrthophotos() method
- Added image_format argument to Chunk.exportPoints() method
- Added page_numbers argument to Chunk.exportReport() method
- Added items, crs, ignore_labels, threshold and progress arguments to Chunk.loadReference() method
- Added create_markers argument to Chunk.loadReference() method
- Added progress argument to Chunk.saveReference() method
- Added quality, volumetric_masks, keep_depth and reuse_depth arguments to Chunk.buildModel() method
- Added selected_faces and fix_borders arguments to Chunk.smoothModel() method
- Added export_points, export_markers, use_labels and progress arguments to Chunk.exportCameras() method
- Added channels and datatype arguments to Photo.image() method
- Added CamerasFormatBlocksExchange and CamerasFormatORIMA to CamerasFormat enum

- Added ImageFormatNone to ImageFormat enum
- Added UndefinedLayout to ImageLayout enum
- Added ModelFormatNone and ModelFormatABC to ModelFormat enum
- Added PointsFormatNone and PointsFormatCesium to PointsFormat enum
- Added RasterFormatNone to RasterFormat enum
- Added ReferenceFormatNone and ReferenceFormatAPM to ReferenceFormat enum
- Added TiledModelFormatNone, TiledModelFormatCesium and TiledModelFormatSLPK to TiledModelFormat enum
- Renamed Chunk.master_channel attribute to Chunk.primary_channel
- Removed MatchesFormat enum
- Removed Chunk.exportMatches() method
- Removed Camera.Reference.accuracy_ypr attribute
- Removed quality, filter, cameras, keep_depth, reuse_depth arguments from Chunk.buildDenseCloud() method
- Removed color_correction argument from Chunk.buildOrthomosaic() and Chunk.buildTexture() methods
- Removed fit_shutter argument from Chunk.optimizeCameras() method

3.17 PhotoScan version 1.3.5

No Python API changes

3.18 PhotoScan version 1.3.4

No Python API changes

3.19 PhotoScan version 1.3.3

- Added network_links argument to Chunk.exportDem() and Chunk.exportOrthomosaic() methods
- Added read_only argument to Document.open() method
- Added NetworkClient.setNodeCPUEnable() and NetworkClient.setNodeGPUMask() methods
- Added Chunk.modified, DenseCloud.modified, DepthMaps.modified, Document.modified, Elevation.modified, Masks.modified, Model.modified, Orthomosaic.modified, PointCloud.modified, Shapes.modified, Thumbnails.modified, TiledModel.modified attributes
- Added Document.read_only attribute
- Added CamerasFormatSummit to CamerasFormat enum

3.20 PhotoScan version 1.3.2

- Added `vertex_colors` argument to `Chunk.buildModel()` method
- Added `Shape.vertex_ids` attribute

3.21 PhotoScan version 1.3.1

- Added `Settings` and `TiledModel` classes
- Added `Application.getBool()` method
- Added `Camera.unproject()` method
- Added `Chunk.addFrames()`, `Chunk.addMarkerGroup()`, `Chunk.addScalebarGroup()` and `Chunk.buildSeamlines()` methods
- Added `DenseCloud.pickPoint()` and `DenseCloud.updateStatistics()` methods
- Added `Elevation.altitude()` method
- Added `Matrix.svd()` method
- Added `Model.pickPoint()` method
- Added `Orthomosaic.reset()` and `Orthomosaic.update()` methods
- Added `PointCloud.pickPoint()` method
- Added `filter` argument to `Application.getOpenFileName()`, `Application.getOpenFileNames()` and `Application.getSaveFileName()` methods
- Added `point` and `visibility` arguments to `Chunk.addMarker()` method
- Added `raster_transform` and `write_scheme` arguments to `Chunk.exportDem()` method
- Added `write_scheme` and `white_background` arguments to `Chunk.exportOrthomosaic()` method
- Added `white_background` argument to `Chunk.exportOrthophotos()` method
- Added `projection` argument to `Chunk.exportMarkers()` method
- Added `markers` argument to `Chunk.exportModel()` method
- Added `pairs` argument to `Chunk.matchPhotos()` method
- Added `columns` and `delimiter` arguments to `Chunk.saveReference()` method
- Added `version` argument to `Document.save()` method
- Renamed `npasses` argument in `Chunk.smoothModel()` method to `strength` and changed its type to `float`
- Renamed `from` and `to` arguments in `CoordinateSystem.transform()`, `DenseCloud.assignClass()`, `DenseCloud.assignClassToSelection()` and `DenseCloud.classifyGroundPoints()` methods to avoid collision with reserved words
- Added `Application.settings` attribute
- Added `Chunk.tiled_model` attribute
- Added `ShapeGroup.color` and `ShapeGroup.show_labels` attributes
- Added `ImageFormatTGA` to `ImageFormat` enum

3.22 PhotoScan version 1.3.0

- Added MarkerGroup, Masks, ScalebarGroup, Shutter and Thumbnails classes
- Added Application.PhotosPane class
- Added Model.Statistics class
- Added Orthomosaic.Patch and Orthomosaic.Patches classes
- Added PointCloud.Filter class
- Added CamerasFormat, EulerAngles, ImageFormat, ImageLayout, MaskOperation, MaskSource, MatchesFormat, ModelFormat, ModelViewMode, PointClass, PointsFormat, RasterFormat, ReferenceFormat, ReferenceItems, RotationOrder, TiffCompression, TiledModelFormat enums
- Added Application.captureOrthoView() method
- Added Chunk.refineMarkers() method
- Added CoordinateSystem.listBuiltinCRS() class method
- Added Matrix.translation() method
- Added Model.statistics() method
- Added NetworkClient.serverInfo(), NetworkClient.nodeStatus(), NetworkClient.setNodeCapability() and NetworkClient.quitNode() methods
- Added Photo.imageMeta() method
- Added Shape.area(), Shape.perimeter2D(), Shape.perimeter3D() and Shape.volume() methods
- Added Utils.createMarkers() method
- Added source argument to Application.captureModelView() method
- Added image_format argument to Chunk.exportDem() method
- Added write_alpha argument to Chunk.exportOrthophotos() method
- Added image_format and write_alpha arguments to Chunk.exportOrthomosaic() method
- Added groups, projection, shift and progress arguments to Chunk.exportShapes() method
- Added items and progress arguments to Chunk.copy() method
- Added sensor argument to Chunk.addCamera() method
- Added layout argument to Chunk.addPhotos() method
- Added jpeg_quality argument to Chunk.exportOrthomosaic() and Chunk.exportOrthophotos() methods
- Added fill_holes argument to Chunk.buildOrthomosaic() method
- Added fit_shutter argument to Chunk.optimizeCameras() method
- Added settings argument to Chunk.exportReport() method
- Added progress argument to various DenseCloud methods
- Added from argument to DenseCloud.classifyGroundPoints() method
- Added chunks and progress arguments to Document.append() method
- Added progress argument to Document.alignChunks() and Document.mergeChunks() methods
- Added revision argument to NetworkClient.batchList(), NetworkClient.batchStatus() methods

- Added Application.photos_pane attribute
- Added Camera.shutter attribute
- Added Chunk.masks and Chunk.thumbnails attributes
- Added Chunk.marker_groups and Chunk.scalebar_groups attributes
- Added Chunk.euler_angles and Chunk.scalebar_accuracy attributes
- Added CoordinateSystem.name attribute
- Added Marker.group and Scalebar.group attributes
- Added Orthomosaic.patches attribute
- Added RasterTransform.false_color attribute
- Added Sensor.bands attribute
- Added Shape.attributes attribute
- Added DepthMapsData, TiledModelData and OrthomosaicData to DataSource enum
- Added CircularTarget14bit to TargetType enum
- Renamed CameraReference class to Camera.Reference
- Renamed ConsolePane class to Application.ConsolePane
- Renamed MarkerProjection class to Marker.Projection
- Renamed MarkerProjections class to Marker.Projections
- Renamed MarkerReference class Marker.Reference
- Renamed MeshFace class to Model.Face
- Renamed MeshFaces class to Model.Faces
- Renamed MeshTexVertex class to Model.TexVertex
- Renamed MeshTexVertices class to Model.TexVertices
- Renamed MeshVertex class to Model.Vertex
- Renamed MeshVertices class to Model.Vertices
- Renamed PointCloudCameras class to PointCloud.Cameras
- Renamed PointCloudPoint class to PointCloud.Point
- Renamed PointCloudPoints class to PointCloud.Points
- Renamed PointCloudProjection class to PointCloud.Projection
- Renamed PointCloudProjections class to PointCloud.Projections
- Renamed PointCloudTrack class to PointCloud.Track
- Renamed PointCloudTracks class to PointCloud.Tracks
- Renamed ScalebarReference class to Scalebar.Reference
- Renamed ShapeVertices class to Shape.Vertices
- Renamed Application.enumOpenCLDevices() method to Application.enumGPUDevices()
- Renamed Shape.boundary attribute to Shape.boundary_type
- Renamed Chunk.accuracy_cameras to Chunk.camera_location_accuracy

- Renamed `Chunk.accuracy_cameras_ypr` to `Chunk.camera_rotation_accuracy`
- Renamed `Chunk.accuracy_markers` to `Chunk.marker_location_accuracy`
- Renamed `Chunk.accuracy_projections` to `Chunk.marker_projection_accuracy`
- Renamed `Chunk.accuracy_tiepoints` to `Chunk.tiepoint_accuracy`
- Renamed method argument in `Chunk.importMasks()` method to `source` and changed its type to `MaskSource`
- Replaced `preselection` argument with `generic_preselection` and `reference_preselection` arguments in `Chunk.matchPhotos()` method
- Replaced `fit_cxcy` argument with `fit_cx` and `fit_cy` arguments in `Chunk.optimizeCameras()` method
- Replaced `fit_k1k2k3` argument with `fit_k1`, `fit_k2` and `fit_k3` arguments in `Chunk.optimizeCameras()` method
- Replaced `fit_p1p2` argument with `fit_p1` and `fit_p2` arguments in `Chunk.optimizeCameras()` method
- Replaced `Application.cpu_cores_inactive` with `Application.cpu_enable` attribute
- Changed type of `source_data` argument in `Chunk.buildContours()` to `DataSource`
- Changed type of `format` argument in `Chunk.importCameras()` and `Chunk.exportCameras()` methods to `Cameras-Format`
- Changed type of `rotation_order` argument in `Chunk.exportCameras()` to `RotationOrder`
- Changed type of `format` argument in `Chunk.exportDem()` and `Chunk.exportOrthomosaic()` methods to `Raster-Format`
- Changed type of `format` argument in `Chunk.exportMatches()` method to `MatchesFormat`
- Changed type of `texture_format` argument in `Chunk.exportModel()` method to `ImageFormat`
- Changed type of `format` argument in `Chunk.importModel()` and `Chunk.exportModel()` methods to `ModelFormat`
- Changed type of `format` argument in `Chunk.exportPoints()` method to `PointsFormat`
- Changed type of `tiff_compression` argument in `Chunk.exportOrthomosaic()` and `Chunk.exportOrthophotos()` methods to `TiffCompression`
- Changed type of `items` argument in `Chunk.exportShapes()` method to `Shape.Type`
- Changed type of `format` argument in `Chunk.exportTiledModel()` method to `TiledModelFormat`
- Changed type of `mesh_format` argument in `Chunk.exportTiledModel()` method to `ModelFormat`
- Changed type of `operation` argument in `Chunk.importMasks()` method to `MaskOperation`
- Changed type of `format` argument in `Chunk.loadReference()` and `Chunk.saveReference()` methods to `Reference-Format`
- Changed type of `items` argument in `Chunk.saveReference()` method to `ReferenceItems`
- Removed return values from `Camera.open()`, `Chunk.addPhotos()`, `Chunk.alignCameras()`, `Chunk.buildContours()`, `Chunk.buildDem()`, `Chunk.buildDenseCloud()`, `Chunk.buildModel()`, `Chunk.buildOrthomosaic()`, `Chunk.buildPoints()`, `Chunk.buildTexture()`, `Chunk.buildTiledModel()`, `Chunk.buildUV()`, `Chunk.decimateModel()`, `Chunk.detectMarkers()`, `Chunk.estimateImageQuality()`, `Chunk.exportCameras()`, `Chunk.exportDem()`, `Chunk.exportMarkers()`, `Chunk.exportMatches()`, `Chunk.exportModel()`, `Chunk.exportOrthomosaic()`, `Chunk.exportOrthophotos()`, `Chunk.exportPoints()`, `Chunk.exportReport()`, `Chunk.exportShapes()`, `Chunk.exportTiledModel()`, `Chunk.importCameras()`, `Chunk.importDem()`, `Chunk.importMarkers()`, `Chunk.importMasks()`, `Chunk.importModel()`, `Chunk.importShapes()`, `Chunk.loadReference()`, `Chunk.loadReferenceExif()`, `Chunk.matchPhotos()`, `Chunk.optimizeCameras()`, `Chunk.remove()`, `Chunk.saveReference()`, `Chunk.smoothModel()`, `Chunk.thinPointCloud()`, `Chunk.trackMarkers()`, `CirTransform.calibrate()`, `CoordinateSystem.init()`

DenseCloud.classifyGroundPoints(), DenseCloud.compactPoints(), DenseCloud.selectMaskedPoints(), DenseCloud.selectPointsByColor(), Document.alignChunks(), Document.append(), Document.clear(), Document.mergeChunks(), Document.open(), Document.remove(), Document.save(), Mask.load(), Model.closeHoles(), Model.fixTopology(), Model.loadTexture(), Model.removeComponents(), Model.saveTexture(), Model.setTexture(), NetworkClient.abortBatch(), NetworkClient.abortNode(), NetworkClient.connect(), NetworkClient.pauseBatch(), NetworkClient.pauseNode(), NetworkClient.resumeBatch(), NetworkClient.resumeNode(), NetworkClient.setBatchPriority(), NetworkClient.setNodePriority(), Photo.open(), PointCloud.export(), RasterTransform.calibrateRange(), Thumbnail.load() methods in favor of exceptions

- Removed Chunk.exportContours() method
- Removed obsolete Matrix.diag() and Matrix.translation() class methods
- Removed unused focal_length argument from Calibration.save() method
- Modified Utils.mat2opk() and Utils.opk2mat() methods to work with camera to world rotation matrices

3.23 PhotoScan version 1.2.6

No Python API changes

3.24 PhotoScan version 1.2.5

- Added ShapeGroup and ShapeVertices classes
- Added CoordinateSystem.proj4 and CoordinateSystem.geogcs attributes
- Added Shapes.shapes and Shapes.groups attributes
- Added Shape.label, Shape.vertices, Shape.group, Shape.has_z, Shape.key and Shape.selected attributes
- Added Shapes.addGroup(), Shapes.addShape() and Shapes.remove() methods
- Added CoordinateSystem.transform() method
- Added Matrix.Diag(), Matrix.Rotation(), Matrix.Translation() and Matrix.Scale() class methods
- Added Matrix.rotation() and Matrix.scale() methods
- Added DenseCloud.restorePoints() and DenseCloud.selectPointsByColor() methods
- Added Application.captureModelView() method
- Added Mask.invert() method
- Added adaptive_fitting parameter to Chunk.alignCameras() method
- Added load_rotation and load_accuracy parameters to Chunk.loadReferenceExif() method
- Added source parameter to Chunk.buildTiledModel() method
- Added fill_holes parameter to Chunk.buildTexture() method

3.25 PhotoScan version 1.2.4

- Added NetworkClient and NetworkTask classes

- Added Calibration.f, Calibration.b1, Calibration.b2 attributes
- Added Chunk.exportMatches() method
- Added DenseCloud.compactPoints() method
- Added Orthomosaic.removeOrthophotos() method
- Added fit_b1 and fit_b2 parameters to Chunk.optimizeCameras() method
- Added tiff_big parameter to Chunk.exportOrthomosaic(), Chunk.exportDem() and Chunk.exportOrthophotos() methods
- Added classes parameter to Chunk.exportPoints() method
- Added progress parameter to processing methods
- Removed Calibration.fx, Calibration.fy, Calibration.skew attributes

3.26 PhotoScan version 1.2.3

- Added tiff_compression parameter to Chunk.exportOrthomosaic() and Chunk.exportOrthophotos() methods

3.27 PhotoScan version 1.2.2

- Added Camera.orientation attribute
- Added chunks parameter to Document.save() method

3.28 PhotoScan version 1.2.1

- Added CirTransform and RasterTransform classes
- Added Chunk.cir_transform and Chunk.raster_transform attributes
- Added Chunk.exportOrthophotos() method
- Added udim parameter to Chunk.exportModel() method
- Renamed RasterTransform enum to RasterTransformType

3.29 PhotoScan version 1.2.0

- Added Elevation and Orthomosaic classes
- Added Shape and Shapes classes
- Added Antenna class
- Added DataSource enum
- Added Camera.error() method
- Added Chunk.buildContours() and Chunk.exportContours() methods
- Added Chunk.importShapes() and Chunk.exportShapes() methods

- Added `Chunk.exportMarkers()` and `Chunk.importMarkers()` methods
- Added `Chunk.importDem()` method
- Added `Chunk.buildDem()`, `Chunk.buildOrthomosaic()` and `Chunk.buildTiledModel()` methods
- Added `PointCloud.removeSelectedPoints()` and `PointCloud.cropSelectedPoints()` methods
- Added `Utils.mat2opk()`, `Utils.mat2ypr()`, `Utils.opk2mat()` and `Utils.ypr2mat()` methods
- Added `Chunk.elevation`, `Chunk.orthomosaic` and `Chunk.shapes` attributes
- Added `Chunk.accuracy_cameras_ypr` attribute
- Added `Sensor.antenna`, `Sensor.plane_count` and `Sensor.planes` attributes
- Added `Calibration.p3` and `Calibration.p4` attributes
- Added `Camera.planes` attribute
- Added `CameraReference.accuracy_ypr` attribute
- Added `CameraReference.accuracy`, `MarkerReference.accuracy` and `ScalebarReference.accuracy` attributes
- Added `Application.activated` attribute
- Added `Chunk.image_brightness` attribute
- Added `fit_p3` and `fit_p4` parameters to `Chunk.optimizeCameras()` method
- Added `icon` parameter to `Application.addItem()` method
- Added `title` and `description` parameters to `Chunk.exportReport()` method
- Added `operation` parameter to `Chunk.importMasks()` method
- Added `columns`, `delimiter`, `group_delimiters`, `skip_rows` parameters to `Chunk.loadReference()` method
- Added `items` parameter to `Chunk.saveReference()` method
- Renamed `Chunk.exportModelTiled()` to `Chunk.exportTiledModel()`
- Renamed `Chunk.exportOrthophoto()` to `Chunk.exportOrthomosaic()`
- Removed `OrthoSurface` and `PointsSource` enums
- Removed `PointCloud.groups` attribute
- Removed `Chunk.camera_offset` attribute

3.30 PhotoScan version 1.1.1

- Added `Chunk.exportModelTiles()` method
- Added `noparity` parameter to `Chunk.detectMarkers()` method
- Added `blockw` and `blockh` parameters to `Chunk.exportPoints()` method

3.31 PhotoScan version 1.1.0

- Added `CameraOffset` and `ConsolePane` classes

- Added CameraGroup, CameraReference, ChunkTransform, DepthMap, DepthMaps, MarkerReference, MarkerProjection, Mask, PointCloudGroups, PointCloudTrack, PointCloudTracks, ScalebarReference, Thumbnail classes
- Added Chunk.key, Sensor.key, Camera.key, Marker.key and Scalebar.key attributes
- Added Application.console attribute
- Added Application.addMenuSeparator() method
- Added Chunk.importMasks() method
- Added Chunk.addSensor(), Chunk.addCameraGroup(), Chunk.addCamera(), Chunk.addMarker(), Chunk.addScalebar() methods
- Added Chunk.addPhotos(), Chunk.addFrame() methods
- Added Chunk.master_channel and Chunk.camera_offset attributes
- Added Calibration.error() method
- Added Matrix.mulp() and Matrix.mulv() methods
- Added DenseCloud.assignClass(), DenseCloud.assignClassToSelection(), DenseCloud.removePoints() methods
- Added DenseCloud.classifyGroundPoints() and DenseCloud.selectMaskedPoints() methods
- Added Model.renderNormalMap() method
- Added DenseCloud.meta and Model.meta attributes
- Added PointCloud.tracks, PointCloud.groups attributes
- Added Image.tostring() and Image.fromstring() methods
- Added Image.channels property
- Added U16 data type support in Image class
- Added classes parameter to Chunk.buildModel() method
- Added crop_borders parameter to Chunk.exportDem() method
- Added chunk parameter to Document.addChunk() method
- Added format parameter to Calibration.save() and Calibration.load() methods
- Moved OpenCL settings into Application class
- Converted string constants to enum objects
- Removed Cameras, Chunks, DenseClouds, Frame, Frames, GroundControl, GroundControlLocations, GroundControlLocation, Markers, MarkerPositions, Models, Scalebars, Sensors classes

3.32 PhotoScan version 1.0.0

- Added DenseCloud and DenseClouds classes
- Added Chunk.exportModel() and Chunk.importModel() methods
- Added Chunk.estimateImageQuality() method
- Added Chunk.buildDenseCloud() and Chunk.smoothModel() methods
- Added Photo.thumbnail() method

- Added Image.resize() method
- Added Application.enumOpenCLDevices() method
- Added Utils.estimateImageQuality() method
- Added Camera.meta, Marker.meta, Scalebar.meta and Photo.meta attributes
- Added Chunk.dense_cloud and Chunk.dense_clouds attributes
- Added page parameter to Model.setTexture() and Model.texture() methods
- Added shortcut parameter to Application.addItem() method
- Added absolute_paths parameter to Document.save() method
- Added fit_f, fit_cxycy, fit_k1k2k3 and fit_k4 parameters to Chunk.optimizePhotos() method
- Changed parameters of Chunk.buildModel() and Chunk.buildTexture() methods
- Changed parameters of Chunk.exportPoints() method
- Changed parameters of Model.save() method
- Changed return value of Chunks.add() method
- Removed Chunk.buildDepth() method
- Removed Camera.depth() and Camera.setDepth() methods
- Removed Frame.depth() and Frame.setDepth() methods
- Removed Frame.depth_calib attribute

3.33 PhotoScan version 0.9.1

- Added Sensor, Scalebar and MetaData classes
- Added Camera.sensor attribute
- Added Chunk.sensors attribute
- Added Calibration.width, Calibration.height and Calibration.k4 attributes
- Added Chunk.refineMatches() method
- Added Model.area() and Model.volume() methods
- Added Model.renderDepth(), Model.renderImage() and Model.renderMask() methods
- Added Chunk.meta and Document.meta attributes
- Added Calibration.project() and Calibration.unproject() methods
- Added Application.addItem() method
- Added Model.closeHoles() and Model.fixTopology() methods

3.34 PhotoScan version 0.9.0

- Added Camera, Frame and CoordinateSystem classes
- Added Chunk.exportReport() method
- Added Chunk.trackMarkers() and Chunk.detectMarkers() methods

- Added `Chunk.extractFrames()` and `Chunk.removeFrames()` methods
- Added `Chunk.matchPhotos()` method
- Added `Chunk.buildDepth()` and `Chunk.resetDepth()` methods
- Added `Chunk.cameras` property
- Added `Utils.createDifferenceMask()` method
- Revised `Chunk.alignPhotos()` method
- Revised `Chunk.buildPoints()` method
- Revised `Chunk.buildModel()` method
- Removed `Photo` class (deprecated)
- Removed `GeoProjection` class (deprecated)
- Removed `Chunk.photos` property (deprecated)

3.35 PhotoScan version 0.8.5

- Added `Chunk.fix_calibration` property
- Added `Chunk.exportCameras()` method
- Added `Chunk.exportPoints()` method for dense/sparse point cloud export
- Added `accuracy_cameras`, `accuracy_markers` and `accuracy_projections` properties to the `GroundControl` class
- Added `Image.undistort()` method
- Added `PointCloudPoint.selected` and `PointCloudPoint.valid` properties
- Added `GeoProjection.authority` property
- Added `GeoProjection.init()` method
- Moved `GroundControl.optimize()` method to `Chunk.optimize()`
- Removed “`fix_calibration`” parameter from `Chunk.alignPhotos()` method
- Removed `GeoProjection.epsg` property

3.36 PhotoScan version 0.8.4

- Added `GroundControl.optimize()` method
- Command line scripting support removed

3.37 PhotoScan version 0.8.3

Initial version of PhotoScan Python API

m

Metashape, 5